

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****Product information**

Product Name : Diesel HV  
Material : 1118978, 1118977

**Company** : Chevron Phillips Chemical Company LP  
Specialty Chemicals  
10001 Six Pines Drive  
The Woodlands, TX 77380

**Emergency telephone:****Health:**

866.442.9628 (North America)  
1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)  
Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090  
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
Mexico CHEMTREC 01-800-681-9531 (24 hours)  
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600  
Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group  
E-mail address : SDS@CPChem.com  
Website : www.CPChem.com

**SECTION 2: Hazards identification****Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

**Classification**

: Acute toxicity, Category 4, Inhalation  
Skin irritation, Category 2  
Carcinogenicity, Category 2  
Specific target organ toxicity - repeated exposure, Category 2,  
Bone marrow, Liver, thymus  
Aspiration hazard, Category 1

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

**Labeling**

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H304: May be fatal if swallowed and enters airways.  
 H315: Causes skin irritation.  
 H332: Harmful if inhaled.  
 H351: Suspected of causing cancer.  
 H373: May cause damage to organs (Bone marrow, Liver, thymus) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
 P264 Wash skin thoroughly after handling.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P331 Do NOT induce vomiting.  
 P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Carcinogenicity:****IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 3: Composition/information on ingredients**

Molecular formula

: UVCB

Component	CAS-No.	Weight %
Diesel fuel, no. 4	68476-31-3	100

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

**SECTION 4: First aid measures**

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**SECTION 5: Firefighting measures**

- Flash point : 155.3°C (311.5°F)  
Method: closed cup
- Autoignition temperature : No data available
- Suitable extinguishing media : Dry chemical. Carbon dioxide (CO<sub>2</sub>). Alcohol-resistant foam.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Fire and explosion protection : Normal measures for preventive fire protection.
- Hazardous decomposition products : Hydrocarbons. Carbon oxides.

**SECTION 6: Accidental release measures**

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation.

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

**SECTION 7: Handling and storage****Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.

**Storage**

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****Ingredients with workplace control parameters****US**

Components	Basis	Value	Control parameters	Note
Diesel fuel, no. 4	ACGIH	TWA	100 mg/m <sup>3</sup>	A3, Skin, Inhalable fraction and vapor

A3 Confirmed animal carcinogen with unknown relevance to humans  
Skin Danger of cutaneous absorption

**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

- Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Organic Vapors, Dusts and Mists. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Protective suit. Safety shoes.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

- Form : liquid
- Physical state : liquid
- Color : Pale yellow to brown (if undyed), red to purple (dyed)
- Odor : Mild

**Safety data**

- Flash point : 155.3°C (311.5°F)  
Method: closed cup
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Oxidizing properties : No
- Autoignition temperature : No data available
- Molecular formula : UVCB
- Molecular weight : Not applicable
- pH : Not applicable

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

Pour point	: No data available
Boiling point/boiling range	: 299.6-361.4°C (571.3-682.5°F)
Vapor pressure	: No data available
Relative density	: 0.8598 at 16 °C (60 °F)
Density	: 0.75 - 0.90 g/cm3
Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: 7.15 cSt at 40°C (104°F)
Relative vapor density	: No data available
Evaporation rate	: No data available
Percent volatile	: > 99 %

**SECTION 10: Stability and reactivity**

<b>Reactivity</b>	: Stable under recommended storage conditions.
<b>Chemical stability</b>	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
<b>Possibility of hazardous reactions</b>	
<b>Hazardous reactions</b>	: Hazardous reactions: Hazardous polymerization does not occur.  Hazardous reactions: Vapors may form explosive mixture with air.
<b>Conditions to avoid</b>	: Heat, flames and sparks.
<b>Materials to avoid</b>	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
<b>Hazardous decomposition products</b>	: Hydrocarbons Carbon oxides
<b>Other data</b>	: No decomposition if stored and applied as directed.

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

**SECTION 11: Toxicological information****Acute oral toxicity**

Diesel fuel, no. 4 : LD50: 7,600 mg/kg  
Species: Rat  
Sex: male and female  
Method: OECD Test Guideline 420

**Acute inhalation toxicity**

Diesel fuel, no. 4 : LC50: 4.1 mg/l  
Exposure time: 4 h  
Species: Rat  
Sex: male and female  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

**Acute dermal toxicity**

Diesel fuel, no. 4 : LD50: > 4,300 mg/kg  
Species: Rabbit  
Sex: male and female  
Method: OECD Test Guideline 434

**Skin irritation**

Diesel fuel, no. 4 : Skin irritation

**Eye irritation**

Diesel fuel, no. 4 : No eye irritation

**Sensitization**

Diesel fuel, no. 4 : Did not cause sensitization on laboratory animals.

**Repeated dose toxicity**

Diesel fuel, no. 4 : Species: Rat, male and female  
Sex: male and female  
Application Route: Inhalation  
Dose: 250, 750, 1500 mg/L  
Exposure time: 13 wk  
Number of exposures: Twice per wk  
NOEL: > 1.71 mg/l > 1700 mg/m3  
Method: OECD Test Guideline 413

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

Species: Rat, male and female  
 Sex: male and female  
 Application Route: Dermal  
 Dose: 30, 125, 500 mg/kg/d  
 Exposure time: 13 wk  
 Number of exposures: 5 d/wk  
 NOEL: 30 mg/kg  
 Method: OECD Guideline 411  
 Target Organs: Thymus, Liver, Bone marrow

**Diesel HV****Aspiration toxicity**

: May be fatal if swallowed and enters airways.

**CMR effects**

Diesel fuel, no. 4

: Carcinogenicity: Limited evidence of carcinogenicity in animal studies  
 Mutagenicity: In vitro tests showed mutagenic effects which were not observed with in vivo test.  
 Teratogenicity: Animal testing did not show any effects on fetal development.  
 Reproductive toxicity: No adverse effects expected

**Diesel HV****Further information**

: Solvents may degrease the skin.

**SECTION 12: Ecological information****Toxicity to fish**

Diesel fuel, no. 4

: LL50: 21 mg/l  
 Exposure time: 96 h  
 Species: Oncorhynchus mykiss (rainbow trout)  
 semi-static test Method: OECD Test Guideline 203

**Toxicity to daphnia and other aquatic invertebrates**

Diesel fuel, no. 4

: 68 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 static test Method: OECD Test Guideline 202

**Toxicity to algae**

Diesel fuel, no. 4

: EL50: 2.9 mg/l  
 Exposure time: 72 h  
 Species: Pseudokirchneriella subcapitata (algae)  
 static test Method: OECD Test Guideline 201

**Biodegradability**

Diesel fuel, no. 4

: aerobic



**Diesel HV**

Version 1.1

Revision Date 2021-08-12

35 %  
 Expected to be inherently biodegradable.  
 Information given is based on data obtained from similar substances.

**Bioaccumulation**

Diesel fuel, no. 4 : The product may be accumulated in organisms.

**Mobility**

Diesel fuel, no. 4 : No data available

**Results of PBT assessment**

Diesel fuel, no. 4 : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : Toxic to aquatic life with long lasting effects.

**Ecotoxicology Assessment****Short-term (acute) aquatic hazard**

Diesel fuel, no. 4 : Toxic to aquatic life.

**Long-term (chronic) aquatic hazard**

Diesel fuel, no. 4 : Toxic to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, (155.3°C), MARINE POLLUTANT, (DIESEL FUEL)

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIESEL FUEL), 9, III

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, (-), ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

**Maritime transport in bulk according to IMO instruments****SECTION 15: Regulatory information****National legislation**

**SARA 311/312 Hazards** : Acute toxicity (any route of exposure)  
 Skin corrosion or irritation  
 Carcinogenicity  
 Specific target organ toxicity (single or repeated exposure)  
 Aspiration hazard

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable : This material does not contain any components with a SARA

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

Quantity 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**US State Regulations**

Pennsylvania Right To Know : Diesel fuel, no. 4 - 68476-31-3

**Notification status**

Europe REACH : Not in compliance with the inventory  
 Switzerland CH INV : On the inventory, or in compliance with the inventory  
 United States of America (USA) : On or in compliance with the active portion of the TSCA inventory  
 Canada DSL : All components of this product are on the Canadian

**Diesel HV**


Version 1.1

Revision Date 2021-08-12

	DSL
Other AIIC	: On the inventory, or in compliance with the inventory
New Zealand NZIoC	: Not in compliance with the inventory
Japan ENCS	: Not in compliance with the inventory
Korea KECI	: Not in compliance with the inventory
Philippines PICCS	: Not in compliance with the inventory
Taiwan TCSI	: On the inventory, or in compliance with the inventory
China IECSC	: Not in compliance with the inventory

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 2  
Fire Hazard: 1  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : CPC00523

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic

**Diesel HV**

Version 1.1

Revision Date 2021-08-12

GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		