



## Soltrol® 125H Isoparaffin Solvent

Version 1.2

Revision Date 2022-11-15

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### Product information

Product Name : Soltrol® 125H Isoparaffin Solvent  
 Material : 1121507, 1121506, 1121505, 1121504, 1120020

**Company** : Chevron Phillips Chemical Company LP  
 10001 Six Pines Drive  
 The Woodlands, TX 77380

#### Emergency telephone:

##### Health:

866.442.9628 (North America)  
 1.832.813.4984 (International)

##### Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)  
 Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090  
 Mexico CHEMTREC 01-800-681-9531 (24 hours)  
 South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600  
 Argentina: +(54)-1159839431  
 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
 Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)  
 Belgium: 070 245 245 (24 hours/day, 7 days/week)  
 Bulgaria: +359 2 9154 233  
 Croatia: +3851 2348 342 (24 hours/day, 7 days/week)  
 Cyprus: 1401  
 Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402  
 Denmark: Danish Poison Center (Gifftlinjen): +45 8212 1212  
 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
 Finland: 0800 147 111 09 471 977 (24 hours/day)  
 France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)  
 Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
 Greece: (0030) 2107793777 (24 hours/day, 7 days/week)  
 Hungary: +36-80-201-199 (24 hours/day, 7 days/week)  
 Iceland: 543 2222 (24 hours/day, 7 days/week)  
 Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
 Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
 Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic  
 Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371  
 67042473. (24 hours.)  
 Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
 Lithuania: +370 (85) 2362052

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)  
 Malta: +356 2395 2000  
 The Netherlands: NVIC: +31 (0)88 755 8000  
 Norway: 22 59 13 00 (24 hours/day, 7 days/week)  
 Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
 Portugal: CIAV phone number: +351 800 250 250  
 Romania: +40213183606  
 Slovakia: +421 2 5477 4166  
 Slovenia: Phone number: 112  
 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)  
 Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group  
 E-mail address : SDS@CPChem.com  
 Website : www.CPChem.com

**SECTION 2: Hazards identification****Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

**Classification**

: Flammable liquids, Category 3  
 Specific target organ toxicity - single exposure, Category 3,  
 Central nervous system  
 Aspiration hazard, Category 1

**Labeling**

Symbol(s) : 

Signal Word : Danger

Hazard Statements : H226: Flammable liquid and vapor.  
 H304: May be fatal if swallowed and enters airways.  
 H336: May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**  
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
 P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

shower.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Carcinogenicity:****IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 3: Composition/information on ingredients**

Synonyms : Isoparaffins  
Aliphatic hydrocarbon  
Isoalkanes

Molecular formula : UVCB

Component	CAS-No.	Weight %
C12-C14 Isoalkanes	68551-19-9	0 - 100
C9-C11 Isoalkanes	68551-16-6	0 - 100

**SECTION 4: First aid measures**

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

**SECTION 5: Firefighting measures**

Flash point	:	48°C (118°F) Method: Tag closed cup
Autoignition temperature	:	336°C (637°F)
Suitable extinguishing media	:	Alcohol-resistant foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical.
Unsuitable extinguishing media	:	High volume water jet.
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Fire and explosion protection	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

**SECTION 6: Accidental release measures**

Personal precautions	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7: Handling and storage****Handling**

Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see
-------------------------	---	--

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

**Storage**

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
C12-C14 Isoalkanes	Manufacturer	TWA	1,200 mg/m3	RCP,
C9-C11 Isoalkanes	Manufacturer	TWA	1,200 mg/m3	RCP,

RCP Reciprocal Calculation Procedure

**US**

Components	Basis	Value	Control parameters	Note
------------	-------	-------	--------------------	------

**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. Full-Face Air-Purifying Respirator for Organic Vapors, Dusts and Mists. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

- Form : liquid  
 Physical state : liquid  
 Color : Colorless at room temperature  
 Odor : Mild, Hydrocarbon

**Safety data**

- Flash point : 48°C (118°F)  
 Method: Tag closed cup
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Oxidizing properties : no
- Autoignition temperature : 336°C (637°F)
- Molecular formula : UVCB
- Molecular weight : Not applicable
- pH : No data available
- Freezing point : No data available
- Pour point : No data available
- Boiling point/boiling range : 178-188°C (352-370°F)
- Vapor pressure : 1.00 MMHG  
 at 20°C (68°F)

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

Relative density	: 0.76 at 15.6 °C (60.1 °F)
Density	: 756.1 g/l
Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: 1.12 cSt at 38°C (100°F)
Relative vapor density	: 3 (Air = 1.0)
Evaporation rate	: 1
Percent volatile	: > 99 %

**SECTION 10: Stability and reactivity**

<b>Reactivity</b>	: Stable under recommended storage conditions.
<b>Chemical stability</b>	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
<b>Possibility of hazardous reactions</b>	
<b>Hazardous reactions</b>	: Further information: No decomposition if stored and applied as directed.  Hazardous reactions: Vapors may form explosive mixture with air.
<b>Conditions to avoid</b>	: Heat, flames and sparks.
<b>Materials to avoid</b>	: Strong oxidizing agents.
<b>Other data</b>	: No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information**

<b>Soltrol® 125H Isoparaffin Solvent</b>	
<b>Acute oral toxicity</b>	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
<b>Soltrol® 125H Isoparaffin Solvent</b>	
<b>Acute inhalation toxicity</b>	: Acute toxicity estimate: > 4.9 mg/l

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

Exposure time: 4 h  
 Test atmosphere: vapor  
 Method: Calculation method  
 An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.  
 anhydrous substance

**Soltrol® 125H Isoparaffin Solvent**

**Acute dermal toxicity** : Acute toxicity estimate: > 2,000 mg/kg  
 Method: Calculation method

**Soltrol® 125H Isoparaffin Solvent**

**Skin irritation** : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin. Information given is based on data obtained from similar substances.

**Soltrol® 125H Isoparaffin Solvent**

**Eye irritation** : Vapors may cause irritation to the eyes, respiratory system and the skin. Information given is based on data obtained from similar substances.

**Soltrol® 125H Isoparaffin Solvent**

**Sensitization** : Did not cause sensitization on laboratory animals. Information given is based on data obtained from similar substances.

**Repeated dose toxicity**

C12-C14 Isoalkanes : Species: Rat, male and female  
 Sex: male and female  
 Application Route: oral gavage  
 Dose: 100, 500, 1000 mg/kg/d  
 Exposure time: 13 wk  
 Number of exposures: daily  
 NOEL: > 1000 mg/kg/d  
 Method: OECD Test Guideline 408  
 No adverse effects expected  
 Information given is based on data obtained from similar substances.

Species: Rat, male and female  
 Sex: male and female  
 Application Route: Inhalation  
 Dose: 2600, 5200, 10400 mg/m<sup>3</sup>  
 Exposure time: 90 d  
 Number of exposures: 6 h/d; 5d/wk  
 NOEL: > 10400 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 413  
 No adverse effects expected  
 Information given is based on data obtained from similar substances.

C9-C11 Isoalkanes

Species: Rat, male and female  
 Sex: male and female  
 Application Route: Inhalation  
 Dose: 0, 2600, 5200, 10400 mg/3  
 Exposure time: 13 wk



**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

Number of exposures: 6 h/d, 5 d/wk  
 NOEL: > 10,400 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 413  
 No significant adverse effects were reported  
 Information given is based on data obtained from similar substances.

**Genotoxicity in vitro**

C12-C14 Isoalkanes : Test Type: Ames test  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 471  
 Result: negative

Test Type: Mouse lymphoma assay  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 476  
 Result: negative

Test Type: Sister Chromatid Exchange Assay  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 479  
 Result: negative

C9-C11 Isoalkanes Test Type: E. Coli bacterial reverse mutation assay  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

Test Type: Ames test  
 Metabolic activation: with and without metabolic activation  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

Test Type: Bacterial DNA repair test  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

**Genotoxicity in vivo**

C12-C14 Isoalkanes : Test Type: dominant lethal test  
 Species: Rat  
 Route of Application: Intraperitoneal injection  
 Dose: 300, 900 ppm  
 Method: OECD Test Guideline 478  
 Remarks: Information given is based on data obtained from similar substances.

C9-C11 Isoalkanes Test Type: Dominant lethal assay  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

Test Type: Mouse micronucleus assay  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

**Developmental Toxicity**

C12-C14 Isoalkanes : Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 400, 1200 ppm  
 Exposure time: 6h  
 Test period: GD 6-15  
 NOAEL Teratogenicity: 1200 ppm  
 NOAEL Maternal: 1200 ppm  
 Information given is based on data obtained from similar substances.

Species: Rat  
 Application Route: Inhalation  
 Dose: 300, 900 ppm  
 Exposure time: 6h  
 Test period: GD 6-15  
 NOAEL Teratogenicity:  $\geq$  900 ppm  
 NOAEL Maternal:  $\geq$  900 ppm  
 Information given is based on data obtained from similar substances.

C9-C11 Isoalkanes : Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 291, 817 ppm  
 Number of exposures: 6 h/d  
 Test period: GD 6-15  
 NOAEL Teratogenicity:  $>$  817 ppm  
 NOAEL Maternal:  $>$  817 ppm

**Soltrol® 125H Isoparaffin Solvent**

**Aspiration toxicity** : May be fatal if swallowed and enters airways.

**CMR effects**

C12-C14 Isoalkanes : Carcinogenicity: Not available  
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects  
 Teratogenicity: Animal testing did not show any effects on fetal development.  
 Reproductive toxicity: Animal testing did not show any effects on fertility.

**Soltrol® 125H Isoparaffin Solvent**

**Further information** : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

**SECTION 12: Ecological information**

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

**Toxicity to fish**

C12-C14 Isoalkanes : LL50: > 1,000 mg/l  
Exposure time: 96 h  
Species: Oncorhynchus mykiss (rainbow trout)  
semi-static test Method: OECD Test Guideline 203  
Information given is based on data obtained from similar substances.

C9-C11 Isoalkanes LL50: 3.6 mg/l  
Exposure time: 96 h  
Species: Oncorhynchus mykiss (rainbow trout)  
semi-static test Method: OECD Test Guideline 203  
Information given is based on data obtained from similar substances.

**Toxicity to daphnia and other aquatic invertebrates**

C12-C14 Isoalkanes : EL50: > 1,000 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)  
static test Method: OECD Test Guideline 202  
Information given is based on data obtained from similar substances.

C9-C11 Isoalkanes EL50: 22 - 46 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)  
static test Method: OECD Test Guideline 202  
Information given is based on data obtained from similar substances.

**Toxicity to algae**

C12-C14 Isoalkanes : EL50: > 1,000 mg/l  
Exposure time: 72 h  
Species: Pseudokirchneriella subcapitata (green algae)  
Growth inhibition Method: OECD Test Guideline 201  
Information given is based on data obtained from similar substances.

C9-C11 Isoalkanes ErL50: > 1,000 mg/l  
Exposure time: 72 h  
Species: Pseudokirchneriella subcapitata (algae)  
static test Method: OECD Test Guideline 201  
Information given is based on data obtained from similar substances.

**Toxicity to fish (Chronic toxicity)**

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

C12-C14 Isoalkanes	: No data available:
C9-C11 Isoalkanes	NOELR: 0.132 mg/ Species: Oncorhynchus mykiss (rainbow trout) Method: QSAR modeled data
Biodegradability	: This material is not expected to be readily biodegradable. Expected to be inherently biodegradable.
Elimination information (persistence and degradability)	
Bioaccumulation	: The product may be accumulated in organisms.
Mobility	
C12-C14 Isoalkanes	: immobile
C9-C11 Isoalkanes	: The product will be dispersed amongst the various environmental compartments (soil/ water/ air).
Results of PBT assessment	
C12-C14 Isoalkanes	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information	: Toxic to aquatic life with long lasting effects.
<b>Ecotoxicology Assessment</b>	
Short-term (acute) aquatic hazard	
C12-C14 Isoalkanes	: This material is not expected to be harmful to aquatic organisms.
C9-C11 Isoalkanes	: Toxic to aquatic life.
Long-term (chronic) aquatic hazard	
C12-C14 Isoalkanes	: This material is not expected to be harmful to aquatic organisms.
C9-C11 Isoalkanes	: Toxic to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
---------	--

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III, (48 °C c.c.), MARINE POLLUTANT, (C9-C11 ISOALKANES)

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS, (C9-C11 ISOALKANES)

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

30, UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS, (C9-C11 ISOALKANES)

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS, (C9-C11 ISOALKANES)

**Maritime transport in bulk according to IMO instruments**

**SECTION 15: Regulatory information****National legislation**

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

Aspiration hazard  
Specific target organ toxicity (single or repeated exposure)

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**US State Regulations**

Pennsylvania Right To Know

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

: C12-C14 Isoalkanes - 68551-19-9  
 C9-C11 Isoalkanes - 68551-16-6

California Prop. 65  
 Components


: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

**Notification status**

Europe REACH	:	Not in compliance with the inventory
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On or in compliance with the active portion of the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Other AIIIC	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).
Philippines PICCS	:	Not in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 1  
 Fire Hazard: 2  
 Reactivity Hazard: 0

**Further information**

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Soltrol® 125H Isoparaffin Solvent**

Version 1.2

Revision Date 2022-11-15

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate