



## Toluene Standardization Fuel 96.9

Version 1.7

Revision Date 2023-08-03

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

##### Product information

Product Name : Toluene Standardization Fuel 96.9  
 Material : 1024367, 1024366, 1024365, 1024364

##### EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
Toluene	108-88-3 203-625-9 601-021-00-3	Chevron Phillips Chemicals International NV 01-2119471310-51-0116
Toluene	108-88-3 203-625-9 601-021-00-3	Chevron Phillips Chemical Company LP 01-2119471310-51-0116
2,2,4-Trimethylpentane (Isooctane)	540-84-1 208-759-1 601-009-00-8	Chevron Phillips Chemicals International NV 01-2119457965-22-0002
2,2,4-Trimethylpentane (Isooctane)	540-84-1 208-759-1 601-009-00-8	Chevron Phillips Chemical Company LP 01-2119457965-22-0013

#### 1.2

##### Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses : Fuel  
 Supported

#### 1.3

##### Details of the supplier of the safety data sheet

**Company** : Chevron Phillips Chemical Company LP  
 Specialty Chemicals  
 10001 Six Pines Drive  
 The Woodlands, TX 77380

**Local** : Chevron Phillips Chemicals International N.V.  
 Airport Plaza (Stockholm Building)  
 Leonardo Da Vincilaan 19  
 1831 Diegem  
 Belgium

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

SDS Requests: (800) 852-5530  
 Responsible Party: Product Safety Group  
 Email:sds@cpchem.com

**1.4****Emergency telephone:****Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic

Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group  
 E-mail address : SDS@CPChem.com  
 Website : www.CPChem.com

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

**SECTION 2: Hazards identification****2.1****Classification of the substance or mixture  
REGULATION (EC) No 1272/2008**

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

**2.2****Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements	:	H225	Highly flammable liquid and vapor.
		H304	May be fatal if swallowed and enters airways.
		H315	Causes skin irritation.
		H336	May cause drowsiness or dizziness.
		H361d	Suspected of damaging the unborn child.
		H373	May cause damage to organs through prolonged or repeated exposure.
H410		Very toxic to aquatic life with long lasting effects.	

Precautionary Statements	:	<b>Prevention:</b>	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P260	Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
		<b>Response:</b>	
		P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.		

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

P370 + P378

In case of fire: Use dry sand, dry chemical  
or alcohol-resistant foam to extinguish.

P391

Collect spillage.

Hazardous ingredients which must be listed on the label:

- 108-88-3            Toluene
- 142-82-5            n-Heptane
- 540-84-1            2,2,4-Trimethylpentane (Isooctane)

**2.3****Other hazards**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.1 - 3.2****Substance or Mixture**

Synonyms : Reference Fuel

Molecular formula : Mixture

**Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]	Specific Conc. Limits, M-factors and ATEs
<b>Toluene</b>	<b>108-88-3</b> <b>203-625-9</b> 601-021-00-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	73 - 75	
n-Heptane	142-82-5 205-563-8 601-008-00-2	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	20 - 22	
2,2,4-	540-84-1	Flam. Liq. 2; H225	4 - 6	

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

Trimethylpentane (Isooctane)	208-759-1 601-009-00-8	Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		
---------------------------------	---------------------------	--	--	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures****4.1****Description of first-aid measures**

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**4.2 Most important symptoms and effects, both acute and delayed****Notes to physician**

- Symptoms : No data available.
- Risks : No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Treatment : No data available.

**SECTION 5: Firefighting measures**

- Flash point : 4°C (39°F)  
Method: closed cup  
estimated

- Autoignition temperature : 528,9°C (984,0°F)

**5.1****Extinguishing media**

- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

**5.2****Special hazards arising from the substance or mixture**

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

**5.3****Advice for firefighters**

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition products : Hydrocarbons. Carbon oxides.

**SECTION 6: Accidental release measures****6.1****Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

**6.2****Environmental precautions**

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3****Methods and materials for containment and cleaning up**

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**6.4****Reference to other sections**

Reference to other sections : For personal protection see section 8. For disposal considerations see section 13.

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

**SECTION 7: Handling and storage****7.1****Precautions for safe handling  
Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

**7.2****Conditions for safe storage, including any incompatibilities****Storage**

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****8.1****Control parameters  
Ingredients with workplace control parameters****SK**

Zložky	Podstata	Hodnota	Kontrolné parametre	Poznámka
Toluene	SK OEL	NPEL priemerný	50 ppm, 192 mg/m <sup>3</sup>	K,
	SK OEL	NPEL krátkodobý	100 ppm, 384 mg/m <sup>3</sup>	K,
n-heptane	SK OEL	NPEL priemerný	500 ppm, 2.085 mg/m <sup>3</sup>	
2,2,4-Trimethylpentane (Isooctane)	SK OEL	NPEL krátkodobý	300 ppm, 1.400 mg/m <sup>3</sup>	
	SK OEL	NPEL priemerný	200 ppm, 900 mg/m <sup>3</sup>	

K Znamená, že faktor môže byť ľahko absorbovaný kožou. Niektoré faktory, ktoré ľahko prenikajú kožou, môžu spôsobovať až smrteľné otravy, často bez varovných príznakov (napr. anilín, nitrobenzén, nitroglykol, fenoly a pod.). Pri látkach s významným prienikom cez kožu, či už v podobe kvapalín alebo pár, je osobitne dôležité zabrániť kožnému kontaktu.

**SI**

Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
Toluene	SI OEL	MV	50 ppm, 192 mg/m <sup>3</sup>	RD-2, K,
	SI OEL	KTV	100 ppm, 384 mg/m <sup>3</sup>	RD-2, K,
n-heptane	SI OEL	MV	500 ppm, 2.085 mg/m <sup>3</sup>	
	SI OEL	KTV	500 ppm, 2.085 mg/m <sup>3</sup>	
2,2,4-Trimethylpentane (Isooctane)	SI OEL	MV	500 ppm, 2.400 mg/m <sup>3</sup>	
	SI OEL	KTV	1.000 ppm, 4.800 mg/m <sup>3</sup>	

K Lastnosť lažjega prehajanja snovi v organizem skozi kožo  
RD-2 Strupeno za rozmnoževanje - lahko škoduje nerojenemu otroku - kategorija 2

## Toluene Standardization Fuel 96.9

Version 1.7

Revision Date 2023-08-03

## SE

Beståndsdelar	Grundval	Värde	Kontrollparametrar	Anmärkning
Toluene	SE AFS	NGV	50 ppm, 192 mg/m <sup>3</sup>	H,
	SE AFS	KGV	100 ppm, 384 mg/m <sup>3</sup>	H,
n-heptane	SE AFS	NGV	200 ppm, 800 mg/m <sup>3</sup>	
	SE AFS	KGV	300 ppm, 1.200 mg/m <sup>3</sup>	V,
2,2,4-Trimethylpentane (Isooctane)	SE AFS	NGV	200 ppm, 900 mg/m <sup>3</sup>	
	SE AFS	KGV	300 ppm, 1.400 mg/m <sup>3</sup>	V,

H Ämnet kan lätt upptas genom huden.

V Vägledande kortidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas

## RU

Компоненты	Основа	Величина	Параметры контроля	Заметка
Толуол	RU OEL	ПДК	50 mg/m <sup>3</sup>	3,
	RU OEL	ПДК разовая	150 mg/m <sup>3</sup>	3,
	RU OEL	ПДК	50 mg/m <sup>3</sup>	3, пары и/или газы
	RU OEL	ПДК разовая	150 mg/m <sup>3</sup>	3, пары и/или газы
	RU OEL	ПДК	50 mg/m <sup>3</sup>	3, пары и/или газы
	RU OEL	ПДК разовая	150 mg/m <sup>3</sup>	3, пары и/или газы
н-гептан	RU OEL	ПДК	300 mg/m <sup>3</sup>	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m <sup>3</sup>	4, пары и/или газы
	RU OEL	ПДК	300 mg/m <sup>3</sup>	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m <sup>3</sup>	4, пары и/или газы
2,2,4-триметилпентан(изооктан)	RU OEL	ПДК	300 mg/m <sup>3</sup>	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m <sup>3</sup>	4, пары и/или газы
	RU OEL	ПДК	300 mg/m <sup>3</sup>	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m <sup>3</sup>	4, пары и/или газы

3 3 класс - опасные

4 4 класс - умеренно опасные

## RS

Компоненты	Основа	Величина	Параметры контроля	Заметка
Толуол	RS OEL	GVI	50 ppm, 192 mg/m <sup>3</sup>	K, EU**,
	RS OEL	KGVI	100 ppm, 384 mg/m <sup>3</sup>	K, EU**,
н-гептан	RS OEL	GVI	500 ppm, 2.085 mg/m <sup>3</sup>	EU*,

EU\* Substance mentioned in indicative exposure limit values in Directive 2000/39 / EC (first list)

EU\*\* Substance mentioned in indicative exposure limit values in Directive 2006/15 / EC (second list)

K This chemical substance can adversely affect the skin.

## RO

Componente	Sursă	Valoare	Parametri de control	Notă
Toluene	RO OEL	TWA	50 ppm, 192 mg/m <sup>3</sup>	R2, P,
	RO OEL	STEL	100 ppm, 384 mg/m <sup>3</sup>	R2, P,
n-heptane	RO OEL	TWA	500 ppm, 2.085 mg/m <sup>3</sup>	

P Contribuție substanțială la încărcarea totală din organism prin posibilă expunere cutanată.

R2 susceptibil de a dăuna fertilității

## PT

Componentes	Bases	Valor	Parâmetros de controlo	Nota
Toluene	PT OEL	VLE-MP	20 ppm,	P, A4,
	PT DL 305/2007	oito horas	50 ppm, 192 mg/m <sup>3</sup>	Cutânea,
	PT DL 305/2007	curta duração	100 ppm, 384 mg/m <sup>3</sup>	Cutânea,
n-heptane	PT DL 305/2007	oito horas	500 ppm, 2.085 mg/m <sup>3</sup>	
	PT OEL	VLE-MP	400 ppm,	
	PT OEL	VLE_CD	500 ppm,	

A4 Agente não classificável como carcinogénico no Homem.

Cutânea Uma notação cutânea atribuída ao valor limite de exposição profissional assinala a possibilidade de absorção significativa através de pele.

P Perigo de absorção cutânea

## PL

Składniki	Podstawa	Wartość	Parametry dotyczące kontroli	Uwaga
Toluene	PL NDS	NDS	100 mg/m <sup>3</sup>	
	PL NDS	NDSch	200 mg/m <sup>3</sup>	
n-heptane	PL NDS	NDS	1.200 mg/m <sup>3</sup>	
	PL NDS	NDSch	2.000 mg/m <sup>3</sup>	

## NO

Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
Toluene	FOR-2011-12-06-1358	GV	25 ppm, 94 mg/m <sup>3</sup>	H,
n-heptane	FOR-2011-12-06-1358	GV	200 ppm, 800 mg/m <sup>3</sup>	

H Kjemikalier som kan tas opp gjennom huden.



## Toluene Standardization Fuel 96.9

Version 1.7

Revision Date 2023-08-03

## NL

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Toluene	NL WG	TGG-8 uur	150 mg/m <sup>3</sup>	
	NL WG	TGG-15 min	384 mg/m <sup>3</sup>	
n-heptane	NL WG	TGG-8 uur	1.200 mg/m <sup>3</sup>	
	NL WG	TGG-15 min	1.600 mg/m <sup>3</sup>	

## MT

Components	Basis	Value	Control parameters	Note
Toluene	MT OEL	TWA	50 ppm, 192 mg/m <sup>3</sup>	Skin,
	MT OEL	STEL	100 ppm, 384 mg/m <sup>3</sup>	Skin,
n-Heptane	MT OEL	TWA	500 ppm, 2.085 mg/m <sup>3</sup>	

Skin A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.

## MK

Съставки	Основа	Стойност	Параметри на контрол	Бележка
Toluene	MK OEL	MV	50 ppm, 192 mg/m <sup>3</sup>	K,
n-heptane	MK OEL	MV	500 ppm, 2.085 mg/m <sup>3</sup>	
2,2,4-Trimethylpentane (Isooctane)	MK OEL	MV	500 ppm, 2.400 mg/m <sup>3</sup>	

K The properties of easier transport of substances into organism through (via) the skin

## LV

Sastāvdaļas	Bāze	Vērtība	Pārvaldības parametri	Piezīme
Toluene	LV OEL	AER 8 st	14 ppm, 50 mg/m <sup>3</sup>	Āda,
	LV OEL	AER īslaicīgā	40 ppm, 150 mg/m <sup>3</sup>	Āda,
n-heptane	LV OEL	AER 8 st	85 ppm, 350 mg/m <sup>3</sup>	
	LV OEL	AER īslaicīgā	500 ppm, 2.085 mg/m <sup>3</sup>	
2,2,4-Trimethylpentane (Isooctane)	LV OEL	AER 8 st	100 mg/m <sup>3</sup>	
	LV OEL	AER īslaicīgā	300 mg/m <sup>3</sup>	

Āda Āda

## LU

Composants	Base	Valeur	Paramètres de contrôle	Note
Toluene	LU OEL	TWA	50 ppm, 192 mg/m <sup>3</sup>	Peau,
	LU OEL	STEL	100 ppm, 384 mg/m <sup>3</sup>	Peau,
n-heptane	LU OEL	TWA	500 ppm, 2.085 mg/m <sup>3</sup>	

Peau Une pénétration cutanée s'ajoutant à l'inhalation réglementée est possible

## LT

Komponentai	Šaltinis	Vertė	Kontrolės parametrai	Pastaba
Toluene	LT OEL	IPRD	50 ppm, 192 mg/m <sup>3</sup>	O,
	LT OEL	TPRD	100 ppm, 384 mg/m <sup>3</sup>	O,
n-heptane	LT OEL	IPRD	500 ppm, 2.085 mg/m <sup>3</sup>	
	LT OEL	TPRD	750 ppm, 3.128 mg/m <sup>3</sup>	
2,2,4-Trimethylpentane (Isooctane)	LT OEL	IPRD	200 ppm, 900 mg/m <sup>3</sup>	
	LT OEL	TPRD	300 ppm, 1.400 mg/m <sup>3</sup>	

O pateikimas per nepažeistą odą

## IT

Componenti	Base	Valore	Parametri di controllo	Nota
Toluene	IT VLEP	TWA	50 ppm, 192 mg/m <sup>3</sup>	Cute,
n-heptane	IT VLEP	TWA	500 ppm, 2.085 mg/m <sup>3</sup>	

Cute La notazione che riporta il termine 'cute' per un valore limite di esposizione professionale, indica la possibilità di un assorbimento significativo attraverso la cute.

## IS

Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
Toluene	IS OEL	TWA	25 ppm, 94 mg/m <sup>3</sup>	H,
	IS OEL	STEL	50 ppm, 188 mg/m <sup>3</sup>	H,
n-heptane	IS OEL	TWA	200 ppm, 820 mg/m <sup>3</sup>	

H Skin notation

## IE

Components	Basis	Value	Control parameters	Note
Toluene	IE OEL	OELV - 8 hrs (TWA)	50 ppm, 192 mg/m <sup>3</sup>	Sk,
	IE OEL	OELV - 15 min (STEL)	100 ppm, 384 mg/m <sup>3</sup>	Sk,
n-Heptane	IE OEL	OELV - 8 hrs (TWA)	500 ppm, 2.085 mg/m <sup>3</sup>	

Sk Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body

## HU

Komponensek	Bázis	Érték	Ellenőrzési paraméterek	Megjegyzés
Toluene	HU OEL	AK-érték	190 mg/m <sup>3</sup>	R+T, b, EU2, i,
	HU OEL	CK-érték	380 mg/m <sup>3</sup>	R+T, b, EU2, i,

## Toluene Standardization Fuel 96.9

Version 1.7

Revision Date 2023-08-03

n-heptane	HU OEL	AK-érték	2.000 mg/m3	R, EU1,
2,2,4-Trimethylpentane (Isooctane)	HU OEL	AK-érték	2.350 mg/m3	R, i,
	HU OEL	CK-érték	4.700 mg/m3	R, i,

b Bőrön át is felszívódik. Az AK-értékek a veszélyes anyagoknak ezt a tulajdonságát, illetve az ebből származó expozíciót csak a levegőben megengedett koncentrációjuk mértékének megfelelően veszik figyelembe

EU1 2000/39/EK irányelvben közölt érték

EU2 2006/15/EK irányelvben közölt érték

i Ingerlő anyag (izgatja a bőrt, nyálkahártyát, szemet vagy mindhámat)

R Azok az anyagok, amelyek egészségkárosító hatása RÖVID expozíció hatására jelentkezik. Korrigált ÁK = ÁK x 8/a napi óraszám

R+T Azok az anyagok, amelyek RÖVID és TARTÓS expozíciója is egészségkárosodást okoz. Korrigált ÁK = ÁK x 8/a napi óraszám; Korrigált ÁK = ÁK x 40/a heti óraszám. A két faktor közül a szigorúbb (kisebb) értéket kell alkalmazni

## HR

Sastojci	Temelj	Vrijednost	Nadzorni parametri	Bilješka
Toluene	HR OEL	GVI	50 ppm, 192 mg/m3	koža,
	HR OEL	KGVI	100 ppm, 384 mg/m3	koža,
n-heptane	HR OEL	GVI	500 ppm, 2.085 mg/m3	koža,
	HR OEL		500 ppm, 2.000 mg/m3	

koža Razvrstana kao tvar koja nadražuje kožu (H315) ili je takva napomena navedena u direktivama

## GR

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
Toluene	GR OEL	TWA	50 ppm, 192 mg/m3	Δ,
	GR OEL	STEL	100 ppm, 384 mg/m3	Δ,
n-heptane	GR OEL	TWA	500 ppm, 2.000 mg/m3	
	GR OEL	STEL	500 ppm, 2.000 mg/m3	

Δ Η ένδειξη 'δέρμα' (Δ), η οποία επισημαίνει ορισμένους χημικούς παράγοντες του πίνακα της παρ. 1 του άρθρου 3, υπονοεί την πιθανή συμβολή στην συνολική έκθεση του εργαζόμενου και της ποσότητας αυτών των χημικών παραγόντων που απορροφάται διαμέσου του δέρματος κατά την άμεση επαφή μαζί τους.

## GB

Components	Basis	Value	Control parameters	Note
Toluene	GB EH40	TWA	50 ppm, 191 mg/m3	Sk,
	GB EH40	STEL	100 ppm, 384 mg/m3	Sk,
n-Heptane	GB EH40	TWA	500 ppm, 2.085 mg/m3	

Sk Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

## FR

Composants	Base	Valeur	Paramètres de contrôle	Note
Toluene	FR VLE	VME	20 ppm, 76,8 mg/m3	R2, Peau, VLR contraignantes,
	FR VLE	VLCT (VLE)	100 ppm, 384 mg/m3	R2, Peau, VLR contraignantes,
n-heptane	FR VLE	VME	400 ppm, 1.668 mg/m3	VLR contraignantes,
	FR VLE	VLCT (VLE)	500 ppm, 2.085 mg/m3	VLR contraignantes,
2,2,4-Trimethylpentane (Isooctane)	FR VLE	VME	1.000 mg/m3	Valeurs limites indicatives, Vapeur
	FR VLE	VLCT (VLE)	1.500 mg/m3	Valeurs limites indicatives, Vapeur

Peau Risque de pénétration percutanée  
R2 Toxique pour la reproduction de catégorie 2 - Substances préoccupantes en raison d'effets toxiques pour la reproduction possibles  
Valeurs limites indicatives Valeurs limites indicatives  
VLR Valeurs limites réglementaires contraignantes  
contraignantes

## FI

Aineosat	Peruste	Arvo	Valvontaa koskevat muuttujat	Huomautus
Toluene	FI OEL	HTP-arvot 8h	25 ppm, 81 mg/m3	melu, iho,
	FI OEL	HTP-arvot 15 min	100 ppm, 380 mg/m3	melu, iho,
n-heptane	FI OEL	HTP-arvot 8h	300 ppm, 1.200 mg/m3	
	FI OEL	HTP-arvot 15 min	500 ppm, 2.100 mg/m3	
	FI OEL	HTP-arvot 8h	300 ppm, 1.200 mg/m3	
	FI OEL	HTP-arvot 15 min	500 ppm, 2.100 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	FI OEL	HTP-arvot 8h	300 ppm, 1.400 mg/m3	
	FI OEL	HTP-arvot 15 min	380 ppm, 1.800 mg/m3	

iho Ihon läpi imeytyvien aineiden elimistöön joutuvia määriä ja elimistöön joutuneesta aineesta aiheutuvaa vaaraa ei voida näin ollen arvioida pelkästään ilmapitoisuuksien avulla. Tämän vuoksi näiden aineiden HTP-arvojen yhteyteen on huomautussarakkeeseen otettu ihon läpi imeytymisen osoittamiseksi merkintä 'iho'. Monet aineet, varsinkin voimakkaat hapot tai emäkset, voivat aiheuttaa iholle jouduttuaan ihon ärsyntymistä tai syöpymistä.

melu Melu: aineille, joiden tiedetään voimistavan melun haitallisia kuulovaikutuksia.

## ES

Componentes	Base	Valor	Parámetros de control	Nota
Toluene	ES VLA	VLA-ED	50 ppm, 192 mg/m3	vía dérmica,
	ES VLA	VLA-EC	100 ppm, 384 mg/m3	vía dérmica,

## Toluene Standardization Fuel 96.9

Version 1.7

Revision Date 2023-08-03

n-heptane	ES VLA	VLA-ED	500 ppm, 2.085 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	ES VLA	VLA-ED	300 ppm, 1.420 mg/m3	
via dérmica Via dérmica				

## EE

Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
Toluene	EE OEL	Piirnorm	50 ppm, 192 mg/m3	A,
	EE OEL	Lühiajalise kokkupuute piirnorm	100 ppm, 384 mg/m3	A,
n-heptane	EE OEL	Piirnorm	500 ppm, 2.085 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	EE OEL	Piirnorm	200 ppm, 900 mg/m3	
	EE OEL	Lühiajalise kokkupuute piirnorm	300 ppm, 1.400 mg/m3	

A Naha kaudu kergesti absorbeeruvad ained

## DK

Komponenter	Basis	Værdi	Kontrolparametre	Note
Toluene	DK OEL	GV	25 ppm, 94 mg/m3	H,
n-heptane	DK OEL	GV	200 ppm, 820 mg/m3	

H Betyder, at stoffet kan optages gennem huden.

## DE

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Toluene	DE TRGS 900	AGW	50 ppm, 190 mg/m3	H, Y,
n-heptane	DE TRGS 900	AGW	500 ppm, 2.100 mg/m3	

H Hautresorptiv

Y Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden

## CZ

Složky	Základ	Hodnota	Kontrolní parametry	Poznámka
Toluene	CZ OEL	PEL	192 mg/m3	I, D,
	CZ OEL	NPK-P	384 mg/m3	I, D,
n-heptane	CZ OEL	PEL	1.000 mg/m3	I,
	CZ OEL	NPK-P	2.000 mg/m3	I,

D Při expozici se významně uplatňuje pronikání faktoru kůži

I dráždí sliznice (oči, dýchací cesty), respektive kůži

## CY

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
Toluene	CY OEL	TWA	50 ppm, 192 mg/m3	
	CY OEL	STEL	100 ppm, 384 mg/m3	
n-heptane	CY OEL	TWA	500 ppm, 2.085 mg/m3	

## CH

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Toluene	CH SUVA	MAK-Wert	50 ppm, 190 mg/m3	OL, H, R2D, R2F, NIOSH, DFG, INRS, HSE, SSc,
	CH SUVA	KZGW	200 ppm, 760 mg/m3	OL, H, R2D, R2F, NIOSH, DFG, INRS, HSE, SSc,
n-heptane	CH SUVA	KZGW	400 ppm, 1.600 mg/m3	NIOSH,
	CH SUVA	MAK-Wert	400 ppm, 1.600 mg/m3	NIOSH,
2,2,4-Trimethylpentane (Isooctane)	CH SUVA	MAK-Wert	300 ppm, 1.400 mg/m3	NIOSH,
	CH SUVA	KZGW	600 ppm, 2.800 mg/m3	NIOSH,
	CH SUVA	MAK-Wert	100 ppm, 470 mg/m3	
	CH SUVA	KZGW	200 ppm, 940 mg/m3	

DFG Deutsche Forschungsgemeinschaft

H Vergiftung durch Hautresorption möglich; Bei Stoffen, welche die Haut leicht zu durchdringen vermögen, kann durch die zusätzliche Hautresorption die innere Belastung wesentlich höher werden als bei alleiniger Aufnahme durch die Atemwege.

HSE Health and Safety Executive (Occupational Medicine and Hygiene Laboratory)

INRS Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles

NIOSH National Institute for Occupational Safety and Health

OL lärmverstärkende Ototoxizität

R2D Stoffe, die möglicherweise beim Menschen reproduktionstoxisch sind; die Beeinträchtigung bezieht sich auf die Entwicklung.

R2F Stoffe, die möglicherweise beim Menschen reproduktionstoxisch sind; die Beeinträchtigung bezieht sich auf die Fruchtbarkeit oder Sexualität.

SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.

## BG

Съставки	Основа	Стойност	Параметри на контрол	Бележка
Toluene	BG OEL	TWA	50 ppm, 192 mg/m3	
	BG OEL	STEL	100 ppm, 384 mg/m3	
n-heptane	BG OEL	TWA	1.600 mg/m3	

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

**BE**

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Toluene	BE OEL	TGG 8 hr	20 ppm, 77 mg/m <sup>3</sup>	D.
	BE OEL	TGG 15 min	100 ppm, 384 mg/m <sup>3</sup>	D.
n-heptane	BE OEL	TGG 8 hr	400 ppm, 1.664 mg/m <sup>3</sup>	
	BE OEL	TGG 15 min	500 ppm, 2.085 mg/m <sup>3</sup>	

D Opname van het agens via de huid, de slijmvliezen of de ogen vormt een belangrijk deel van de totale blootstelling. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.

**AT**

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Toluene	AT OEL	MAK-TMW	50 ppm, 190 mg/m <sup>3</sup>	H.
	AT OEL	MAK-KZW	100 ppm, 380 mg/m <sup>3</sup>	H.
n-heptane	AT OEL	MAK-TMW	500 ppm, 2.000 mg/m <sup>3</sup>	
	AT OEL	MAK-KZW	2.000 ppm, 8.000 mg/m <sup>3</sup>	
2,2,4-Trimethylpentane (Isooctane)	AT OEL	MAK-TMW	300 ppm, 1.400 mg/m <sup>3</sup>	
	AT OEL	MAK-KZW	1.200 ppm, 5.600 mg/m <sup>3</sup>	

H Besondere Gefahr der Hautresorption

**Biological exposure indices****SK**

Názov látky	Č. CAS	Kontrolné parametre	Doba odberu vzorky	Aktualizácia
Toluene	108-88-3	toluén: 600 µg/l (Krv)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		toluén: 6.517 µmol.l-1 (Krv)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		kyselina hippurová: 2.401 mg/l (moč)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		kyselina hippurová: 13399 µmol.l-1 (moč)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		kyselina hippurová: 1600 mg/g kreatinínu (moč)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		kyselina hippurová: 1010 µmol/mmol kreatinínu (moč)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		o-krezol: 14.3 µmol.l-1 (moč)	Pri dlhodobej expozícii; po viacerých predchádzajúcich pracovných zmenáchKoniec vystavenia alebo pracovnej zmeny	2016-01-18
		o-krezol: 1.03 mg/g kreatinínu (moč)	Pri dlhodobej expozícii; po viacerých predchádzajúcich pracovných zmenáchKoniec vystavenia alebo pracovnej zmeny	2016-01-18
		o-krezol: 1.08 µmol/mmol kreatinínu (moč)	Pri dlhodobej expozícii; po viacerých predchádzajúcich pracovných zmenáchKoniec vystavenia alebo pracovnej zmeny	2016-01-18

## Toluene Standardization Fuel 96.9

Version 1.7

Revision Date 2023-08-03

		o-krezol: 1,5 mg/l (moč)	Pri dlhodobej expozícii; po viacerých predchádzajúcich pracovných zmenáchKoniec vystavenia alebo pracovnej zmeny	2016-01-18
--	--	--------------------------	--	------------

## SI

Ime snovi	Št. CAS	Parametri nadzora	Čas vzorčenja	Sprememba
Toluene	108-88-3	toluen: 600 µmol/l (Kri)	Ob koncu delovne izmene	2018-12-04
		o-krezol: 1,5 mg/l po hidrolizi (Urin)	pri dolgotrajni izpostavljenosti: ob koncu delovne izmene po več zaporednih delavnikihOb koncu delovne izmene	2018-12-04

## RO

Numele substanței	Nr. CAS	Parametri de control	Tim de prelevare a probei	Adus la zi
Toluene	108-88-3	o-cresol: 3 mg/l (Urină)	Sfârșit schimb	2018-08-17
		acid hipuric: 2 g/l (Urină)	Sfârșit schimb	2018-08-17

## PT

Nome da substância	No. CAS	Parâmetros de controlo	Tempo de amostra	Atualizada em
Toluene	108-88-3	Tolueno: 0,02 mg/l (Sangue)	Antes do último turno da semana de trabalho	2014-11-14
		Tolueno: 0,03 mg/l (Urina)	Fim do turno	2014-11-14
		o-Cresol: 0.3 mg/g creatinina Com hidrólise (Urina) Valor basal ( )	Fim do turno	2014-11-14

## LV

Vielas nosaukums	CAS Nr.	Pārvaldības parametri	Parauga ņemšanas laiks	Precizējums
Toluene	108-88-3	toluolu: 0,05 mg/l (Asinis)	maiņas beigās nosaka	2007-05-18
		hipurskābi: 1.6 g/g kreatinīns (Urīns)	maiņas beigās nosaka	2007-05-18

## IT

Denominazione della sostanza	N. CAS	Parametri di controllo	Tempo di campionamento	Aggiornamento
------------------------------	--------	------------------------	------------------------	---------------

## HU

Az anyag megnevezése	CAS szám	Ellenőrzési paraméterek	Mintavétel időpontja	Aktualizálás
Toluene	108-88-3	o-krezol: 1 mg/g kreatinin (húgyhólyag)	A műszak végén	2020-02-06
		o-krezol: 1 µmol/mmol kreatinin (kerekített értékek) (húgyhólyag)	A műszak végén	2020-02-06

## HR

Naziv tvari	CAS-br.	Nadzorni parametri	Vrijeme uzorkovanja	Ažurirati
Toluene	108-88-3	toluen: 10.85 µmol/l (Krv)	na kraju radne smjene	2018-10-12
		toluen: 1 mg/l (Krv)	na kraju radne smjene	2018-10-12
		toluen: 0.83 µmol/l (krajnje izdahnuti zrak)	za vrijeme izloženosti	2018-10-12

## Toluene Standardization Fuel 96.9

Version 1.7

Revision Date 2023-08-03

		toluen: 20 dijelova na milijun (krajnje izdahnuti zrak)	za vrijeme izloženosti	2018-10-12
		hipurna kiselina: 1.58 mol/mol kreatinina Računato na prosječnu vrijednost kreatinina od 1,2 g/L urina. Za sve rezultate koji se izražavaju na kreatinin, koncentracije kreatinina < 0,5 g/L i > 3,0 g/L ne mogu se uzeti u obzir. (Urin) hrana bogata voćem i povrćem te konzervirana Na-benzoatom povisuje nalaz ( )	na kraju radne smjene	2018-10-12
		hipurna kiselina: 2.5 g/g kreatinin Računato na prosječnu vrijednost kreatinina od 1,2 g/L urina. Za sve rezultate koji se izražavaju na kreatinin, koncentracije kreatinina < 0,5 g/L i > 3,0 g/L ne mogu se uzeti u obzir. (Urin) hrana bogata voćem i povrćem te konzervirana Na-benzoatom povisuje nalaz ( )	na kraju radne smjene	2018-10-12
		o-krezol: 1.05 mmol/mol kreatinina Računato na prosječnu vrijednost kreatinina od 1,2 g/L urina. Za sve rezultate koji se izražavaju na kreatinin, koncentracije kreatinina < 0,5 g/L i > 3,0 g/L ne mogu se uzeti u obzir. (Urin)	na kraju radne smjene	2018-10-12
		o-krezol: 1 mg/g kreatinina Računato na prosječnu vrijednost kreatinina od 1,2 g/L urina. Za sve rezultate koji se izražavaju na kreatinin, koncentracije kreatinina < 0,5 g/L i > 3,0 g/L ne mogu se uzeti u obzir. (Urin)	na kraju radne smjene	2018-10-12

## FI

Aineen nimi	CAS-Nro.	Valvontaa koskevat muuttujat	Näytteenottoaika	Päivämäärä
Toluene	108-88-3	tolueeni: 500 nmol/l (Veri)	Työpäivän jälkeinen aamu	2016-12-22

## ES

Nombre de la sustancia	No. CAS	Parámetros de control	Hora de muestreo	Puesto al día
Toluene	108-88-3	o-cresol: 0.6 mg/g creatinina Cuando el final de la exposición no coincide con el final de la jornada laboral, la muestra se tomará lo antes posible después de que cese la exposición real (Orina) Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB. ( )	Final de la jornada laboral	2018-02-19
		tolueno: 0,05 mg/l Antes del comienzo de la quinta jornada consecutiva de exposición. (Sangre)	principio de la última jornada de la semana laboral	2018-02-19
		tolueno: 0,08 mg/l Cuando el final de la exposición no coincide con el final de la jornada laboral, la muestra se tomará lo antes posible después de que cese la exposición real (Orina)	Final de la jornada laboral	2018-02-19

## DE

Stoffname	CAS-Nr.	Zu überwachende Parameter	Probennahmezeit punkt	Stand
Toluene	108-88-3	Toluol: 600 µg/l (Blut)	Schichtende	2019-03-29

## Toluene Standardization Fuel 96.9

Version 1.7

Revision Date 2023-08-03

		o-Kresol: 1,5 mg/l Nach Hydrolyse (Urin)	bei Langzeitexposition: nach mehreren vorangegangenen Schichten Expositionsende, bzw. Schichtende	2019-03-29
		Toluol: 75 µg/l (Urin)	Expositionsende, bzw. Schichtende	2019-03-29

## CZ

Název látky	Č. CAS	Kontrolní parametry	Doba odběru vzorku	Aktualizace
Toluene	108-88-3	Hippurová kyselina: 1600 mg/g kreatininu Je-li hodnota při nálezu kyseliny hippurové vyšší než 1600 mg/g, avšak nepřesahuje 2500 mg/g kreatininu, použije se ke zpřesnění expozice toluenu biologický expoziční test podle ukazatele o-Kresol. Je-li hodnota při nálezu kyseliny hippurové vyšší než 2500 mg/g, považuje se za hodnotu prokazující, že jde o pracovní expozici toluenu, jehož hodnota PEL je překračována a biologický expoziční test podle ukazatele o-Kresol se již neprovádí (moč)	Konec směny	2013-04-22
		Hippurová kyselina: 1000 µmol/mmol kreatininu Je-li hodnota při nálezu kyseliny hippurové vyšší než 1600 mg/g, avšak nepřesahuje 2500 mg/g kreatininu, použije se ke zpřesnění expozice toluenu biologický expoziční test podle ukazatele o-Kresol. Je-li hodnota při nálezu kyseliny hippurové vyšší než 2500 mg/g, považuje se za hodnotu prokazující, že jde o pracovní expozici toluenu, jehož hodnota PEL je překračována a biologický expoziční test podle ukazatele o-Kresol se již neprovádí (moč)	Konec směny	2013-04-22
		o-Kresol: 1.5 mg/g kreatininu Po hydrolyse (moč)	Konec směny	2013-04-22
		o-Kresol: 1.6 µmol/mmol kreatininu Po hydrolyse (moč)	Konec směny	2013-04-22

## CH

Stoffname	CAS-Nr.	Zu überwachende Parameter	Probennahmezeitpunkt	Stand
Toluene	108-88-3	o-Kresol: 0,5 mg/l Quantitative Interpretation schwierig; Bei den mit Q gekennzeichneten biologischen Parametern ist die exakte quantitative Interpretation schwierig. Als Screening-Test kann der biologische Parameter verwendet werden, ebenfalls als Zusatzuntersuchung nach der Bestimmung nicht spezifischer Parameter (N). (Urin)	Expositionsende, bzw. Schichtende bei Langzeitexposition: nach mehreren vorangegangenen Schichten	2018-01-18

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

		Hippursäure: 2 g/g Kreatinin Nicht spezifischer Parameter; Die mit N gekennzeichneten biologischen Parameter sind nicht für den aufgeführten Arbeitsstoff spezifisch, sondern können auch nach Expositionen gegenüber bestimmten anderen Arbeitsstoffen im biologischen Material gemessen werden. In der Praxis hat sich die Bestimmung dieser Stoffe jedoch bewährt. Bei speziellen Problemen empfiehlt sich zusätzlich die Bestimmung eines spezifischen Parameters. (Urin) Umwelteinflüsse; Die mit X gekennzeichneten biologischen Parameter werden auch in unterschiedlicher Quantität bei beruflich Nichtexponierten gemessen, da sie zusätzlich auf Umwelteinflüsse zurückgeführt werden können. Die Festsetzung des BAT-Wertes berücksichtigt bei diesen Parametern auch die Einflüsse von Umweltfaktoren. ()	Expositionsende, bzw. Schichtende bei Langzeitexpositionen: nach mehreren vorangegangenen Schichten	2018-01-18
		Toluol: 6.48 µmol/l (Blut)	Expositionsende, bzw. Schichtende	2018-01-18
		Hippursäure: 1.26 mmol/mmol Kreatinin Nicht spezifischer Parameter; Die mit N gekennzeichneten biologischen Parameter sind nicht für den aufgeführten Arbeitsstoff spezifisch, sondern können auch nach Expositionen gegenüber bestimmten anderen Arbeitsstoffen im biologischen Material gemessen werden. In der Praxis hat sich die Bestimmung dieser Stoffe jedoch bewährt. Bei speziellen Problemen empfiehlt sich zusätzlich die Bestimmung eines spezifischen Parameters. (Urin) Umwelteinflüsse; Die mit X gekennzeichneten biologischen Parameter werden auch in unterschiedlicher Quantität bei beruflich Nichtexponierten gemessen, da sie zusätzlich auf Umwelteinflüsse zurückgeführt werden können. Die Festsetzung des BAT-Wertes berücksichtigt bei diesen Parametern auch die Einflüsse von Umweltfaktoren. ()	Expositionsende, bzw. Schichtende bei Langzeitexpositionen: nach mehreren vorangegangenen Schichten	2018-01-18
		o-Kresol: 4.62 µmol/l Quantitative Interpretation schwierig; Bei den mit Q gekennzeichneten biologischen Parametern ist die exakte quantitative Interpretation schwierig. Als Screening-Test kann der biologische Parameter verwendet werden, ebenfalls als Zusatzuntersuchung nach der Bestimmung nicht spezifischer Parameter (N). (Urin)	Expositionsende, bzw. Schichtende bei Langzeitexpositionen: nach mehreren vorangegangenen Schichten	2018-01-18
		Toluol: 600 µg/l (Blut)	Expositionsende, bzw. Schichtende	2018-01-18

**BG**

Наименование на веществото	CAS номер	Параметри на контрол	Време на взимане на пробата	Последна актуализация
----------------------------	-----------	----------------------	-----------------------------	-----------------------



**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

Toluene	108-88-3	хипурова киселина: 1.6 mmol/mmol креатинин (Урина)	В края на експозицията или в края на работната смяна	2007-08-17
---------	----------	---	---	------------

**AT**

Stoffname	CAS-Nr.	Zu überwachende Parameter	Probennahmezeitpunkt	Stand
Toluene	108-88-3	o-Cresol: 0,8 mg/l Bei wiederholt erhöhten o-Cresolwerten ist zusätzlich Toluol im Blut am Ende eines Arbeitstages zu bestimmen (der Zeitpunkt der Untersuchung ist anzugeben). (Urin)	Nach Ablauf einer Arbeitswoche/am Ende des Arbeitstages/am Schichtende	2014-02-18
		Toluol: 250 µg/l (Blut)	Am Ende eines Arbeitstages	2014-02-18

DNEL  
n-Heptane :

**8.2**

**Exposure controls**  
**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant antistatic protective clothing. Workers should wear antistatic

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****9.1****Information on basic physical and chemical properties****Appearance**

Form : Non-viscous, liquid  
Physical state : liquid  
Color : Clear  
Odor : Strong gasoline

**Safety data**

Flash point : 4°C (39°F)  
Method: closed cup  
estimated

Lower explosion limit : 1,1 %(V)  
Upper explosion limit : 7,1 %(V)  
Oxidizing properties : No

Autoignition temperature : 528,9°C (984,0°F)

Molecular formula : Mixture  
Molecular weight : Not applicable  
pH : Not applicable  
Freezing point : -94,44°C (-137,99°F)

Pour point : No data available

Boiling point/boiling range : 99°C (210°F)  
Vapor pressure : 30,00 MMHG  
estimated

Relative density : 0,823  
at 15,6 °C (60,1 °F)

Density : 0,823 g/cm<sup>3</sup>  
Water solubility : negligible  
Partition coefficient: n-  
octanol/water : No data available  
Viscosity, kinematic : No data available

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

Relative vapor density : 3,2  
(Air = 1.0)

Evaporation rate : 4,5

Percent volatile : > 99 %  
0,02 %

**9.2****Other information**

Conductivity : No data available

**SECTION 10: Stability and reactivity****10.1**

**Reactivity** : Stable under recommended storage conditions.

**10.2**

**Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**10.3****Possibility of hazardous reactions**

**Hazardous reactions** : Hazardous reactions: Hazardous polymerization does not occur.

Hazardous reactions: Vapors may form explosive mixture with air.

**10.4**

**Conditions to avoid** : Heat, flames and sparks.

**10.5**

**Materials to avoid** : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**10.6**

**Hazardous decomposition products** : Hydrocarbons  
Carbon oxides

**Other data** : No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****11.1****Information on toxicological effects****Toluene Standardization Fuel 96.9**

**Acute oral toxicity** : Acute toxicity estimate: > 5.000 mg/kg

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

Method: Calculation method

**Toluene Standardization Fuel 96.9**

**Acute inhalation toxicity** : Acute toxicity estimate: > 20 mg/l  
 Exposure time: 4 h  
 Test atmosphere: vapor  
 Method: Calculation method

**Toluene Standardization Fuel 96.9**

**Acute dermal toxicity** : Acute toxicity estimate: > 5.000 mg/kg  
 Method: Calculation method

**Toluene Standardization Fuel 96.9**

**Skin irritation** : Skin irritation  
 largely based on animal evidence.  
 May cause skin irritation in susceptible persons.

**Toluene Standardization Fuel 96.9**

**Eye irritation** : Vapors may cause irritation to the eyes, respiratory system  
 and the skin.  
 Vapors may cause irritation to the eyes, respiratory system  
 and the skin.

**Toluene Standardization Fuel 96.9**

**Sensitization** : Does not cause skin sensitization.  
 largely based on animal evidence.

**Repeated dose toxicity**

Toluene : Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 100, 625, 1250, 3000 ppm  
 Exposure time: 15 wk  
 Number of exposures: 6.5 h/d, 5 d/wk  
 NOEL: 625 ppm

Species: Mouse  
 Application Route: Inhalation  
 Dose: 0, 100, 625, 1250, 3000 ppm  
 Exposure time: 14 wk  
 Number of exposures: 6.5 h/d, 5 d/wk  
 NOEL: 100 ppm

n-Heptane

Species: Rat, male  
 Sex: male  
 Application Route: Inhalation  
 Dose: 12.47 mg/l  
 Exposure time: 16 wk  
 Number of exposures: 12 h/d, 7 d/wk  
 NOEL: 12,47 mg/l  
 No adverse effect has been observed in chronic toxicity tests.

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

Species: Rat, Male and female  
 Sex: Male and female  
 Application Route: Inhalation  
 Dose: 12.35 mg/l  
 Exposure time: 26 wk  
 Number of exposures: 6 h/d, 5 d/wk  
 Method: OECD Test Guideline 413  
 No adverse effect has been observed in chronic toxicity tests.

2,2,4-Trimethylpentane  
 (Isooctane)

Species: Rat, Male and female  
 Sex: Male and female  
 Application Route: Inhalation  
 Dose: 0, 668, 2220, 6646 ppm  
 Exposure time: 13 weeks  
 Number of exposures: 6 hr/day 5 d/wk  
 NOEL: 8,117 mg/l 2220 ppm  
 Method: OECD Guideline 413  
 Information given is based on data obtained from similar substances.

**Genotoxicity in vitro**

Toluene

: Test Type: Ames test  
 Result: negative

Test Type: Sister Chromatid Exchange Assay  
 Result: negative

Test Type: Mouse lymphoma assay  
 Result: negative

Test Type: Cytogenetic assay  
 Result: negative

n-Heptane

Test Type: Ames test  
 Method: Mutagenicity (Escherichia coli - reverse mutation assay)  
 Result: negative

Test Type: Mammalian cell gene mutation assay  
 Method: OECD Guideline 476  
 Result: negative

Test Type: Chromosome aberration test in vitro  
 Method: OECD Guideline 473  
 Result: negative

Test Type: Mitotic recombination  
 Result: negative

2,2,4-Trimethylpentane  
 (Isooctane)

Test Type: Ames test  
 Method: Mutagenicity (Escherichia coli - reverse mutation assay)  
 Result: negative

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

Test Type: Mouse lymphoma assay  
 Method: OECD Guideline 476  
 Result: negative

Test Type: Sister Chromatid Exchange Assay  
 Result: negative

Test Type: Unscheduled DNA synthesis assay  
 Result: negative

**Genotoxicity in vivo**

Toluene : Test Type: Cytogenetic assay  
 Result: negative

Test Type: Mouse micronucleus assay  
 Result: negative

2,2,4-Trimethylpentane (Isooctane) : Test Type: Unscheduled DNA synthesis assay  
 Species: Mouse  
 Dose: 500 mg/kg  
 Result: negative

Test Type: Unscheduled DNA synthesis assay  
 Species: Rat  
 Dose: 500 mg/kg  
 Result: negative

**Carcinogenicity**

Toluene : Species: Rat  
 Dose: 0, 600, 1200 ppm  
 Exposure time: 2 yrs  
 Number of exposures: 6.5 h/d, 5 d/wk  
 Remarks: No evidence of carcinogenicity

Species: Mouse  
 Dose: 0, 600, 1200 ppm  
 Exposure time: 2 yrs  
 Number of exposures: 6.5 h/d, 5 d/wk  
 Remarks: No evidence of carcinogenicity

**Reproductive toxicity**

Toluene : Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 100, 500, 2000 ppm  
 Test period: 95 d  
 NOAEL Parent: 2000 ppm

n-Heptane : Species: Rat  
 Sex: male and female  
 Application Route: Inhalation  
 Dose: 0, 900, 3000, 9000 ppm  
 Number of exposures: 6 hr/d, 5 d/wk  
 Test period: 13 wk  
 Method: OECD Test Guideline 416  
 NOAEL Parent: 9000 ppm

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

NOAEL F1: 3000 ppm  
 NOAEL F2: 3000 ppm  
 Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane  
 (Isooctane)

Species: Rat  
 Sex: male and female  
 Application Route: Inhalation  
 Dose: 0, 900, 3000, 9000 ppm  
 Number of exposures: 6 h/d 5 d/wk  
 Method: OECD Test Guideline 416  
 NOAEL Parent: 3000 ppm  
 NOAEL F1: 3000 ppm  
 NOAEL F2: 3000 ppm  
 Information given is based on data obtained from similar substances.

**Developmental Toxicity**

Toluene

: Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 100, 500, 2000 ppm  
 Test period: 95 d  
 NOAEL Teratogenicity: 400-750 ppm

n-Heptane

Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 900, 3000, 9000 ppm  
 Exposure time: GD6-15  
 Number of exposures: 6 hrs/d  
 NOAEL Teratogenicity: 9000 ppm  
 NOAEL Maternal: 3000 ppm

2,2,4-Trimethylpentane  
 (Isooctane)

Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 400, 1200 ppm  
 Number of exposures: 6h/d  
 Test period: GD6-15  
 NOAEL Teratogenicity: 1200 ppm  
 NOAEL Maternal: 1200 ppm  
 Information given is based on data obtained from similar substances.

Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 900, 3000, 9000 ppm  
 Number of exposures: 6h/d  
 Test period: GD6-15  
 Method: OECD Guideline 414  
 NOAEL Teratogenicity: 9000 ppm  
 NOAEL Maternal: 3000 ppm  
 Information given is based on data obtained from similar substances.

**Toluene Standardization Fuel 96.9**

**Aspiration toxicity** : May be fatal if swallowed and enters airways.

**Specific Target Organ Toxicity (Single Exposure)**

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

Toluene : Assessment: May cause drowsiness or dizziness.

n-Heptane Target Organs: Central nervous system  
Assessment: May cause drowsiness or dizziness.

2,2,4-Trimethylpentane (Isooctane) Assessment: May cause drowsiness or dizziness.

**Specific Target Organ Toxicity (Repeated Exposure)**

Toluene : Route of Exposure: Inhalation  
Target Organs: Auditory organs, color vision  
Assessment: May cause damage to organs through prolonged or repeated exposure.

**CMR effects**

Toluene : Carcinogenicity: Not classifiable as a human carcinogen.  
Mutagenicity: Animal testing did not show any mutagenic effects.  
Teratogenicity: Some evidence of adverse effects on development, based on animal experiments.  
Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

n-Heptane Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.  
Teratogenicity: Animal testing did not show any effects on fetal development.  
Reproductive toxicity: No toxicity to reproduction

2,2,4-Trimethylpentane (Isooctane) Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.  
Teratogenicity: Animal testing did not show any effects on fetal development.  
Reproductive toxicity: Animal testing did not show any effects on fertility.

**11.2****Information on other hazards****Toluene Standardization Fuel 96.9**

**Further information** : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 12: Ecological information****12.1****Toxicity**



**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

**Toxicity to fish**

Toluene	: LC50: 18 - 36 mg/l Exposure time: 96 h Species: Pimephales promelas (fathead minnow)
n-Heptane	LL50: 5,738 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) Method: QSAR modeled data
2,2,4-Trimethylpentane (Isooctane)	LC50: 0,11 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar substances.

**Toxicity to daphnia and other aquatic invertebrates**

Toluene	: EC50: 3,78 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
n-Heptane	EC50: 1,5 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) static test Toxic to aquatic organisms.  LC50: 0,1 mg/l Exposure time: 96 h Species: Mysidopsis bahia (mysid shrimp) semi-static test Very toxic to aquatic organisms.
2,2,4-Trimethylpentane (Isooctane)	EC50: 0,4 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) static test Information given is based on data obtained from similar substances.

**Toxicity to algae**

Toluene	: EC50: 134 mg/l Exposure time: 72 h Species: Chlamydomonas angulosa (Green algae)
n-Heptane	EL50: 4,338 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (microalgae) Method: QSAR
2,2,4-Trimethylpentane (Isooctane)	EL50: 2,943 mg/l Exposure time: 72 h Method: QSAR modeled data

**Toxicity to fish (Chronic toxicity)**

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

n-Heptane : NOELR: 1,284 mg/l  
 Exposure time: 28 d  
 Species: Oncorhynchus mykiss (rainbow trout)  
 Method: QSAR modeled data

**Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)**

2,2,4-Trimethylpentane (Isooctane) : NOEL: 0,17 mg/l  
 Exposure time: 21 d  
 Species: Daphnia magna (Water flea)  
 Method: OECD Test Guideline 211  
 Information given is based on data obtained from similar substances.

**12.2****Persistence and degradability**

Biodegradability : Expected to be inherently biodegradable.

**12.3****Bioaccumulative potential**

Elimination information (persistence and degradability)

Bioaccumulation

Toluene : This material is not expected to bioaccumulate.

n-Heptane : Bioconcentration factor (BCF): 552  
 Method: QSAR modeled data  
 This material is not expected to bioaccumulate.

2,2,4-Trimethylpentane (Isooctane) : Bioconcentration factor (BCF): 231  
 Method: QSAR modeled data  
 This material is not expected to bioaccumulate.

**12.4****Mobility in soil**

Mobility

Toluene : Not expected to adsorb on soil.

n-Heptane : Medium: Air  
 Method: Calculation, Mackay Level I Fugacity Model  
 Content: 100 %  
 After release, disperses into the air.

2,2,4-Trimethylpentane (Isooctane) : Medium: Air  
 Method: Calculation, Mackay Level I Fugacity Model  
 After release, disperses into the air.

**12.5****Results of PBT and vPvB assessment**

Results of PBT assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

**12.6****Endocrine disrupting properties**

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7****Other adverse effects**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

**12.8****Additional Information****Ecotoxicology Assessment****Short-term (acute) aquatic hazard**

Toluene : Toxic to aquatic life.

n-Heptane : Very toxic to aquatic life.

2,2,4-Trimethylpentane (Isooctane) : Very toxic to aquatic life.

**Long-term (chronic) aquatic hazard**

Toluene : Harmful to aquatic life with long lasting effects.

n-Heptane : Very toxic to aquatic life with long lasting effects.

2,2,4-Trimethylpentane (Isooctane) : Very toxic to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations****13.1****Waste treatment methods**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

**SECTION 14: Transport information****14.1 - 14.7****Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, MARINE POLLUTANT, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (4 °C c.c.), MARINE POLLUTANT, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

33, UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

Maritime transport in bulk according to IMO instruments

**SECTION 15: Regulatory information****15.1**

Safety, health and environmental regulations/legislation specific for the substance or mixture  
National legislation

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

**Water hazard class (Germany)** : WGK 3 highly water endangering

**15.2**

**Major Accident Hazard Legislation**

- : 96/82/EC Update: 2003  
Highly flammable  
7b  
Quantity 1: 5.000 t  
Quantity 2: 50.000 t
- : 96/82/EC Update: 2003  
Dangerous for the environment  
9b  
Quantity 1: 200 t  
Quantity 2: 500 t
- : ZEU\_SEVES3 Update:  
FLAMMABLE LIQUIDS  
P5c  
Quantity 1: 5.000 t  
Quantity 2: 50.000 t
- : ZEU\_SEVES3 Update:  
ENVIRONMENTAL HAZARDS  
E1  
Quantity 1: 100 t  
Quantity 2: 200 t

**Notification status**

Europe REACH : This mixture contains only ingredients which have been registered according to Regulation (EU) No. 1907/2006 (REACH).

Switzerland CH INV : On the inventory, or in compliance with the inventory

United States of America (USA) TSCA : On or in compliance with the active portion of the TSCA inventory

Canada DSL : All components of this product are on the Canadian DSL

Australia AIIC : On the inventory, or in compliance with the inventory

New Zealand NZIoC : Not in compliance with the inventory

Japan ENCS : On the inventory, or in compliance with the inventory

Korea KECI : A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).

Philippines PICCS : On the inventory, or in compliance with the inventory

Taiwan TCSI : On the inventory, or in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory


**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 2  
Fire Hazard: 3  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 26820

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act

**Toluene Standardization Fuel 96.9**

Version 1.7

Revision Date 2023-08-03

	New Chemical Substances		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

**Full text of H-Statements referred to under sections 2 and 3.**

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.