



Scentinel® U

Version 3.0

Revision Date 2023-08-03

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product information

Product Name : Scentinel® U
 Material : 1124494, 1124460

EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
Diethyl Sulfide	352-93-2 206-526-9	Chevron Phillips Chemicals International NV 01-2119971585-25-0000
t-Butyl Mercaptan	75-66-1 200-890-2	Chevron Phillips Chemicals International NV 01-2119491288-26-0000
Ethyl Mercaptan	75-08-1 200-837-3 016-022-00-9	Chevron Phillips Chemicals International NV 01-2119491286-30-0000

1.2

Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses : For export from the EU only.
 Supported

1.3

Details of the supplier of the safety data sheet

Company : Chevron Phillips Chemical Company LP
 10001 Six Pines Drive
 The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
 Airport Plaza (Stockholm Building)
 Leonardo Da Vincilaan 19
 1831 Diegem
 Belgium

SDS Requests: (800) 852-5530
 Responsible Party: Product Safety Group

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Email:sds@cpchem.com

1.4**Emergency telephone:****Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Gifftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic

Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com

Website : www.CPChem.com

ODOR-FADE WARNING

A GAS LEAK CAN CAUSE A FIRE OR EXPLOSION RESULTING IN SERIOUS INJURY OR DEATH.

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Be aware that the stenching chemical added to gas to make it detectable may not warn of a gas leak or the presence of propane or natural gas to all persons in every instance.

Instances where the odorant in an odorized gas may be undetectable include:

- Odor intensity may fade or be eliminated for a variety of chemical and physical causes, including the oxidation of rusting pipes, adsorption into or sticking onto the interior of pipes or appliances, or absorption into liquids.
- Contact with soil in underground leaks may de-odorize or remove odorant from the gas.
- Some people have a diminished ability, or inability to smell the stench. Factors that negatively affect a person's sense of smell include age, gender, medical conditions, and alcohol/tobacco usage.
- The stench of odorized gas may not awaken sleeping persons.
- Other odors may mask or hide the stench.
- Exposure to the odor for even a short period of time, may cause nasal fatigue, where a person can no longer smell the stench.

Gas detectors listed by the Underwriters Laboratories (UL) can be used as an extra measure of safety for detecting gas leaks, especially under conditions where the odorant alone may not provide an adequate warning. Gas detectors emit a loud, shrill sound when gas is present and do not depend on sense of smell. Because the odor intensity can fade or people may have problems with their sense of smell, we recommend installing, per manufacturer's instructions, one or more combustible gas detectors, in suitable locations to ensure adequate coverage to detect gas leaks.

Educate yourself, your employees, and your customers with the content of this warning and other important facts associated with the so-called "odor-fade phenomenon."

SECTION 2: Hazards identification**2.1****Classification of the substance or mixture
REGULATION (EC) No 1272/2008**

Flammable liquids, Category 2

H225:

Highly flammable liquid and vapor.

Serious eye damage, Category 1

H318:

Causes serious eye damage.

Skin sensitization, Category 1

H317:

May cause an allergic skin reaction.

Short-term (acute) aquatic hazard,
Category 1

H400:

Very toxic to aquatic life.

Long-term (chronic) aquatic hazard,
Category 1

H410:

Very toxic to aquatic life with long lasting effects.

2.2**Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H225

Highly flammable liquid and vapor.

H317

May cause an allergic skin reaction.

H318

Causes serious eye damage.

H410

Very toxic to aquatic life with long lasting effects.

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Precautionary Statements	Prevention: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P273 P280	Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
	Response: P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
	P391	Collect spillage.

Hazardous ingredients which must be listed on the label:

- 75-66-1 t-Butyl Mercaptan
- 75-08-1 Ethyl Mercaptan

2.3**Other hazards**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.1 - 3.2****Substance or Mixture****Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]	Specific Conc. Limits, M-factors and ATEs
Diethyl Sulfide	352-93-2 206-526-9	Flam. Liq. 2; H225 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	77 - 84	M [Acute]=1 M [Chronic]=1
t-Butyl Mercaptan	75-66-1 200-890-2	Flam. Liq. 2; H225 Eye Irrit. 2; H319 Skin Sens. 1B; H317	13 - 17	

Scentinel® U

Version 3.0

Revision Date 2023-08-03

		Aquatic Chronic 2; H411		
Ethyl Mercaptan	75-08-1 200-837-3 016-022-00-9	Flam. Liq. 1; H224 Flam. Liq. 2; H225 Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	4 - 6	M [Acute]=10 M [Chronic]=10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1****Description of first-aid measures**

- General advice : Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed**Notes to physician**

- Symptoms : No data available.
- Risks : No data available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No data available.

SECTION 5: Firefighting measures

- Flash point : <10°C (<50°F)
Method: ASTM D 93

5.1

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.

Unsuitable extinguishing media : High volume water jet.

5.2**Special hazards arising from the substance or mixture**

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3**Advice for firefighters**

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

SECTION 6: Accidental release measures**6.1****Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

6.2**Environmental precautions**

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3**Methods and materials for containment and cleaning up**

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4**Reference to other sections**

Reference to other sections : For personal protection see section 8. For disposal considerations see section 13.

Scentinel® U

Version 3.0

Revision Date 2023-08-03

SECTION 7: Handling and storage**7.1****Precautions for safe handling
Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

7.2**Conditions for safe storage, including any incompatibilities****Storage**

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**8.1****Control parameters
Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
t-Butyl Mercaptan	Manufacturer	TWA	0,5 ppm,	

SK

Zložky	Podstata	Hodnota	Kontrolné parametre	Poznámka
Ethyl Mercaptan	SK OEL	NPEL priemerný	0,5 ppm, 1,3 mg/m3	
	SK OEL	NPEL krátkodobý	1 ppm, 2,6 mg/m3	

SI

Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
Ethyl Mercaptan	SI OEL	MV	0,5 ppm, 1,3 mg/m3	
	SI OEL	KTV	1 ppm, 2,6 mg/m3	

Scentinel® U

Version 3.0

Revision Date 2023-08-03

RO

Componente	Sursă	Valoare	Parametri de control	Notă
Ethyl Mercaptan	RO OEL	STEL	1 mg/m3	

PT

Componentes	Bases	Valor	Parâmetros de controlo	Nota
Ethyl Mercaptan	PT OEL	VLE-MP	0,5 ppm,	

PL

Składniki	Podstawa	Wartość	Parametry dotyczące kontroli	Uwaga
Ethyl Mercaptan	PL NDS	NDS	1 mg/m3	
	PL NDS	NDSch	2 mg/m3	

NO

Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
Ethyl Mercaptan	FOR-2011-12-06-1358	GV	0,5 ppm, 1 mg/m3	

MK

Съставки	Основа	Стойност	Параметри на контрол	Бележка
Ethyl Mercaptan	MK OEL	MV	0,5 ppm, 1,3 mg/m3	

LV

Sastāvdaļas	Bāze	Vērtība	Pārvaldības parametri	Piezīme
Ethyl Mercaptan	LV OEL	AER 8 st	1 mg/m3	

LT

Komponentai	Šaltinis	Vertė	Kontrolės parametrai	Pastaba
Ethyl Mercaptan	LT OEL	IPRD	1 mg/m3	O,

O pateikimas per nepažeistą odą

IS

Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
Ethyl Mercaptan	IS OEL	TWA	0,5 ppm, 1 mg/m3	

IE

Components	Basis	Value	Control parameters	Note
Ethyl Mercaptan	IE OEL	OELV - 8 hrs (TWA)	0,5 ppm,	

HU

Komponensek	Bázis	Érték	Ellenőrzési paraméterek	Megjegyzés
Ethyl Mercaptan	HU OEL	AK-érték	1 mg/m3	N, i,
	HU OEL	CK-érték	2 mg/m3	N, i,

i Ingerlő anyag (izgatja a bőrt, nyálkahártyát, szemet vagy mindhámat)

N Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok. Korrekció NEM szükséges.

HR

Sastojci	Temelj	Vrijednost	Nadzorni parametri	Bilješka
Ethyl Mercaptan	HR OEL	GVI	0,5 ppm, 1,3 mg/m3	
	HR OEL	KGVI	2 ppm, 5,2 mg/m3	

GR

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
Ethyl Mercaptan	GR OEL	TWA	10 ppm, 25 mg/m3	
	GR OEL	STEL	10 ppm, 25 mg/m3	

GB

Components	Basis	Value	Control parameters	Note
Ethyl Mercaptan	GB EH40	TWA	0,5 ppm, 1,3 mg/m3	
	GB EH40	STEL	2 ppm, 5,2 mg/m3	

FR

Composants	Base	Valeur	Paramètres de contrôle	Note
t-Butyl Mercaptan	FR VLE	VME	0,5 ppm, 1,5 mg/m3	Valeurs limites indicatives,
Ethyl Mercaptan	FR VLE	VME	0,5 ppm, 1 mg/m3	Valeurs limites indicatives,

Valeurs limites Valeurs limites indicatives
indicatives

FI

Aineosat	Peruste	Arvo	Valvontaa koskevat	Huomautus

SDS Number:100000104262

8/25

Scentinel® U

Version 3.0

Revision Date 2023-08-03

			muuttujat	
Ethyl Mercaptan	FI OEL	HTP-arvot 15 min	0,5 ppm, 1,3 mg/m3	

ES

Componentes	Base	Valor	Parámetros de control	Nota
Ethyl Mercaptan	ES VLA	VLA-ED	0,5 ppm, 1,3 mg/m3	

EE

Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
Ethyl Mercaptan	EE OEL	Piirnorm	0,5 ppm, 1 mg/m3	C,

C Kantserogeensed ained

DK

Komponenter	Basis	Værdi	Kontrolparametre	Note
Ethyl Mercaptan	DK OEL	GV	0,5 ppm, 1 mg/m3	

DE

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Ethyl Mercaptan	DE TRGS 900	AGW	0,5 ppm, 1,3 mg/m3	H,

H Hautresorptiv

CH

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Ethyl Mercaptan	CH SUVA	MAK-Wert	0,5 ppm, 1,3 mg/m3	
	CH SUVA	KZGW	1 ppm, 2,6 mg/m3	

BG

Съставки	Основа	Стойност	Параметри на контрол	Бележка
Ethyl Mercaptan	BG OEL	TWA	1 mg/m3	

BE

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Ethyl Mercaptan	BE OEL	TGG 8 hr	0,5 ppm, 1,3 mg/m3	

AT

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Ethyl Mercaptan	AT OEL	MAK-KZW	0,5 ppm, 1,3 mg/m3	
	AT OEL	MAK-TMW	0,5 ppm, 1,3 mg/m3	

8.2**Exposure controls
Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Scentinel® U

Version 3.0

Revision Date 2023-08-03

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Remove and wash contaminated clothing before re-use. Skin should be washed after contact. Complete head face and neck protection. Rubber apron. Footwear protecting against chemicals.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**9.1****Information on basic physical and chemical properties****Appearance**

- Form : liquid
- Physical state : liquid
- Color : Clear With No Particulate Matter
- Odor : Pungent
- Odor Threshold : No data available

Safety data

- Flash point : <10°C (<50°F)
Method: ASTM D 93
- Ignition temperature : Remarks: No data available
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Molecular weight : 62,13 g/mol
- pH : No data available
- Freezing point : <-50°C (<-58°F)
- Melting point/range : No data available
- Pour point : No data available

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Initial boiling point and boiling range	: 69,8°C (157,6°F)
Vapor pressure	: : 0,58 bar at 20°C (68°F) No data available
Relative density	: 0,836
Density	: 0,836 G/ML at 15,6°C (60,1°F)
Water solubility	: Insoluble
Partition coefficient: n-octanol/water	: No data available
Solubility in other solvents	: Soluble in hydrocarbons
Viscosity, kinematic	: 0,36 cSt
Relative vapor density	: No data available
Evaporation rate	: No data available

9.2**Other information**

Conductivity : No data available

SECTION 10: Stability and reactivity**10.1****Reactivity** : Stable under recommended storage conditions.**10.2****Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.**10.3****Possibility of hazardous reactions****Hazardous reactions** : Hazardous reactions: Vapors may form explosive mixture with air.**10.4****Conditions to avoid** : Heat, flames and sparks.**10.6****Other data** : No decomposition if stored and applied as directed.

Scentinel® U

Version 3.0

Revision Date 2023-08-03

SECTION 11: Toxicological information**11.1****Information on toxicological effects****Scentinel® U**

Acute oral toxicity : Acute toxicity estimate: > 5.000 mg/kg
Method: Calculation method

Scentinel® U

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Scentinel® U

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Scentinel® U

Skin irritation : May irritate skin. largely based on animal evidence.

Scentinel® U

Eye irritation : Risk of serious damage to eyes.

Scentinel® U

Sensitization : Causes sensitization. largely based on animal evidence.

Repeated dose toxicity**Diethyl Sulfide**

: Species: Rat, male and female
Sex: male and female
Application Route: oral gavage
Dose: 0, 2.5, 25, 250 mg/kg/bw/d
Exposure time: 14 wk
Number of exposures: 7 d/wk
Method: OECD Test Guideline 408
No adverse effects expected
Information given is based on data obtained from similar substances.

t-Butyl Mercaptan

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 9, 97, 196 ppm
Exposure time: 13 wks
Number of exposures: 6 hrs/d, 5 d/wk
NOEL: > 196 ppm

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Species: Rat, Male and female
Sex: Male and female
Application Route: oral gavage
Dose: 10, 50, 200 mg/kg bw/day
Exposure time: 42-53 days
Number of exposures: Daily
NOEL: 50 mg/kg bw/day
Lowest observable effect level: 200 mg/kg bw/day
Method: OECD Guideline 422

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 25.1, 99.6, 403.4 ppm
Exposure time: 13 wks
Number of exposures: 6 hrs/d, 5 d/wk
NOEL: 99.6 ppm
Lowest observable effect level: 403.4 ppm
Method: OECD Guideline 413
Target Organs: Liver, Kidney, Blood, Upper respiratory tract
Information given is based on data obtained from similar substances.

Ethyl Mercaptan

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 25, 100, 400 ppm
Exposure time: 13 wks
Number of exposures: 6 hr/d, 5 d/wk
NOEL: 100 ppm
Lowest observable effect level: 400 ppm
Method: OECD Guideline 413
Information given is based on data obtained from similar substances.

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Species: Rat, Male and female
Sex: Male and female
Application Route: Oral
Dose: 0, 10, 50, 200 mg/kg
Exposure time: 42-53 days
NOEL: 50 mg/kg
Method: OECD Guideline 422
Information given is based on data obtained from similar substances.

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 9, 97, 196 ppm
Exposure time: 13 wks
Number of exposures: 6 hr/d, 5 d/wk
NOEL: >=196 ppm
Method: OECD Guideline 413
Information given is based on data obtained from similar substances.

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 0.03, 0.26, 0.55 mg/L
Exposure time: 13 wks
Number of exposures: 6 hr/d, 5 d/wk
NOEL: 0,03 mg/l
Method: OECD Test Guideline 413
Information given is based on data obtained from similar substances.

Genotoxicity in vitro

Diethyl Sulfide

: Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
Remarks: Information given is based on data obtained from similar substances.

Scentinel® U

Version 3.0

Revision Date 2023-08-03

	<p>Test Type: Ames test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative Remarks: Information given is based on data obtained from similar substances.</p> <p>Test Type: Chromosome aberration test in vitro Metabolic activation: with and without metabolic activation Method: OECD Guideline 473 Result: negative Remarks: Information given is based on data obtained from similar substances.</p> <p>Test Type: Mouse lymphoma assay Metabolic activation: with and without metabolic activation Method: OECD Guideline 476 Result: negative Remarks: Information given is based on data obtained from similar substances.</p>
t-Butyl Mercaptan	<p>Test Type: Ames test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative</p> <p>Test Type: Mouse lymphoma assay Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative</p> <p>Test Type: Sister Chromatid Exchange Assay Metabolic activation: with and without metabolic activation Result: negative</p>
Ethyl Mercaptan	<p>Test Type: Ames test Metabolic activation: with and without metabolic activation Method: Mutagenicity (Escherichia coli - reverse mutation assay) Result: negative</p> <p>Test Type: Mouse lymphoma assay Method: OECD Guideline 476 Result: Ambiguous</p> <p>Test Type: Sister Chromatid Exchange Assay Metabolic activation: with and without metabolic activation Result: positive</p> <p>Test Type: Micronucleus test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 487 Result: negative</p>
Genotoxicity in vivo	
Diethyl Sulfide	: Test Type: In vivo micronucleus test Species: Mouse Cell type: Bone marrow

Scentinel® U

Version 3.0

Revision Date 2023-08-03

t-Butyl Mercaptan
 Route of Application: Oral
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Information given is based on data obtained from similar substances.

t-Butyl Mercaptan
 Test Type: Mouse micronucleus assay
 Species: Mouse
 Dose: 1250, 2500, 5000 mg/kg
 Method: OECD Test Guideline 474
 Result: negative

Ethyl Mercaptan
 Test Type: Micronucleus test
 Species: Mouse
 Method: Mutagenicity (micronucleus test)
 Result: negative

Reproductive toxicity

t-Butyl Mercaptan : Species: Rat
 Sex: male and female
 Application Route: oral gavage
 Dose: 10, 50, 200 mg/kg bw/day
 Number of exposures: Daily
 Test period: 42 -53 days
 Method: OECD Guideline 422
 NOAEL Parent: 200 mg/kg bw/day
 NOAEL F1: 50 mg/kg bw/day
 No adverse effects expected

Ethyl Mercaptan
 Species: Rat
 Sex: male and female
 Application Route: Oral diet
 Dose: 0, 10, 50, 200 mg/kg
 Exposure time: 42-53 days
 Number of exposures: once daily
 Method: OECD Guideline 422
 NOAEL Parent: 200 mg/kg
 NOAEL F1: 50 mg/kg
 Information given is based on data obtained from similar substances.

Developmental Toxicity

Diethyl Sulfide : Species: Rat
 Application Route: oral gavage
 Dose: 100, 500, 1000 mg/kg/d
 Exposure time: GD 6 -19
 Number of exposures: Daily
 Test period: 20 d
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 1.000 mg/kg
 NOAEL Maternal: 1.000 mg/kg
 No adverse effects expected
 Information given is based on data obtained from similar substances.

t-Butyl Mercaptan
 Species: Mouse
 Application Route: Inhalation

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Dose: 11, 99, 195 ppm
 Exposure time: GD 6-16
 Number of exposures: 6 hrs/d
 NOAEL Teratogenicity: > = 195 ppm
 NOAEL Maternal: > = 195 ppm

Species: Rat
 Application Route: Inhalation
 Dose: 11, 99, 195 ppm
 Exposure time: GD6-19
 Number of exposures: 6 hrs/d
 NOAEL Teratogenicity: > =195 ppm
 NOAEL Maternal: > = 195 ppm

Species: Rat
 Application Route: oral gavage
 Dose: 10, 50, 200 mg/kg bw/day
 Exposure time: 42-53 days
 Number of exposures: Daily
 NOAEL Teratogenicity: 50 mg/kg bw /day
 NOAEL Maternal: 200 mg/kg bw /day

Ethyl Mercaptan

Species: Rat
 Application Route: Inhalation
 Dose: 0, 0.037, 0.28, or 0.56 mg/L
 Number of exposures: 6 hrs/d
 Test period: GD 6-19
 Method: OECD Guideline 414
 NOAEL Teratogenicity: > 0,56 mg/l
 Information given is based on data obtained from similar substances.

Species: Rat
 Application Route: Inhalation
 Dose: 0, 10, 100, 200 ppm
 Number of exposures: 6 hrs/d
 Test period: GD 6-19
 Method: OECD Guideline 414
 NOAEL Teratogenicity: > 200 ppm
 NOAEL Maternal: > 200 ppm
 Information given is based on data obtained from similar substances.

Scentinel® U**Aspiration toxicity**

: May be harmful if swallowed and enters airways.

CMR effects**Diethyl Sulfide**: Carcinogenicity: Not available
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects
 Teratogenicity: Animal testing did not show any effects on fetal development.
 Reproductive toxicity: Not available**t-Butyl Mercaptan**Carcinogenicity: Not available
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Ethyl Mercaptan	<p>mutagenic effects Reproductive toxicity: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.</p> <p>Carcinogenicity: Not available Mutagenicity: Not mutagenic in Ames Test. Teratogenicity: Animal testing did not show any effects on fetal development. Reproductive toxicity: Animal testing did not show any effects on fertility.</p>
-----------------	---

11.2**Information on other hazards****Scentinel® U****Further information**

Endocrine disrupting properties

- : Solvents may degrease the skin. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
- : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information**12.1****Toxicity****Toxicity to fish**

Diethyl Sulfide	<p>: LC50: > 49,8 mg/l Exposure time: 96 h Species: Danio rerio (Zebra Fish) semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar substances.</p>
-----------------	---

t-Butyl Mercaptan	<p>LC50: 34 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203</p>
-------------------	--

Ethyl Mercaptan	<p>2,4 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) Method: OECD Test Guideline 203</p>
-----------------	--

Toxicity to daphnia and other aquatic invertebrates

Diethyl Sulfide	<p>: EC50: 17 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) static test Information given is based on data obtained from similar substances.</p>
-----------------	---

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Method: OECD Test Guideline 301D
Information given is based on data obtained from similar substances.

t-Butyl Mercaptan : aerobic
Result: Not readily biodegradable.
6 %
Testing period: 63 d
Method: OECD Test Guideline 301

Ethyl Mercaptan : aerobic
Result: Not readily biodegradable.
0 %
Testing period: 29 d
Method: OECD Test Guideline 301F

12.3**Bioaccumulative potential**

Bioaccumulation

Diethyl Sulfide : This material is not expected to bioaccumulate.

t-Butyl Mercaptan : Bioconcentration factor (BCF): 12
Method: QSAR modeled data
This material is not expected to bioaccumulate.

Ethyl Mercaptan : This material is not expected to bioaccumulate.

12.4**Mobility in soil**

Mobility

Diethyl Sulfide : No data available

t-Butyl Mercaptan : Method: Calculation, Mackay Level III Fugacity Model
The product will be dispersed amongst the various environmental compartments (soil/ water/ air).

Ethyl Mercaptan : The product will be dispersed amongst the various environmental compartments (soil/ water/ air).

12.5**Results of PBT and vPvB assessment**

Results of PBT assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6**Endocrine disrupting properties**

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Scentinel® U

Version 3.0

Revision Date 2023-08-03

12.7**Other adverse effects**

Additional ecological information : Very toxic to aquatic life with long lasting effects.

12.8**Additional Information****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard

Diethyl Sulfide : Harmful to aquatic life.

t-Butyl Mercaptan : Toxic to aquatic life.

Ethyl Mercaptan : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard

Diethyl Sulfide : Harmful to aquatic life with long lasting effects.

t-Butyl Mercaptan : Toxic to aquatic life with long lasting effects.

Ethyl Mercaptan : Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1****Waste treatment methods**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**14.1 - 14.7****Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the

Scentinel® U

Version 3.0

Revision Date 2023-08-03

bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (DIETHYL SULFIDE, TERTIARY BUTYL MERCAPTAN), 3, II, MARINE POLLUTANT, (ETHYL MERCAPTAN)

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (DIETHYL SULFIDE, TERTIARY BUTYL MERCAPTAN), 3, II, (< 10 °C c.c.), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN, ETHYL MERCAPTAN)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (DIETHYL SULFIDE, TERTIARY BUTYL MERCAPTAN), 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (DIETHYL SULFIDE, TERTIARY BUTYL MERCAPTAN), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN, ETHYL MERCAPTAN)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

33, UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (DIETHYL SULFIDE, TERTIARY BUTYL MERCAPTAN), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN, ETHYL MERCAPTAN)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (DIETHYL SULFIDE, TERTIARY BUTYL MERCAPTAN), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN, ETHYL MERCAPTAN)

Maritime transport in bulk according to IMO instruments**SECTION 15: Regulatory information****15.1****Safety, health and environmental regulations/legislation specific for the substance or mixture
National legislation**

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

15.2**Chemical Safety Assessment**

Scentinel® U

Version 3.0

Revision Date 2023-08-03

Components : 2-methylpropane-2-thiol A Chemical Safety Assessment 200-890-2
has been carried out for this substance.

Chemical Safety Assessment

ethanethiol A Chemical Safety Assessment 200-837-3
has been carried out for this substance.

Major Accident Hazard Legislation

: ZEU_SEVES3 Update:
FLAMMABLE LIQUIDS
P5c
Quantity 1: 5.000 t
Quantity 2: 50.000 t

: ZEU_SEVES3 Update:
ENVIRONMENTAL HAZARDS
E1
Quantity 1: 100 t
Quantity 2: 200 t

Notification status

Europe REACH : This mixture contains only ingredients which have been registered according to Regulation (EU) No. 1907/2006 (REACH).

Switzerland CH INV : On the inventory, or in compliance with the inventory

United States of America (USA) TSCA : All substances listed as active on the TSCA inventory

Canada DSL : All components of this product are on the Canadian DSL

Other AICS : On the inventory, or in compliance with the inventory

New Zealand NZIoC : On the inventory, or in compliance with the inventory

Japan ENCS : Not in compliance with the inventory

Korea KECI : A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).


Philippines PICCS : On the inventory, or in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory

Taiwan TCSI : On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 3
Fire Hazard: 3
Reactivity Hazard: 0



Scentinel® U

Version 3.0

Revision Date 2023-08-03

Further information

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIRC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

Full text of H-Statements referred to under sections 2 and 3.

Scentinel® U

Version 3.0

Revision Date 2023-08-03

H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.