



## Scentinel® F-35 Gas Odorant

Version 3.2

Revision Date 2023-08-03

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

##### Product information

Product Name : Scentinel® F-35 Gas Odorant  
 Material : 1086514, 1098152, 1086548, 1024699, 1024698, 1024700,  
 1029446, 1105016, 1105017

##### EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
t-Butyl Mercaptan	75-66-1 200-890-2	Chevron Phillips Chemicals International NV 01-2119491288-26-0000
Dimethyl Sulfide	75-18-3 200-846-2	Chevron Phillips Chemicals International NV 01-2119487127-32-0001
Dimethyl Sulfide	75-18-3 200-846-2	Chevron Phillips Chemical Company LP 01-2119487127-32-0001

#### 1.2

##### Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses Supported : Distribution  
 Formulation  
 Use as an intermediate  
 Injection as odorant in fuels – industrial

#### 1.3

##### Details of the supplier of the safety data sheet

Company : Chevron Phillips Chemical Company LP  
 Specialty Chemicals  
 10001 Six Pines Drive  
 The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.  
 Airport Plaza (Stockholm Building)  
 Leonardo Da Vincilaan 19  
 1831 Diegem

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

Belgium

SDS Requests: (800) 852-5530  
 Responsible Party: Product Safety Group  
 Email:sds@cpchem.com

**1.4****Emergency telephone:****Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic

Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group  
 E-mail address : SDS@CPChem.com  
 Website : www.CPChem.com

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**ODOR-FADE WARNING**

A GAS LEAK CAN CAUSE A FIRE OR EXPLOSION RESULTING IN SERIOUS INJURY OR DEATH.

Be aware that the stenching chemical added to gas to make it detectable may not warn of a gas leak or the presence of propane or natural gas to all persons in every instance.

Instances where the odorant in an odorized gas may be undetectable include:

- Odor intensity may fade or be eliminated for a variety of chemical and physical causes, including the oxidation of rusting pipes, adsorption into or sticking onto the interior of pipes or appliances, or absorption into liquids.
- Contact with soil in underground leaks may de-odorize or remove odorant from the gas.
- Some people have a diminished ability, or inability to smell the stench. Factors that negatively affect a person's sense of smell include age, gender, medical conditions, and alcohol/tobacco usage.
- The stench of odorized gas may not awaken sleeping persons.
- Other odors may mask or hide the stench.
- Exposure to the odor for even a short period of time, may cause nasal fatigue, where a person can no longer smell the stench.

Gas detectors listed by the Underwriters Laboratories (UL) can be used as an extra measure of safety for detecting gas leaks, especially under conditions where the odorant alone may not provide an adequate warning. Gas detectors emit a loud, shrill sound when gas is present and do not depend on sense of smell. Because the odor intensity can fade or people may have problems with their sense of smell, we recommend installing, per manufacturer's instructions, one or more combustible gas detectors, in suitable locations to ensure adequate coverage to detect gas leaks.

Educate yourself, your employees, and your customers with the content of this warning and other important facts associated with the so-called "odor-fade phenomenon."

**SECTION 2: Hazards identification****2.1****Classification of the substance or mixture  
REGULATION (EC) No 1272/2008**

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

**2.2****Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

	H411	Toxic to aquatic life with long lasting effects.
Precautionary Statements	<b>Prevention:</b> P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233	Keep container tightly closed.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
	<b>Response:</b> P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
	P391	Collect spillage.

Hazardous ingredients which must be listed on the label:

- 75-66-1 t-Butyl Mercaptan

**2.3****Other hazards**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.1 - 3.2****Substance or Mixture**

Synonyms : Mercaptan Mixture  
Gas Odorant

Molecular formula : Mixture

**Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]	Specific Conc. Limits, M-factors and ATEs
<b>t-Butyl Mercaptan</b>	<b>75-66-1</b> <b>200-890-2</b>	Flam. Liq. 2; H225 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 2; H411	63 - 67	
Dimethyl Sulfide	75-18-3	Flam. Liq. 2; H225	33 - 37	

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

200-846-2

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures****4.1****Description of first-aid measures**

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**4.2 Most important symptoms and effects, both acute and delayed****Notes to physician**

- Symptoms : No data available.
- Risks : No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Treatment : No data available.

**SECTION 5: Firefighting measures**

- Flash point : -18°C (0°F)  
estimated
- Autoignition temperature : No data available

**5.1****Extinguishing media**

- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.

**5.2****Special hazards arising from the substance or mixture**

- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**5.3****Advice for firefighters**

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition products : Carbon oxides. Sulfur oxides.

**SECTION 6: Accidental release measures****6.1****Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

**6.2****Environmental precautions**

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3****Methods and materials for containment and cleaning up**

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**6.4****Reference to other sections**

For additional details, see the Exposure Scenario in the Annex portion

**SECTION 7: Handling and storage****7.1****Precautions for safe handling  
Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

**7.2****Conditions for safe storage, including any incompatibilities****Storage**

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
t-Butyl Mercaptan	Manufacturer	TWA	0,5 ppm,	

**SE**

Beståndsdelar	Grundval	Värde	Kontrollparametrar	Anmärkning
Dimethyl Sulfide	SE AFS	NGV	1 ppm,	

**RU**

Компоненты	Основа	Величина	Параметры контроля	Заметка
Диметилсульфид	RU OEL	ПДК разовая	50 mg/m3	+, 4, пары и/или газы
	RU OEL	ПДК разовая	50 mg/m3	4, пары и/или газы

+ соединения, при работе с которыми требуется специальная защита кожи и глаз; символ проставлен вслед за наименованием вещества

4 4 класс - умеренно опасные

**PT**

Componentes	Bases	Valor	Parâmetros de controlo	Nota
Dimethyl Sulfide	PT OEL	VLE-MP	10 ppm,	

**LV**

Sastāvdaļas	Bāze	Vērtība	Pārvaldības parametri	Piezīme
Dimethyl Sulfide	LV OEL	AER 8 st	50 mg/m3	

**LT**

Komponentai	Šaltinis	Vertė	Kontrolės parametrai	Pastaba
Dimethyl Sulfide	LT OEL	IPRD	1 ppm,	

**IE**

Components	Basis	Value	Control parameters	Note
Dimethyl Sulfide	IE OEL	OELV - 8 hrs (TWA)	10 ppm,	

**HR**

Sastojci	Temelj	Vrijednost	Nadzorni parametri	Bilješka

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

Dimethyl Sulfide	HR OEL	GVI	5 ppm, 13 mg/m <sup>3</sup>	koža,
koža Razvrstana kao tvar koja nadražuje kožu (H315) ili je takva napomena navedena u direktivama				

**FR**

Composants	Base	Valeur	Paramètres de contrôle	Note
t-Butyl Mercaptan	FR VLE	VME	0,5 ppm, 1,5 mg/m <sup>3</sup>	Valeurs limites indicatives,

Valeurs limites Valeurs limites indicatives  
indicatives

**ES**

Componentes	Base	Valor	Parámetros de control	Nota
Dimethyl Sulfide	ES VLA	VLA-ED	10 ppm,	

**EE**

Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
Dimethyl Sulfide	EE OEL	Piinorm	1 ppm,	

**BE**

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Dimethyl Sulfide	BE OEL	TGG 8 hr	10 ppm, 26 mg/m <sup>3</sup>	

**8.2**

### Exposure controls Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

### Personal protective equipment

- Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. Full-Face Air-Purifying Respirator for Organic Vapors, Dusts and Mists. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the



**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

specific work-place. Wear as appropriate. Remove and wash contaminated clothing before re-use. Skin should be washed after contact. Footwear protecting against chemicals.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

For additional details, see the Exposure Scenario in the Annex portion

**SECTION 9: Physical and chemical properties****9.1****Information on basic physical and chemical properties****Appearance**

Form : liquid  
 Physical state : liquid  
 Color : Clear  
 Odor : Repulsive

**Safety data**

Flash point : -18°C (0°F)  
 estimated

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : no

Autoignition temperature : No data available

Molecular formula : Mixture

Molecular weight : Not applicable

pH : Not applicable

Freezing point : -45,6°C (-50,1°F)

Pour point : No data available

Boiling point/boiling range : 42,2-93,3°C (108,0-199,9°F)

Vapor pressure : 9,40 PSI  
 at 38°C (100°F)  
 estimated

Relative density : 0,822  
 at 15,6 °C (60,1 °F)

Density : 819,6 g/l

Water solubility : negligible

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

Partition coefficient: n-octanol/water : No data available  
 Viscosity, kinematic : No data available

Relative vapor density : 2  
 (Air = 1.0)

Evaporation rate : No data available

Percent volatile : > 99 %

**9.2****Other information**

Conductivity : No data available

**SECTION 10: Stability and reactivity****10.1**

**Reactivity** : Stable under recommended storage conditions.

**10.2**

**Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**10.3****Possibility of hazardous reactions**

**Hazardous reactions** : Hazardous reactions: Hazardous polymerization does not occur.

Hazardous reactions: Vapors may form explosive mixture with air.

**10.4**

**Conditions to avoid** : Heat, flames and sparks.

**10.6**

**Hazardous decomposition products** : Carbon oxides  
 Sulfur oxides

**Other data** : No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****11.1****Information on toxicological effects****Scentinel® F-35 Gas Odorant**

**Acute oral toxicity** : LD50: > 5.000 mg/kg  
 Species: Rat  
 Method: Acute toxicity estimate

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**Scentinel® F-35 Gas Odorant**

**Acute inhalation toxicity** : LC50: > 20 mg/l  
 Test atmosphere: vapor  
 Method: Acute toxicity estimate

**Scentinel® F-35 Gas Odorant**

**Acute dermal toxicity** : LD50: > 2.000 mg/kg  
 Method: Acute toxicity estimate

**Scentinel® F-35 Gas Odorant**

**Skin irritation** : No skin irritation. largely based on animal evidence.

**Scentinel® F-35 Gas Odorant**

**Eye irritation** : Mild eye irritation.

**Scentinel® F-35 Gas Odorant**

**Sensitization** : Causes sensitization. largely based on animal evidence.

**Repeated dose toxicity**

t-Butyl Mercaptan

: Species: Rat, Male and female  
 Sex: Male and female  
 Application Route: Inhalation  
 Dose: 9, 97, 196 ppm  
 Exposure time: 13 wks  
 Number of exposures: 6 hrs/d, 5 d/wk  
 NOEL: > 196 ppm

Species: Rat, Male and female  
 Sex: Male and female  
 Application Route: oral gavage  
 Dose: 10, 50, 200 mg/kg bw/day  
 Exposure time: 42-53 days  
 Number of exposures: Daily  
 NOEL: 50 mg/kg bw/day  
 Lowest observable effect level: 200 mg/kg bw/day  
 Method: OECD Guideline 422

Species: Rat, Male and female  
 Sex: Male and female  
 Application Route: Inhalation  
 Dose: 25.1, 99.6, 403.4 ppm  
 Exposure time: 13 wks  
 Number of exposures: 6 hrs/d, 5 d/wk  
 NOEL: 99.6 ppm  
 Lowest observable effect level: 403.4 ppm  
 Method: OECD Guideline 413  
 Target Organs: Liver, Kidney, Blood, Upper respiratory tract  
 Information given is based on data obtained from similar substances.

Dimethyl Sulfide

Species: Rat, Male and female  
 Sex: Male and female  
 Application Route: Oral diet  
 Dose: 0, 2.5, 25, 250 mg/kg bw/day  
 Exposure time: 14 wk

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

Number of exposures: daily  
 NOEL: 250 mg/kg  
 Method: OECD Test Guideline 408  
 No adverse effects expected

Species: Rat, Male and female  
 Sex: Male and female  
 Application Route: inhalation (vapor)  
 Dose: 0, 0.310, 0.964, 2.783 mg/l  
 Exposure time: 13 wk (6 h)  
 Number of exposures: 7 d/wk  
 NOEL: 2,783 mg/l  
 Method: OECD Guideline 413  
 Information given is based on data obtained from similar substances.

**Genotoxicity in vitro**

t-Butyl Mercaptan

: Test Type: Ames test  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 471  
 Result: negative

Test Type: Mouse lymphoma assay  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 476  
 Result: negative

Test Type: Sister Chromatid Exchange Assay  
 Metabolic activation: with and without metabolic activation  
 Result: negative

Dimethyl Sulfide

Test Type: Ames test  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 471  
 Result: negative

Test Type: Mouse lymphoma assay  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Guideline 476  
 Result: negative

**Genotoxicity in vivo**

t-Butyl Mercaptan

: Test Type: Mouse micronucleus assay  
 Species: Mouse  
 Dose: 1250, 2500, 5000 mg/kg  
 Method: OECD Test Guideline 474  
 Result: negative

Dimethyl Sulfide

Test Type: In vivo micronucleus test  
 Species: Mouse  
 Cell type: Bone marrow  
 Route of Application: Oral  
 Dose: 1250, 2500, 5000 mg/kg  
 Method: OECD Test Guideline 474  
 Result: negative

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**Reproductive toxicity**

t-Butyl Mercaptan : Species: Rat  
 Sex: male and female  
 Application Route: oral gavage  
 Dose: 10, 50, 200 mg/kg bw/day  
 Number of exposures: Daily  
 Test period: 42 -53 days  
 Method: OECD Guideline 422  
 NOAEL Parent: 200 mg/kg bw/day  
 NOAEL F1: 50 mg/kg bw/day  
 No adverse effects expected

**Developmental Toxicity**

t-Butyl Mercaptan : Species: Mouse  
 Application Route: Inhalation  
 Dose: 11, 99, 195 ppm  
 Exposure time: GD 6-16  
 Number of exposures: 6 hrs/d  
 NOAEL Teratogenicity: > = 195 ppm  
 NOAEL Maternal: > = 195 ppm

Species: Rat  
 Application Route: Inhalation  
 Dose: 11, 99, 195 ppm  
 Exposure time: GD6-19  
 Number of exposures: 6 hrs/d  
 NOAEL Teratogenicity: > =195 ppm  
 NOAEL Maternal: > = 195 ppm

Species: Rat  
 Application Route: oral gavage  
 Dose: 10, 50, 200 mg/kg bw/day  
 Exposure time: 42-53 days  
 Number of exposures: Daily  
 NOAEL Teratogenicity: 50 mg/kg bw /day  
 NOAEL Maternal: 200 mg/kg bw /day

Dimethyl Sulfide : Species: Rat  
 Application Route: oral gavage  
 Dose: 100, 500, 1000 mg/kg  
 Exposure time: GD 6 - 19  
 Number of exposures: daily  
 Test period: 20 d  
 Method: OECD Guideline 414  
 NOAEL Teratogenicity: 1.000 mg/kg  
 NOAEL Maternal: 1.000 mg/kg

**Scentinel® F-35 Gas Odorant  
Aspiration toxicity**

: May be harmful if swallowed and enters airways.

**CMR effects**

t-Butyl Mercaptan : Carcinogenicity: Not available  
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects  
 Reproductive toxicity: No evidence of adverse effects on

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

sexual function and fertility, or on development, based on animal experiments.

Dimethyl Sulfide

Carcinogenicity: Not available  
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects  
 Reproductive toxicity: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

**11.2****Information on other hazards****Scentinel® F-35 Gas Odorant****Further information**

Endocrine disrupting properties

: Solvents may degrease the skin.  
 : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 12: Ecological information****12.1****Toxicity****Toxicity to fish**

t-Butyl Mercaptan : LC50: 34 mg/l  
 Exposure time: 96 h  
 Species: Oncorhynchus mykiss (rainbow trout)  
 semi-static test Method: OECD Test Guideline 203

Dimethyl Sulfide LC50: 213 mg/l  
 Exposure time: 96 h  
 Species: Oncorhynchus mykiss (rainbow trout)  
 Method: OECD Test Guideline 203

**Toxicity to daphnia and other aquatic invertebrates**

t-Butyl Mercaptan : EC50: 6,7 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 static test Method: OECD Test Guideline 202

Dimethyl Sulfide EC50: 29 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 static test Method: OECD Test Guideline 202

**Toxicity to algae**

t-Butyl Mercaptan : EC50: 24 mg/l  
 Exposure time: 72 h  
 Species: Pseudokirchneriella subcapitata (green algae)

**Sc Sentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

Method: OECD Test Guideline 201

Dimethyl Sulfide

IC50: &gt; 113,7 mg/l

Exposure time: 72 h

Species: Selenastrum capricornutum (algae)

Method: OECD Test Guideline 201

**12.2****Persistence and degradability**

Biodegradability

: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

**12.3****Bioaccumulative potential**

Elimination information (persistence and degradability)

Bioaccumulation

t-Butyl Mercaptan

: Bioconcentration factor (BCF): 12

Method: QSAR modeled data

This material is not expected to bioaccumulate.

Dimethyl Sulfide

: No bioaccumulation is to be expected (log Pow &lt;= 4).

**12.4****Mobility in soil**

Mobility

t-Butyl Mercaptan

: Method: Calculation, Mackay Level III Fugacity Model

The product will be dispersed amongst the various environmental compartments (soil/ water/ air).

Dimethyl Sulfide

: Method: Calculation, Mackay Level III Fugacity Model

The product will be dispersed amongst the various environmental compartments (soil/ water/ air).

**12.5****Results of PBT and vPvB assessment**

Results of PBT assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6****Endocrine disrupting properties**

Endocrine disrupting properties

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7****Other adverse effects**

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

Additional ecological information : Toxic to aquatic life with long lasting effects.

**12.8****Additional Information****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard

t-Butyl Mercaptan : Toxic to aquatic life.

Dimethyl Sulfide : Harmful to aquatic life.

Long-term (chronic) aquatic hazard

t-Butyl Mercaptan : Toxic to aquatic life with long lasting effects.

Dimethyl Sulfide : This material is not expected to be harmful to aquatic organisms.

**SECTION 13: Disposal considerations****13.1****Waste treatment methods**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

For additional details, see the Exposure Scenario in the Annex portion

**SECTION 14: Transport information****14.1 - 14.7****Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.



**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II, (-18 °C c.c.), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN)

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

33, UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

**Maritime transport in bulk according to IMO instruments****SECTION 15: Regulatory information****15.1****Safety, health and environmental regulations/legislation specific for the substance or mixture  
National legislation**

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

**Water hazard class (Germany)** : WGK 3 highly water endangering**15.2****Major Accident Hazard Legislation** : 96/82/EC Update: 2003  
Highly flammable  
7b

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

Quantity 1: 5.000 t  
Quantity 2: 50.000 t


: 96/82/EC      Update: 2003  
Dangerous for the environment  
9b  
Quantity 1: 200 t  
Quantity 2: 500 t

**Notification status**

Europe REACH	:	This mixture contains only ingredients which have been registered according to Regulation (EU) No. 1907/2006 (REACH).
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On or in compliance with the active portion of the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Other AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).
Philippines PICCS	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory

**SECTION 16: Other information**

**NFPA Classification**      : Health Hazard: 2  
Fire Hazard: 3  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number      : 34290

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

**Full text of H-Statements referred to under sections 2 and 3.**

H225	Highly flammable liquid and vapor.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**Annex****1. Short title of Exposure Scenario: Distribution**

Main User Groups	:	<b>SU 3:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	:	<b>SU3:</b> Industrial Manufacturing (all)
Process category	:	<b>PROC1:</b> Use in closed process, no likelihood of exposure <b>PROC2:</b> Use in closed, continuous process with occasional controlled exposure <b>PROC3:</b> Use in closed batch process (synthesis or formulation) <b>PROC4:</b> Use in batch and other process (synthesis) where opportunity for exposure arises <b>PROC8a:</b> Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities <b>PROC8b:</b> Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities <b>PROC9:</b> Transfer of substance or preparation into small containers (dedicated filling line, including weighing) <b>PROC15:</b> Use as laboratory reagent
Environmental release category	:	<b>ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7:</b> Manufacture of substances, Formulation of preparations, Formulation in materials, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in inclusion into or onto a matrix, Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids, Industrial use of monomers for manufacture of thermoplastics, Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers, Industrial use of substances in closed systems
Further information	:	Lead substance(s) EC-No. 200-890-2 Ec-No. 200-846-2  Distribution of Substance: loading (including marine vessel/barge, rail/road car IBC loading), and repacking including drums and small packs of substance, including its distribution and associated laboratory activities.

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Use as laboratory reagent**

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**Amount used**

Remarks : Not applicable

**2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7: Manufacture of substances, Formulation of preparations, Formulation in materials, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in inclusion into or onto a matrix, Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids, Industrial use of monomers for manufacture of thermoplastics, Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers, Industrial use of substances in closed systems**

**Product characteristics**

Viscosity, dynamic : 1,6 mPa.s at 20 °C

**Environment factors not influenced by risk management**

Flow rate : 18.000 m3/d  
 Dilution Factor (River) : 10  
 Dilution Factor (Coastal Areas) : 100

**Other given operational conditions affecting environmental exposure**

Number of emission days per year : 300  
 Emission or Release Factor: Air : 0,01 %  
 Emission or Release Factor: Water : 0,001 %  
 Emission or Release Factor: Soil : 0,001 %

**Technical conditions and measures / Organizational measures**

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,9 %)  
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99,9 %)  
 Remarks : Negligible wastewater emissions as process operates without water contact.

**Conditions and measures related to municipal sewage treatment plant**

Flow rate of sewage treatment plant effluent : 2.000 m3/d  
 Remarks : Not applicable as there is no release to wastewater.

**Conditions and measures related to external treatment of waste for disposal**

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste**

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process**

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**(synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Use as laboratory reagent**

**Organizational measures to prevent /limit releases, dispersion and exposure**

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374.

**3. Exposure estimation and reference to its source****Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio (PEC/PNEC):
ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7	EUSES		Freshwater		0,107 µg/L	0,016
			Marine water		0,10 µg/L	0,149
			Freshwater sediment		0,44 µg/kg	0,0379
			Marine sediment		0,411 µg/kg	0,354
			Soil		1,63 µg/kg	0,236

ERC1: Manufacture of substances  
 ERC2: Formulation of preparations  
 ERC3: Formulation in materials  
 ERC4: Industrial use of processing aids in processes and products, not becoming part of articles  
 ERC5: Industrial use resulting in inclusion into or onto a matrix  
 ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)  
 ERC6b: Industrial use of reactive processing aids  
 ERC6c: Industrial use of monomers for manufacture of thermoplastics  
 ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers  
 ERC7: Industrial use of substances in closed systems

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

**1. Short title of Exposure Scenario: Formulation**

Main User Groups	:	<b>SU 3:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	:	<b>SU 10:</b> Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
Process category	:	<p><b>PROC1:</b> Use in closed process, no likelihood of exposure</p> <p><b>PROC2:</b> Use in closed, continuous process with occasional controlled exposure</p> <p><b>PROC3:</b> Use in closed batch process (synthesis or formulation)</p> <p><b>PROC4:</b> Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p><b>PROC5:</b> Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)</p> <p><b>PROC8a:</b> Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p><b>PROC8b:</b> Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities</p> <p><b>PROC9:</b> Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p><b>PROC15:</b> Use as laboratory reagent</p>
Environmental release category	:	<b>ERC2:</b> Formulation of preparations
Further information	:	<p>Lead substance(s) EC-No. 200-890-2 Ec-No. 200-846-2</p> <p>Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials, transfers, mixing, large and small scale packing, maintenance and associated laboratory activities.</p>

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact), Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Transfer of substance or preparation into small containers (dedicated filling line, including**

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**weighing), Use as laboratory reagent****Amount used**

Remarks : Not applicable

**2.1 Contributing scenario controlling environmental exposure for:ERC2: Formulation of preparations****Product characteristics**

Viscosity, dynamic : 1,6 mPa.s at 20 °C

**Environment factors not influenced by risk management**

Flow rate : 18.000 m3/d

Dilution Factor (River) : 10

Dilution Factor (Coastal Areas) : 100

**Other given operational conditions affecting environmental exposure**

Number of emission days per year : 365

Emission or Release Factor: Air : 0,25 %

Emission or Release Factor: Water : 0,001 %

Emission or Release Factor: Soil : 0,01 %

**Technical conditions and measures / Organizational measures**

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: &gt; 99,8 %)

Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99,9 %)

Remarks : Negligible wastewater emissions as process operates without water contact.

**Conditions and measures related to municipal sewage treatment plant**

Flow rate of sewage treatment plant effluent : 2.000 m3/d

Remarks : Not applicable as there is no release to wastewater.

**Conditions and measures related to external treatment of waste for disposal**

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste**

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact), Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Transfer**



**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**of substance or preparation into small containers (dedicated filling line, including weighing), Use as laboratory reagent**

**Organizational measures to prevent /limit releases, dispersion and exposure**

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374.

**3. Exposure estimation and reference to its source****Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio (PEC/PNEC):
ERC2	EUSES		Freshwater		0,0395 µg/L	0,00589
			Marine water		0,0367 µg/L	0,0548
			Freshwater sediment		0,162 µg/kg	0,0140
			Marine sediment		0,151 µg/kg	0,130
			Soil		1,71 µg/kg	0,248

ERC2: Formulation of preparations

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

**1. Short title of Exposure Scenario: Use as an intermediate**

Main User Groups	: <b>SU 3:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	: <b>SU3, SU8, SU9:</b> Industrial Manufacturing (all), Manufacture of bulk, large scale chemicals (including petroleum products), Manufacture of fine chemicals
Process category	: <b>PROC1:</b> Use in closed process, no likelihood of exposure <b>PROC2:</b> Use in closed, continuous process with occasional controlled exposure <b>PROC3:</b> Use in closed batch process (synthesis or formulation) <b>PROC4:</b> Use in batch and other process (synthesis) where opportunity for exposure arises

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**PROC8a:** Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

**PROC8b:** Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities

**PROC15:** Use as laboratory reagent

Environmental release category : **ERC6a:** Industrial use resulting in manufacture of another substance (use of intermediates)

Further information : Lead substance(s)  
EC-No. 200-890-2  
Ec-No. 200-846-2

Use as an isolated intermediate under strictly controlled conditions

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent**

**Amount used**

Remarks : Not applicable

**2.1 Contributing scenario controlling environmental exposure for:ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)**

**Product characteristics**

Viscosity, dynamic : 1,6 mPa.s at 20 °C

**Environment factors not influenced by risk management**

Flow rate : 18.000 m3/d  
Dilution Factor (River) : 10  
Dilution Factor (Coastal Areas) : 100

**Other given operational conditions affecting environmental exposure**

Number of emission days per year : 300  
Emission or Release Factor: Air : 0,5 %  
Emission or Release Factor: Water : 1,0 %  
Emission or Release Factor: Soil : 0,1 %

**Technical conditions and measures / Organizational measures**

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,5 %)  
Water : Treat onsite wastewater (prior to receiving water discharge) to

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

Remarks : provide the required removal efficiency of  $\geq$  (%):  
(Effectiveness: 99 %)  
: Negligible wastewater emissions as process operates without water contact.

**Conditions and measures related to municipal sewage treatment plant**

Flow rate of sewage treatment : 2.000 m<sup>3</sup>/d  
plant effluent  
Remarks : Not applicable as there is no release to wastewater.

**Conditions and measures related to external treatment of waste for disposal**

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste**

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent**

**Organizational measures to prevent /limit releases, dispersion and exposure**

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374.

**3. Exposure estimation and reference to its source****Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio (PEC/PNEC):
ERC6a	EUSES		Freshwater		0,178 µg/L	0,0266
			Marine water		0,167 µg/L	0,249
			Freshwater sediment		0,732 µg/kg	0,0631
			Marine water		0,685 µg/kg	0,590
			Soil		2,52 µg/kg	0,364

ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

1. Short title of Exposure Scenario: **Injection as odorant in fuels – industrial**

Main User Groups	: <b>SU 3:</b> Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	: <b>SU3:</b> Industrial Manufacturing (all)
Process category	: <b>PROC1:</b> Use in closed process, no likelihood of exposure <b>PROC2:</b> Use in closed, continuous process with occasional controlled exposure <b>PROC3:</b> Use in closed batch process (synthesis or formulation) <b>PROC8a:</b> Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities <b>PROC8b:</b> Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities <b>PROC15:</b> Use as laboratory reagent
Environmental release category	: <b>ERC7:</b> Industrial use of substances in closed systems
Further information	: Lead substance(s) EC-No. 200-890-2 Ec-No. 200-846-2  Covers injection as odourant in fuel and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent**

**Amount used**  
Remarks : Not applicable

**2.1 Contributing scenario controlling environmental exposure for:ERC7: Industrial use of substances in closed systems**

**Product characteristics**  
Viscosity, dynamic : 1,6 mPa.s at 20 °C

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**Environment factors not influenced by risk management**

Flow rate : 18.000 m3/d  
 Dilution Factor (River) : 10  
 Dilution Factor (Coastal Areas) : 100

**Other given operational conditions affecting environmental exposure**

Number of emission days per year : 365  
 Emission or Release Factor: Air : 0,25 %  
 Emission or Release Factor: Water : 0,001 %  
 Emission or Release Factor: Soil : 0 %

**Technical conditions and measures / Organizational measures**

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,8 %)  
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99,9 %)  
 Remarks : Soil emission controls are not applicable as there is no direct release to soil.  
 Remarks : Negligible wastewater emissions as process operates without water contact.  
 Remarks : Wastewater emissions generated from equipment cleaning with water.

**Conditions and measures related to municipal sewage treatment plant**

Flow rate of sewage treatment plant effluent : 2.000 m3/d  
 Remarks : Not applicable as there is no release to wastewater.

**Conditions and measures related to external treatment of waste for disposal**

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste**

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

**2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent**

**Organizational measures to prevent /limit releases, dispersion and exposure**

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374.

**Scentinel® F-35 Gas Odorant**

Version 3.2

Revision Date 2023-08-03

**3. Exposure estimation and reference to its source****Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio (PEC/PNEC):
ERC7	EUSES		Freshwater		0,0324 µg/L	0,00484
			Marine water		0,0301 µg/L	0,0449
			Marine sediment		0,124 µg/kg	0,107
			Freshwater sediment		0,133 µg/kg	0,0115
			Soil		1,61 µg/kg	0,233

ERC7: Industrial use of substances in closed systems

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario**

When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis. When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterization ratios are expected to be less than 1.