

# AlphaPlus® 1-Decene

### Version 2.15

Revision Date 2023-10-30

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

### **Product information**

Product Name	:	AlphaPlus® 1-Decene
Material	:	1128500, 1095875, 1068252, 1037000, 1015428, 1036999

### **EC-No.Registration number**

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
1-Decene	872-05-9 212-819-2	Chevron Phillips Chemical Company LP 01-2119486878-12-0006

### 1.2

### Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses Supported	<ul> <li>Manufacture         Use as an intermediate         Formulation         Use in coatings – industrial         Use in coatings – professional         Use in Coatings - Consumer         Use in Oil and Gas field drilling and production operations -         Industrial         Use in polymer production – industrial</li> </ul>
1.3 Details of the supplier of t	he safety data sheet

# 

Company	: Chevron Phillips Chemical Company LP
	Normal Alpha Olefins (NAO)
	10001 Six Pines Drive
	The Woodlands, TX 77380

### Local

SDS Number:100000068089

:	Chevron Phillips Chemicals International N.V. Airport Plaza (Stockholm Building) Leonardo Da Vincilaan 19 1831 Diegem Belgium
---	---

SDS Requests: (800) 852-5530

Version 2.15

Revision Date 2023-10-30

### Responsible Party: Product Safety Group Email:sds@cpchem.com

#### 1.4

### **Emergency telephone:**

Health:

866.442.9628 (North America) 1.832.813.4984 (International) Transport: CHEMTREC 800.424.9300 or 703.527.3887(int'l) Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090 Mexico CHEMTREC 01-800-681-9531 (24 hours) South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600 Argentina: +(54)-1159839431 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week) Belgium: 070 245 245 (24 hours/day, 7 days/week) Bulgaria: +359 2 9154 233 Croatia: +3851 2348 342 (24 hours/day, 7 days/week) Cyprus: 1401 Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402 Denmark: Danish Poison Center (Giftlinien): +45 8212 1212 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Finland: 0800 147 111 09 471 977 (24 hours/day) France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week) Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Greece: (0030) 2107793777 (24 hours/day, 7 days/week) Hungary: +36-80-201-199 (24 hours/day, 7 days/week) Iceland: 543 2222 (24 hours/day, 7 days/week) Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.) Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Lithuania: +370 (85) 2362052 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week) Malta: +356 2395 2000 The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week) Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Portugal: CIAV phone number: +351 800 250 250 Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week) Sweden: 112 - ask for Poisons Information Responsible Department : Product Safety and Toxicology Group E-mail address : SDS@CPChem.com

Website	:	www.CPChem.com

### **SECTION 2: Hazards identification**

### 2.1

Classification of the substance or mixture

Version 2.15

### REGULATION (EC) No 1272/2008

Flammable liquids, Category 3

Aspiration hazard, Category 1

Short-term (acute) aquatic hazard, Category 1 Long-term (chronic) aquatic hazard, Category 1 H226: Flammable liquid and vapor. H304: May be fatal if swallowed and enters airways. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects.

#### 2.2

### Labeling (REGULATION (EC) No 1272/2008)

	Hazard pictograms	:		
	Signal Word	:	Danger	
	Hazard Statements	:	H226 H304 H410	Flammable liquid and vapor. May be fatal if swallowed and enters airways. Very toxic to aquatic life with long lasting effects.
	Precautionary Statements	:	<b>Prevention:</b> P210 P273 <b>Response:</b> P301 + P310 P331 P370 + P378 P391	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Collect spillage.
	Hazardous ingredients which • 872-05-9 1-De			e label:
2.3	Other hazards Results of PBT and vPvB assessment	:	be either persist	mixture contains no components considered to ent, bioaccumulative and toxic (PBT), or very ery bioaccumulative (vPvB) at levels of 0.1%
	Endocrine disrupting properties	:	considered to h	mixture does not contain components ave endocrine disrupting properties according le 57(f) or Commission Delegated regulation
SD	S Number:100000068089			3/88

### SAFETY DATA SHEET

# AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

### 3.1 - 3.2

### Substance or Mixture

Synonyms	: Decene-n-1
	NAO 10
	Decene-1 (C10)
	(C10 H20)

Molecular formula : C10H20

### Hazardous ingredients

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]	Specific Conc. Limits, M-factors and ATEs
1-Decene	872-05-9 212-819-2	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	96 - 100	M [Acute]=1 M [Chronic]=1
2-Butyl-1-Hexene	6795-79-5	Flam. Liq. 3; H226 Asp. Tox. 1; H304	1 - 5	
2-Ethyl-1-Octene	51655-64-2	Flam. Liq. 3; H226 Asp. Tox. 1; H304	1 - 5	

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **SECTION 4: First aid measures**

### 4.1

### Description of first-aid measures

General advice	:	Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
4.2 Most important symptoms Notes to physician	and	l effects, both acute and delayed

Alı	ohaPlus® 1-Decene		SAFETY DATA SHEET
	sion 2.15		Revision Date 2023-10-30
	Symptoms	:	No data available.
4.3	Risks Indication of any immediate	: e me	No data available. edical attention and special treatment needed
	Treatment	:	No data available.
SEC	CTION 5: Firefighting measu	res	
	Flash point	:	49°C (120°F) Method: closed cup
	Autoignition temperature	:	210°C (410°F)
5.1	Extinguishing media		
	Suitable extinguishing media	:	Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.
	Unsuitable extinguishing media	:	High volume water jet.
5.2	<b>Special hazards arising fro</b> Specific hazards during fire fighting		<b>he substance or mixture</b> Do not allow run-off from fire fighting to enter drains or water courses.
5.3	Advice for firefighters Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
	Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
	Fire and explosion protection	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
	Hazardous decomposition products	:	Carbon oxides.
SEC	CTION 6: Accidental release	me	asures
5.1			
-	Personal precautions, prot	ecti	ve equipment and emergency procedures
	Personal precautions	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
	S Number:100000068089		5/88

AlphaPlus® 1-Decene
---------------------

Version 2.15

6.2	
-----	--

6.2	Environmental precautions	
	Environmental precautions :	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3		
6.4	Methods and materials for co Methods for cleaning up :	Intainment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
0.4	Reference to other sections	
	Reference to other sections :	For personal protection see section 8. For disposal considerations see section 13.
SEC	CTION 7: Handling and storage	)
7.1	Precautions for safe handling Handling	3
	Advice on safe handling :	Avoid formation of aerosol. Do not breathe vapors/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
	Advice on protection : against fire and explosion	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
7.2	Conditions for safe storage, i	including any incompatibilities
	Storage	
	Requirements for storage : areas and containers	No smoking. Keep container tightly closed in a dry and well- ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
SEC	CTION 8: Exposure controls/pe	ersonal protection
8.1	Control parameters	
	PNEC	: Fresh water
SDS	S Number:100000068089	6/88

Version 2.15

SAFETY DATA SHEE	SAFETY	DATA	SHEET
------------------	--------	------	-------

Revision Date 2023-10-30

	Value: 0,0012 mg/l
PNEC	: Sea water Value: 0,0012 mg/l
PNEC	: Fresh water sediment Value: 2,14 mg/kg
PNEC	: Sea sediment Value: 2,14 mg/kg
PNEC	: Soil Value: 0,43 mg/kg

### 8.2

#### Exposure controls Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

### Personal protective equipment

Respiratory protection	: If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
Hand protection	: The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggles.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
Hygiene measures	: When using do not eat or drink. When using do not smoke.
SDS Number:100000068089	7/88

Version 2.15

Revision Date 2023-10-30

Wash hands before breaks and at the end of workday.

For additional details, see the Exposure Scenario in the Annex portion

### **SECTION 9: Physical and chemical properties**

Appearance	
Form Physical state Color	: liquid : liquid : Clear, colorless
Safety data	
Flash point	: 49°C (120°F) Method: closed cup
Lower explosion limit	: 0,7 %(V)
Upper explosion limit	: 5,9 %(V)
Oxidizing properties	: no
Autoignition temperature	: 210°C (410°F)
Thermal decomposition	: No data available
Molecular formula	: C10H20
Molecular weight	: 140,3 g/mol
рН	: Not applicable
Freezing point	: -66°C (-87°F)
Pour point	No data available
Boiling point/boiling range	: 170,56°C (339,01°F)
Vapor pressure	: 0,21 kPa at 25°C (77°F)
	2,30 kPa at  65°C (149°F)
Relative density	: 0,75 at 15,6 °C (60,1 °F)
Density	: 745 kg/m3 at 15°C (59°F)
	740 kg/m3 at 20°C (68°F)

AlphaPlus® 1-Decene	SAFETY DATA SHEE
Version 2.15	Revision Date 2023-10-3
	717 kg/m3 at 50°C (122°F)
Water solubility	: Soluble in hydrocarbon solvents; insoluble in water.
Partition coefficient: n- octanol/water	: No data available
Viscosity, kinematic	: 1,1 cSt at 20°C (68°F)
Relative vapor density	: 4,84 (Air = 1.0)
Evaporation rate	: No data available
SECTION 10: Stability and reacti	vity
10.1	
Reactivity	: Stable at normal ambient temperature and pressure.
0.2	
Chemical stability	<ul> <li>This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.</li> </ul>
0.3 Possibility of hazardous rea	ctions
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur.
	Further information: No decomposition if stored and applied as directed.
	Hazardous reactions: Vapors may form explosive mixture with air.
0.4 Conditions to avoid	: Heat, flames and sparks.
0.5 Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Thermal decomposition	: No data available
0.6 Hazardous decomposition products	: Carbon oxides
Other data	: No decomposition if stored and applied as directed.
SDS Number:100000068089	9/88

Version 2.15

SAFETY DATA SHEET

TION 11: Toxicological inf	
Information on toxicologi	cal effects
Acute oral toxicity	
1-Decene	<ul> <li>LD50: &gt; 3.575 mg/kg</li> <li>Species: Rat</li> <li>Sex: male and female</li> <li>Method: Fixed Dose Method</li> <li>Information given is based on data obtained from similar substances.</li> </ul>
Acute inhalation toxicity	
1-Decene	<ul> <li>LC50: &gt; 2,1 mg/l Exposure time: 4 h Species: Rat Sex: male and female Test atmosphere: vapor Method: OECD Test Guideline 403 Information given is based on data obtained from similar substances. Not classified due to data which are conclusive although insufficient for classification.</li> </ul>
Acute dermal toxicity	
1-Decene	<ul> <li>LD50: &gt; 2.000 mg/kg</li> <li>Species: Rat</li> <li>Sex: male and female</li> <li>Method: OECD Test Guideline 402</li> <li>Information given is based on data obtained from similar substances.</li> </ul>
Skin irritation	
1-Decene	: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.
<b>Eye irritation</b> 1-Decene	: No eye irritation
Sensitization	
1-Decene	: Did not cause sensitization on laboratory animals. Information given is based on data obtained from similar substances.
Repeated dose toxicity	
1-Decene	<ul> <li>Species: Rat, Male and female Sex: Male and female Application Route: Oral Dose: 0, 100, 500, 1000 mg/kg Exposure time: 13 wks</li> </ul>
Number:100000068089	10/88

haPlus® 1-Decene	SAFETY DATA SH
sion 2.15	Revision Date 2023-1
	Number of exposures: 7 d/wk NOEL: 1.000 mg/kg Method: OCED Guideline 408 Information given is based on data obtained from similar substances.
	Species: Rat, Male and female Sex: Male and female Application Route: Inhalation Dose: 0, 300, 1000, 3000 ppm Exposure time: 13 wks Number of exposures: 6 hr/d, 5 d/wk NOEL: 3000 ppm Method: OECD Guideline 413 Information given is based on data obtained from similar substances.
Genotoxicity in vitro	
1-Decene	<ul> <li>Test Type: Ames test Metabolic activation: with and without metabolic activation Method: Mutagenicity (Escherichia coli - reverse mutation assay) Result: negative</li> </ul>
	Test Type: Mammalian cell gene mutation assay Metabolic activation: with and without metabolic activation Method: OECD Guideline 476 Result: negative
	Test Type: Chromosome aberration test in vitro Metabolic activation: with and without metabolic activation Method: OECD Guideline 473 Result: negative
Genotoxicity in vivo	
1-Decene	: Test Type: Micronucleus test Species: Mouse Method: Mutagenicity (micronucleus test) Result: negative
Reproductive toxicity	
1-Decene	<ul> <li>Species: Rat Sex: male</li> <li>Application Route: Oral diet</li> <li>Dose: 0, 100, 500, 1000 mg/kg</li> <li>Method: OECD Guideline 421</li> <li>NOAEL Parent: 1.000 mg/kg</li> <li>NOAEL F1: 1.000 mg/kg</li> </ul>
AlphaPlus® 1-Decene	
Aspiration toxicity	<ul> <li>May be fatal if swallowed and enters airways. Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity hazard.</li> </ul>
S Number:100000068089	11/88

Mutagenici did not sho Teratogeni fetal develo Reproducti on fertility. 1.2 Information on other hazards AlphaPlus® 1-Decene Further information : Solvents m Endocrine disrupting : The substa considered to REACH (EU) 2017/ levels of 0. SECTION 12: Ecological information 2.1 Toxicity Toxicity to fish 1-Decene : LC50: 0,12 Exposure t Species: C semi-static Information substances Toxicity to daphnia and other aquatic inve 1-Decene : EC50: 0,56 Exposure t Species: D Method: O Toxicity to algae 1-Decene : EC50: 1 - 6 Exposure t Species: P	Revision Date 2023-10-30 nicity: Not available ty: Tests on bacterial or mammalian cell cultures w mutagenic effects. city: Animal testing did not show any effects on opment. ve toxicity: Animal testing did not show any effects		
1-Decene       : Carcinoger Mutagenici did not sho Teratogeni fetal develo Reproducti on fertility.         1.2       Information on other hazards         AlphaPlus® 1-Decene Further information       : Solvents m Endocrine disrupting properties         Endocrine disrupting properties       : The substa considered to REACH (EU) 2017/ levels of 0.         SECTION 12: Ecological information         SECTION 12: Ecological information         2.1 Toxicity to fish         1-Decene       : LC50: 0,12 Exposure t Species: C Species: C         Toxicity to daphnia and other aquatic inve 1-Decene         1-Decene       : EC50: 0,56 Exposure t Species: D Method: O         Toxicity to algae         1-Decene       : EC50: 1 - 4 Exposure t Species: P	ty: Tests on bacterial or mammalian cell cultures w mutagenic effects. city: Animal testing did not show any effects on opment.		
1-Decene       : Carcinoger Mutagenici did not sho Teratogeni fetal develo Reproducti on fertility.         1.2       Information on other hazards         AlphaPlus® 1-Decene Further information       : Solvents m         Endocrine disrupting       : The substa considered to REACH (EU) 2017/ levels of 0.         SECTION 12: Ecological information         2.1 Toxicity Toxicity to fish         1-Decene       : LC50: 0,12 Exposure t Species: C semi-static Information         Toxicity to daphnia and other aquatic inve         1-Decene       : EC50: 0,56 Exposure t Species: D Method: O         Toxicity to algae         1-Decene       : EC50: 1 - 4 Exposure t Species: P	ty: Tests on bacterial or mammalian cell cultures w mutagenic effects. city: Animal testing did not show any effects on opment.		
AlphaPlus® 1-Decene         Further information       : Solvents m         Endocrine disrupting       : The substaconsidered to REACH         properties       considered to REACH         (EU) 2017/levels of 0.         SECTION 12: Ecological information         Image: Section 12: Ecological information         SECTION 12: Ecological information         Image: Section 1-1         Toxicity to daphnia and other aquatic inverted Species: D         I-Decene       : EC50: 0.56         Exposure to Species: D         Method: O         Toxicity to algae         1-Decene       : EC50: 1 - f         Exposure to Species: P			
Further information       : Solvents m         Endocrine disrupting       : The substaconsidered to REACH (EU) 2017/levels of 0.         SECTION 12: Ecological information         Sector         Sector         Toxicity to fish         1-Decene         1-Dec			
2.1 Toxicity to fish 1-Decene : LC50: 0,12 Exposure t Species: O semi-static Information substances Toxicity to daphnia and other aquatic inve 1-Decene : EC50: 0,56 Exposure t Species: D Method: O Toxicity to algae 1-Decene : EC50: 1 - 7 Exposure t Species: P	ay degrease the skin. nce/mixture does not contain components to have endocrine disrupting properties according Article 57(f) or Commission Delegated regulation 2100 or Commission Regulation (EU) 2018/605 at 1% or higher.		
Toxicity         Toxicity to fish         1-Decene       : LC50: 0,12         Exposure to Species: Or Semi-static Information substances         Toxicity to daphnia and other aquatic invection         1-Decene       : EC50: 0,56         Exposure to Species: D Method: Or Method:			
Toxicity         Toxicity to fish         1-Decene       : LC50: 0,12 Exposure to Species: One Species: Dong Species: Provide Spec			
<ul> <li>1-Decene : LC50: 0,12 Exposure t Species: C semi-static Information substances</li> <li>Toxicity to daphnia and other aquatic inve</li> <li>1-Decene : EC50: 0,56 Exposure t Species: D Method: O</li> <li>Toxicity to algae</li> <li>1-Decene : EC50: 1 - 7 Exposure t Species: P</li> </ul>			
Exposure t Species: C semi-static Information substances <b>Toxicity to daphnia and other aquatic inve</b> 1-Decene : EC50: 0,56 Exposure t Species: D Method: O <b>Toxicity to algae</b> 1-Decene : EC50: 1 - 7 Exposure t Species: P			
<ul> <li>1-Decene : EC50: 0,56 Exposure t Species: D Method: O</li> <li>Toxicity to algae</li> <li>1-Decene : EC50: 1 - 7 Exposure t Species: P</li> </ul>	ime: 96 h ncorhynchus mykiss (rainbow trout) test Method: OECD Test Guideline 203 given is based on data obtained from similar		
Exposure t Species: D Method: O Toxicity to algae 1-Decene : EC50: 1 - 7 Exposure t Species: P	Toxicity to daphnia and other aquatic invertebrates		
1-Decene : EC50: 1 - Exposure t Species: P	ime: 48 h		
Exposure t Species: P			
M-Factor	(Acute Aquat. Tox.) 1		
DS Number:10000068089	(Acute Aquat. Tox.) 1 (Chron. Aquat. Tox.) 1		

AlphaPlus® 1-Decene	SAFETY DATA SHEET				
Version 2.15	Revision Date 2023-10-30				
Toxicity to daphnia and oth	Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)				
1-Decene	: NOEC: 0,0194 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Analytical monitoring: yes Test substance: yes Method: OECD Test Guideline 211				
12.2 Persistence and degradabi	lity				
Biodegradability	: This material is expected to be readily biodegradable.				
12.3 Bioaccumulative potential Elimination information (pers					
Bioaccumulation					
1-Decene	: No data available				
12.4 Mobility in soil					
Mobility					
1-Decene	: No data available				
12.5 Results of PBT and vPvB a Results of PBT assessment	<ul> <li>ssessment</li> <li>This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.</li> </ul>				
12.6 Endocrine disrupting properties					
Endocrine disrupting properties	: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.				
12.7 Other adverse effects					
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.				
12.8 Additional Information					
Ecotoxicology Assessmen	t				
SDS Number:100000068089	13/88				

Version 2.15

Revision Date 2023-10-30

Short-term (acute) aqu		
1-Decene	: Very toxic to aquatic life.	
Long-term (chronic) aq	uatic hazard	

1-Decene : Very toxic to aquatic life with long lasting effects.

### **SECTION 13: Disposal considerations**

### 13.1

### Waste treatment methods

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	The product should not be allowed to enter drains, wa courses or the soil. Do not contaminate ponds, water ditches with chemical or used container. Send to a lic waste management company.	ways or
Contaminated packaging	Empty remaining contents. Dispose of as unused pro Do not re-use empty containers. Do not burn, or use torch on, the empty drum.	

For additional details, see the Exposure Scenario in the Annex portion

### **SECTION 14: Transport information**

### 14.1 - 14.7

### Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

### US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III

### IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III, (49 °C c.c.), MARINE POLLUTANT, (1-DECENE)

### IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, III

### SDS Number:100000068089

# AlphaPlus® 1-Decene

Version 2.15

ADR (AGREEMENT ON DA UN3295, HYDROCARBO HAZARDOUS, (1-DECEN	NS, LIQUID, N.O	<b>DS BY ROAD (EUROPE))</b> .S., 3, III, (D/E), ENVIRONMENTALL	.Y
DANGEROUS GOODS (EU	ROPE))	<b>TERNATIONAL TRANSPORT OF</b> O.S., 3, III, ENVIRONMENTALLY HA	AZARDOUS, (1-
OF DANGEROUS GOODS E UN3295, HYDROCARBO DECENE) For Tank Vessels and/or	<b>BY INLAND WAT</b> INS, LIQUID, N.O Barges: INS, LIQUID, N.O	ING THE INTERNATIONAL CARRIA ERWAYS) .S., 3, III, ENVIRONMENTALLY HAZ .S., 3, (N1, CMR, F), III, ENVIRONM	ZARDOUS, (1-
Other information Maritime transport in bulk		•	
SECTION 15: Regulatory inform	ation		
15.1 Safety, health and environr National legislation	mental regulatior	ns/legislation specific for the subs	tance or mixture
	d of the Council or	lune 2020 amending Regulation (EC n the Registration, Evaluation, Author	
Water hazard class (Germany)	:WGK 3 high	nly water endangering	
15.2 Chamical Safaty Assessme			
Chemical Safety Assessme Components : d	ec-1-ene	A Chemical Safety Assessment has been carried out for this substance.	212-819-2
Major Accident Hazard Legislation	-	5.000 t	
	9a Quantity 1:	100 t	
SDS Number 10000000000	•		
SDS Number:100000068089		15/88	

Version 2.15

Version 2.15	Revision Date 2023-10-30
	Quantity 2: 200 t
:	ZEU_SEVES3 Update: FLAMMABLE LIQUIDS P5c Quantity 1: 5.000 t Quantity 2: 50.000 t
:	96/82/EC Update: 2003 Flammable. 6 Quantity 1: 5.000 t Quantity 2: 50.000 t
:	ZEU_SEVES3 Update: ENVIRONMENTAL HAZARDS E1 Quantity 1: 100 t Quantity 2: 200 t
Notification status Europe REACH Switzerland CH INV United States of America (USA) TSCA Canada DSL Australia AIIC New Zealand NZIoC Japan ENCS Korea KECI	<ul> <li>This product is in full compliance according to REACH regulation 1907/2006/EC.</li> <li>On the inventory, or in compliance with the inventory</li> <li>On or in compliance with the active portion of the TSCA inventory</li> <li>All components of this product are on the Canadian DSL</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>Description of the registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).</li> </ul>
Philippines PICCS Taiwan TCSI China IECSC	<ul> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> </ul>
SECTION 16: Other information	
	Health Hazard: 1 Fire Hazard: 2 Reactivity Hazard: 0
SDS Number:100000068089	16/88

Revision Date 2023-10-30

Version 2.15

### Further information

Legacy SDS Number : PE0018

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ŀ	Key or legend to abbreviations and a	cronyms used	d in the safety data sheet
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

Full text of H-Statements referred to under sections 2 and 3.

SAFETY DATA SHEET

Version 2.15	Revision Date 2023-10-30
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Version 2.15

SAFETY DATA SHEET

Revision Date 2023-10-30

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

# Annex: Exposure Scenarios

### Table of Contents

Number	Title	
ES 1	Manufacture; Industrial uses (SU3).	
ES 2	Use as an intermediate; Industrial uses (SU3).	
ES 3	Formulation; Industrial uses (SU3).	
ES 4	Use in coatings – industrial; Industrial uses (SU3).	
ES 5	Use in coatings – professional; Professional uses (SU22).	
ES 6	Use in Coatings - Consumer; Consumer uses (SU21).	
ES 7	Use in Oil and Gas field drilling and production operations - Industrial; Industrial uses (SU3).	
ES 8	Use in polymer production – industrial; Industrial uses (SU3).	

		SAFE	TY DATA SHEET
-	Plus® 1-Decene		D.1. 0000 40 00
Version 2		Revision	Date 2023-10-30
ES 1: Ma	anufacture; Industrial uses (SU3).		
1.1. Title	esection		
Exposur	e Scenario name : Manufacture		
Structur	ed Short Title : Manufacture; Industrial us	es (SU3).	
Substan	<b>ce</b> : dec-1-ene <u>EC-No.:</u> 212-819-2		
Environ	ment		
CS 1	Manufacture		ERC1, ERC4
Worker			
CS 2	General measures applicable to all activities, Genera irritants)	l measures (skin	PROC1
CS 3	General measures applicable to all activities, Genera irritants)	l measures (skin	PROC2
CS 4	General measures applicable to all activities, Genera irritants)	l measures (skin	PROC3
CS 5	General measures applicable to all activities, Genera irritants)	l measures (skin	PROC4
CS 6	General measures applicable to all activities, Genera irritants)	l measures (skin	PROC8a
CS 7	General measures applicable to all activities, Genera irritants)	l measures (skin	PROC8b
CS 8	General measures applicable to all activities, Genera irritants)	l measures (skin	PROC15
1.2.1. Co	ditions of use affecting exposure ntrol of environmental exposure: Manufacture of the su processing aid at industrial site (no inclusion into or or		Jse of non-
Product	(article) characteristics		
Covers p	ercentage substance in the product up to 100 %.		
Amount	used (or contained in articles), frequency and duration	of use/exposure	
Maximun (MSafe)	n allowable site tonnage : 352.467 kg/day		
Release			
Emission	a days : 300		
Technica	al and organisational conditions and measures		
SDS Num	nber:10000068089 21/	/88	

SAFETY DATA SHEET

Version 2.15

Risk from environmental exposure Air - minimum efficiency of 90 % Water - minimum efficiency of 97,4	
Conditions and measures related	to sewage treatment plant
STP type	: Municipal sewage treatment plant
STP sludge treatment	<ul> <li>Prevent discharge of undissolved substance to or recover fror wastewater.</li> <li>Do not apply industrial sludge to natural soils.</li> <li>Sewage sludge should be incinerated, contained or reclaimed</li> </ul>
STP effluent	: 2.000 m3/d
Conditions and measures relate	to treatment of waste (including article waste)
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Other conditions affecting enviro	nmental exposure
Receiving surface water flow	: 18.000 m3/d
Local freshwater dilution factor	: 40
Local marine water dilution factor	: 100
likelihood of exposure or proces	es with equivalent containment conditions (PROC1)
likelihood of exposure or process Product (article) characteristics	es with equivalent containment conditions (PROC1)
· ·	
Product (article) characteristics	
Product (article) characteristics Covers percentage substance in th Physical form of product	e product up to 100 %. : Liquid, vapour pressure < 0.5 kPa at Standard Temperature
Product (article) characteristics Covers percentage substance in th Physical form of product	e product up to 100 %. : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Product (article) characteristics Covers percentage substance in th Physical form of product Amount used (or contained in ar	e product up to 100 %. : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure icles), frequency and duration of use/exposure : Covers daily exposures up to 8 hours
Product (article) characteristics Covers percentage substance in th Physical form of product Amount used (or contained in ar Duration Technical and organisational co Do not ingest. If swallowed then se Avoid direct skin contact with produ (tested to EN374) if hand contact w occur. Wash off any skin contamina	<ul> <li>e product up to 100 %.</li> <li>: Liquid, vapour pressure &lt; 0.5 kPa at Standard Temperature and Pressure</li> <li>icles), frequency and duration of use/exposure</li> <li>: Covers daily exposures up to 8 hours</li> <li>iditions and measures</li> <li>ek immediate medical assistance.</li> <li>ct. Identify potential areas for indirect skin contact. Wear gloves ith substance likely. Clean up contamination/spills as soon as they ition immediately. Provide basic employee training to prevent / ny skin problems that may develop.</li> </ul>
<ul> <li>Product (article) characteristics</li> <li>Covers percentage substance in the Physical form of product</li> <li>Amount used (or contained in are Duration</li> <li>Technical and organisational condition</li> <li>Do not ingest. If swallowed then see Avoid direct skin contact with product (tested to EN374) if hand contact with</li></ul>	e product up to 100 %. : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure iicles), frequency and duration of use/exposure : Covers daily exposures up to 8 hours iditions and measures ek immediate medical assistance. ct. Identify potential areas for indirect skin contact. Wear gloves ith substance likely. Clean up contamination/spills as soon as they tion immediately. Provide basic employee training to prevent / ny skin problems that may develop.
<ul> <li>Product (article) characteristics</li> <li>Covers percentage substance in the Physical form of product</li> <li>Amount used (or contained in ar Duration</li> <li>Technical and organisational contained direct skin contact with product (tested to EN374) if hand contact with product (tested to EN374) if hand contact wo occur. Wash off any skin contaminational to report a No other specific measures identification</li> </ul>	e product up to 100 %. : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure iicles), frequency and duration of use/exposure : Covers daily exposures up to 8 hours iditions and measures ek immediate medical assistance. ct. Identify potential areas for indirect skin contact. Wear gloves ith substance likely. Clean up contamination/spills as soon as they tion immediately. Provide basic employee training to prevent / ny skin problems that may develop.
Product (article) characteristics Covers percentage substance in the Physical form of product Amount used (or contained in ar Duration Technical and organisational co Do not ingest. If swallowed then se Avoid direct skin contact with product (tested to EN374) if hand contact with occur. Wash off any skin contamina- minimise exposures and to report a No other specific measures identifie Other conditions affecting worked	e product up to 100 %. : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure icles), frequency and duration of use/exposure : Covers daily exposures up to 8 hours iditions and measures ek immediate medical assistance. ct. Identify potential areas for indirect skin contact. Wear gloves ith substance likely. Clean up contamination/spills as soon as they ith substance likely. Clean up contamination/spills as soon as they ith substance likely. Provide basic employee training to prevent / ny skin problems that may develop. ed. rs exposure : Assumes use at not more than 20°C above ambient

	SAFETY DATA SHEET
AlphaPlus® 1-Decene	
Version 2.15	Revision Date 2023-10-30
	Chemical production or refinery in closed continuous process are or processes with equivalent containment conditions
Product (article) characteristics	
Covers percentage substance in the	product up to 100 %.
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amount used (or contained in arti	cles), frequency and duration of use/exposure
Duration	: Covers daily exposures up to 8 hours
Technical and organisational con	ditions and measures
(tested to EN374) if hand contact wit	ct. Identify potential areas for indirect skin contact. Wear gloves th substance likely. Clean up contamination/spills as soon as they tion immediately. Provide basic employee training to prevent / ny skin problems that may develop.
Other conditions affecting worker	's exposure
Temperature	: Assumes use at not more than 20°C above ambient temperature.
	Manufacture or formulation in the chemical industry in closed controlled exposure or processes with equivalent containment
Product (article) characteristics	
Covers percentage substance in the	product up to 100 %.
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amount used (or contained in arti	cles), frequency and duration of use/exposure
Duration	: Covers daily exposures up to 8 hours
Technical and organisational con	ditions and measures
(tested to EN374) if hand contact wit	ct. Identify potential areas for indirect skin contact. Wear gloves th substance likely. Clean up contamination/spills as soon as they tion immediately. Provide basic employee training to prevent / ny skin problems that may develop.
Other conditions affecting worker	rs exposure
Temperature	: Assumes use at not more than 20°C above ambient
SDS Number:100000068089	23/88

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

temperature.

# 1.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

### **Product (article) characteristics**

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 1.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

# Product (article) characteristics Covers percentage substance in the product up to 100 %. Physical form of product : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure</td>

### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

### Other conditions affecting workers exposure

SDS Number:100000068089

### AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

Temperature

Assumes use at not more than 20°C above ambient temperature.

# 1.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

### **Product (article) characteristics**

Covers percentage substance in the product up to 100 %.

Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
--------------------------	---

Amount used (or contained in articles), frequency and duration of use/exposure

:

Duration

: Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

### Other conditions affecting workers exposure

Temperature

Assumes use at not more than 20°C above ambient temperature.

### 1.2.8. Control of worker exposure: Use as laboratory reagent (PROC15)

:

### Product (article) characteristics

Covers percentage substance in the product up to 100 %.

 Physical form of product
 : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure</td>

### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

### Other conditions affecting workers exposure

Version 2.15

Revision Date 2023-10-30

Temperature

: Assumes use at not more than 20°C above ambient temperature.

### **1.3. Exposure estimation and reference to its source**

1.3.1. Environmental release and exposure: Manufacture of the substance (ERC1) / Use of nonreactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Protection Target	Exposure estimate	RCR
Freshwater	0,795 µg/l (EUSES)	0,662
Sea water	0,302 µg/l (EUSES)	0,252
Freshwater sediment	0,306 mg/kg wet weight (EUSES)	0,658
Sea sediment	0,116 mg/kg wet weight (EUSES)	0,250
Soil	0,0117 mg/kg wet weight (EUSES)	0,301
Air	0,0649 mg/m <sup>3</sup>	

### Additional information on exposure estimation

Common practices vary across sites thus conservative process release estimates used.

1.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

1.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

1.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

1.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

SDS Number:10000068089

### AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

1.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

# 1.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

### 1.3.8. Worker exposure: Use as laboratory reagent (PROC15)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

### 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).

SAFETY DATA SHEET

Version 2.15

		2410 2020 10 00			
ES 2: Us	se as an intermediate; Industrial uses (SU3).				
2.1. Title	2.1. Title section				
Fxposur	e Scenario name : Use as an intermediate				
•	Exposure Scenario name       : Use as an intermediate         Structured Short Title       : Use as an intermediate; Industrial uses (SU3).				
Substance : dec-1-ene					
	<u>EC-No.:</u> 212-819-2				
Environ	ment				
CS 1	Use as an intermediate	ERC6a			
Worker					
CS 2	General measures applicable to all activities, General measures (skin irritants)	PROC1			
CS 3	General measures applicable to all activities, General measures (skin irritants)	PROC2			
CS 4	General measures applicable to all activities, General measures (skin irritants)	PROC3			
CS 5	General measures applicable to all activities, General measures (skin irritants)	PROC4			
CS 6	General measures applicable to all activities, General measures (skin irritants)	PROC8a			
CS 7	General measures applicable to all activities, General measures (skin irritants)	PROC8b			
CS 8	General measures applicable to all activities, General measures (skin irritants)	PROC15			
2.2. Conditions of use affecting exposure 2.2.1. Control of environmental exposure: Use of intermediate (ERC6a) Product (article) characteristics					
Covers p	ercentage substance in the product up to 100 %.				
Amount used (or contained in articles), frequency and duration of use/exposure					
Maximur (MSafe)	n allowable site tonnage : 51.813 kg/day				
Release	type : Continuous release				
Emissior	i days : 300				
Technic	al and organisational conditions and measures				
Risk fron	n environmental exposure is driven by soil.				
SDS Num	nber:10000068089 28/88				

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

Conditions and measures related to sewage treatment plar	nt
Air - minimum efficiency of 80 % Water - minimum efficiency of 97,4 %	
Air - minimum efficiency of 80 %	

STP type	:	Municipal sewage treatment plant
STP sludge treatment	:	Prevent discharge of undissolved substance to or recover from wastewater. Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
STP effluent	:	2.000 m3/d

### Conditions and measures related to treatment of waste (including article waste)

Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.		
Other conditions affecting environmental exposure			

Receiving surface water flow	:	18.000 m3/d
Local freshwater dilution factor	:	10
Local marine water dilution factor	:	100

# 2.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

	SAFETY DATA SHEET			
AlphaPlus® 1-Decene				
Version 2.15	Revision Date 2023-10-30			
2.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)				
Product (article) characteristics				
Covers percentage substance in the product up to 100	)%.			
Physical form of product : Liquid, vapo and Pressur	ur pressure < 0.5 kPa at Standard Temperature e			
Amount used (or contained in articles), frequency and duration of use/exposure				
Duration : Covers daily	exposures up to 8 hours			
Technical and organisational conditions and meas	ures			
Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.				
Other conditions affecting workers exposure				
Temperature : Assumes us temperature	e at not more than 20°C above ambient			
2.2.4. Control of worker exposure: Manufacture or batch processes with occasional controlled exposition (PROC3)				
Product (article) characteristics				
Covers percentage substance in the product up to 100				
Physical form of product : Liquid, vapo	) %.			
and Pressur	ur pressure < 0.5 kPa at Standard Temperature			
	ur pressure < 0.5 kPa at Standard Temperature e			
and Pressur Amount used (or contained in articles), frequency	ur pressure < 0.5 kPa at Standard Temperature e			
and Pressur Amount used (or contained in articles), frequency	ur pressure < 0.5 kPa at Standard Temperature e and duration of use/exposure v exposures up to 8 hours			
Amount used (or contained in articles), frequency Duration : Covers daily	ur pressure < 0.5 kPa at Standard Temperature e and duration of use/exposure / exposures up to 8 hours sures ical assistance. al areas for indirect skin contact. Wear gloves /. Clean up contamination/spills as soon as they Provide basic employee training to prevent /			
Amount used (or contained in articles), frequency Duration : Covers daily Technical and organisational conditions and meas Do not ingest. If swallowed then seek immediate medi Avoid direct skin contact with product. Identify potentia (tested to EN374) if hand contact with substance likely occur. Wash off any skin contamination immediately. I minimise exposures and to report any skin problems t	ur pressure < 0.5 kPa at Standard Temperature e and duration of use/exposure / exposures up to 8 hours sures ical assistance. al areas for indirect skin contact. Wear gloves /. Clean up contamination/spills as soon as they Provide basic employee training to prevent /			
Amount used (or contained in articles), frequency         Duration       : Covers daily         Technical and organisational conditions and mease         Do not ingest. If swallowed then seek immediate media         Avoid direct skin contact with product. Identify potentia         (tested to EN374) if hand contact with substance likely         occur. Wash off any skin contamination immediately. I         minimise exposures and to report any skin problems to         No other specific measures identified.         Other conditions affecting workers exposure	ur pressure < 0.5 kPa at Standard Temperature e and duration of use/exposure / exposures up to 8 hours sures ical assistance. al areas for indirect skin contact. Wear gloves /. Clean up contamination/spills as soon as they Provide basic employee training to prevent /			

Γ

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

temperature.

# 2.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

### **Product (article) characteristics**

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 2.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) character	istics		
Covers percentage substance in the product up to 100 %.			
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure		
Amount used (or contained	d in articles), frequency and duration of use/exposure		
Duration	: Covers daily exposures up to 8 hours		
Technical and organisational conditions and measures			
Avoid direct skin contact with	hen seek immediate medical assistance. n product. Identify potential areas for indirect skin contact. Wear gloves ntact with substance likely. Clean up contamination/spills as soon as they		

(tested to EN3/4) If hand contact with substance likely. Clean up contamination/spills as soon as the occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

No other specific measures identified.

### Other conditions affecting workers exposure

SDS Number:100000068089

### AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

Temperature

Assumes use at not more than 20°C above ambient temperature.

# 2.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

### **Product (article) characteristics**

Covers percentage substance in the product up to 100 %.

Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
--------------------------	---

Amount used (or contained in articles), frequency and duration of use/exposure

:

Duration

: Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

### Other conditions affecting workers exposure

Temperature

Assumes use at not more than 20°C above ambient temperature.

### 2.2.8. Control of worker exposure: Use as laboratory reagent (PROC15)

:

### Product (article) characteristics

Covers percentage substance in the product up to 100 %.

 Physical form of product
 : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure</td>

### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

### Other conditions affecting workers exposure

Version 2.15

Revision Date 2023-10-30

Temperature

: Assumes use at not more than 20°C above ambient temperature.

### 2.3. Exposure estimation and reference to its source

### 2.3.1. Environmental release and exposure: Use of intermediate (ERC6a)

Protection Target	Exposure estimate	RCR
Freshwater	0,433 µg/l (EUSES)	0,361
Sea water	0,0426 μg/l (EUSES)	0,036
Freshwater sediment	0,167 mg/kg wet weight (EUSES)	0,359
Sea sediment	0,0164 mg/kg wet weight (EUSES)	0,035
Soil	0,220 mg/kg wet weight (EUSES)	0,579
Air	0,0017 mg/m <sup>3</sup>	

### Additional information on exposure estimation

Common practices vary across sites thus conservative process release estimates used.

2.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

2.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

2.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

### 2.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

SDS Number:100000068089

### AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

2.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

# 2.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

### 2.3.8. Worker exposure: Use as laboratory reagent (PROC15)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

### 2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).

SAFETY	ράτα	SHEET
		SHELL

Version 2.15

ES 3: Formulation; Industrial uses (SU3).				
3.1. Title section				
Exposure Scenario name : Formulation				
Structured Short Title : Formulation; Industrial uses (SU3).				
Substance         : dec-1-ene <u>EC-No.:</u> 212-819-2				
Environment				
CS 1 Formulation	ERC2			
Worker				
CS 2 General measures applicable to all activities, General measures (skin irritants)	PROC1			
CS 3 General measures applicable to all activities, General measures (skin irritants)	PROC2			
CS 4 General measures applicable to all activities, General measures (skin irritants)	PROC3			
CS 5 General measures applicable to all activities, General measures (skin irritants)	PROC4			
CS 6 General measures applicable to all activities, General measures (skin irritants)	PROC8a			
CS 7 General measures applicable to all activities, General measures (skin irritants)	PROC8b			
CS 8 General measures applicable to all activities, General measures (skin irritants)	PROC9			
CS 9 General measures applicable to all activities, General measures (skin irritants)	PROC14			
CS 10 General measures applicable to all activities, General measures (skin irritants)	PROC15			
3.2. Conditions of use affecting exposure 3.2.1. Control of environmental exposure: Formulation into mixture (ERC2)				
Product (article) characteristics				
Covers percentage substance in the product up to 100 %.				
Amount used (or contained in articles), frequency and duration of use/exposure				
Maximum allowable site tonnage : 91.503 kg/day (MSafe)				
Release type : Continuous release				
SDS Number:10000068089 35/88				

Version 2.15

SAFETY DATA SHEET

Revision Date 2023-10-30

Emission days

: 300

### Technical and organisational conditions and measures

Risk from environmental exposure is driven by soil. Air - minimum efficiency of 0 % Water - minimum efficiency of 97,4 %

### Conditions and measures related to sewage treatment plant

STP type	:	Municipal sewage treatment plant
STP sludge treatment	:	Prevent discharge of undissolved substance to or recover from wastewater. Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
STP effluent	:	2.000 m3/d

### Conditions and measures related to treatment of waste (including article waste)

Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
-----------------	---

### Other conditions affecting environmental exposure

	18.000 m3/d
•	10.000 110/0
:	10
:	100
	:

# 3.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics Covers percentage substance in the product up to 100 %.		
Amount used (or contained in ar	ticles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours	
Technical and organisational co	nditions and measures	
(tested to EN374) if hand contact w occur. Wash off any skin contamination	uct. Identify potential areas for indirect skin contact. Wear gloves vith substance likely. Clean up contamination/spills as soon as they ation immediately. Provide basic employee training to prevent / any skin problems that may develop.	
Other conditions affecting workers exposure		
Temperature	: Assumes use at not more than 20°C above ambient	
SDS Number:100000068089	36/88	

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

temperature.

# 3.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

#### **Product (article) characteristics**

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

Amount used (or contained in articles), frequency and duration of use/exposure

:

Duration

: Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

Assumes use at not more than 20°C above ambient temperature.

3.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

SDS Number:100000068089

# AlphaPlus® 1-Decene

Version 2.15

Other conditions affecting workers exposure			
Temperature	: Assumes use at not more than 20°C above ambient temperature.		
3.2.5. Control of worker exposure (PROC4)	e: Chemical production where opportunity for exposure arises		
Product (article) characteristics			
Covers percentage substance in th	e product up to 100 %.		
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure		
Amount used (or contained in an	ticles), frequency and duration of use/exposure		
Duration	: Covers daily exposures up to 8 hours		
Technical and organisational cor	nditions and measures		
(tested to EN374) if hand contact w occur. Wash off any skin contamination	uct. Identify potential areas for indirect skin contact. Wear gloves with substance likely. Clean up contamination/spills as soon as they ation immediately. Provide basic employee training to prevent / any skin problems that may develop.		
Other conditions affecting worke	ers exposure		
Temperature	: Assumes use at not more than 20°C above ambient temperature.		
3.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)			
Product (article) characteristics			
Covers percentage substance in th	e product up to 100 %.		
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure		
Amount used (or contained in articles), frequency and duration of use/exposure			
Duration	: Covers daily exposures up to 8 hours		
Technical and organisational conditions and measures			
(tested to EN374) if hand contact w occur. Wash off any skin contamination	act. Identify potential areas for indirect skin contact. Wear gloves with substance likely. Clean up contamination/spills as soon as they ation immediately. Provide basic employee training to prevent / any skin problems that may develop.		
SDS Number:100000068089	38/88		

# AlphaPlus® 1-Decene

Version 2.15

Other conditions affecting workers exposure		
Temperature	: Assumes use at not more than 20°C above ambient temperature.	
3.2.7. Control of worker exposure: dedicated facilities (PROC8b)	: Transfer of substance or mixture (charging/discharging) at	
Product (article) characteristics		
Covers percentage substance in the	e product up to 100 %.	
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure	
Amount used (or contained in art	icles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours	
Technical and organisational con	ditions and measures	
(tested to EN374) if hand contact wi	ct. Identify potential areas for indirect skin contact. Wear gloves ith substance likely. Clean up contamination/spills as soon as they tion immediately. Provide basic employee training to prevent / ny skin problems that may develop.	
Other conditions affecting worke	rs exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.	
3.2.8. Control of worker exposure: (dedicated filling line, including w	: Transfer of substance or mixture into small containers eighing) (PROC9)	
Product (article) characteristics		
Covers percentage substance in the	e product up to 100 %.	
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure	
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures		
(tested to EN374) if hand contact wi	ct. Identify potential areas for indirect skin contact. Wear gloves ith substance likely. Clean up contamination/spills as soon as they tion immediately. Provide basic employee training to prevent / ny skin problems that may develop.	
SDS Number:100000068089	39/88	

# AlphaPlus® 1-Decene

Version 2.15

Other conditions affecting workers exposure		
Temperature	: Assumes use at not more than 20°C above ambient temperature.	
3.2.9. Control of worker exposure: (PROC14)	Tabletting, compression, extrusion, pelettisation, granulation	
Product (article) characteristics		
Covers percentage substance in the	product up to 100 %.	
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure	
Amount used (or contained in artic	cles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours	
Technical and organisational cond	litions and measures	
(tested to EN374) if hand contact with	t. Identify potential areas for indirect skin contact. Wear gloves h substance likely. Clean up contamination/spills as soon as they on immediately. Provide basic employee training to prevent / y skin problems that may develop.	
Other conditions affecting workers	s exposure	
Temperature	: Assumes use at not more than 20°C above ambient temperature.	
3.2.10. Control of worker exposure:	: Use as laboratory reagent (PROC15)	
Product (article) characteristics		
Covers percentage substance in the	product up to 100 %.	
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure	
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures		
(tested to EN374) if hand contact with	t. Identify potential areas for indirect skin contact. Wear gloves h substance likely. Clean up contamination/spills as soon as they on immediately. Provide basic employee training to prevent / y skin problems that may develop.	
SDS Number:100000068089	40/88	

Version 2.15

Revision Date 2023-10-30

SAFETY DATA SHEET

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 3.3. Exposure estimation and reference to its source

#### 3.3.1. Environmental release and exposure: Formulation into mixture (ERC2)

Protection Target	Exposure estimate	RCR
Freshwater	0,0005 mg/I (EUSES)	0,414
Sea water	0,049 μg/l (EUSES)	0,041
Freshwater sediment	0,191 mg/kg wet weight (EUSES)	0,412
Sea sediment	0,019 mg/kg wet weight (EUSES)	0,041
Soil	0,290 mg/kg wet weight (EUSES)	0,765
Air	0,195 mg/m³	

#### Additional information on exposure estimation

Common practices vary across sites thus conservative process release estimates used.

3.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

3.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

3.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 3.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

SDS Number:100000068089

Version 2.15

Revision Date 2023-10-30

# 3.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

# 3.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

# 3.3.8. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 3.3.9. Worker exposure: Tabletting, compression, extrusion, pelettisation, granulation (PROC14)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 3.3.10. Worker exposure: Use as laboratory reagent (PROC15)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).

Alpha	-	FETY DATA SHEET
Version 2	Plus® 1-Decene	sion Date 2023-10-30
	e in coatings – industrial; Industrial uses (SU3).	
4.1. Title	section	
Exposur	e Scenario name : Use in coatings – industrial	
Structur	ed Short Title : Use in coatings – industrial; Industrial uses	s (SU3).
Substan	ce : dec-1-ene <u>EC-No.:</u> 212-819-2	
Environ	nent	
CS 1	Use in coatings – industrial	ERC4
Worker		
CS 2	General measures applicable to all activities, General measures (ski irritants)	in PROC1
CS 3	General measures applicable to all activities, General measures (ski irritants)	in PROC2
CS 4	General measures applicable to all activities, General measures (ski irritants)	in PROC3
CS 5	General measures applicable to all activities, General measures (ski irritants)	in PROC4
CS 6	General measures applicable to all activities, General measures (ski irritants)	in PROC5
CS 7	General measures applicable to all activities, General measures (ski irritants)	in PROC7
CS 8	General measures applicable to all activities, General measures (ski irritants)	in PROC8a
CS 9	General measures applicable to all activities, General measures (ski irritants)	in PROC8b
CS 10	General measures applicable to all activities, General measures (ski irritants)	in PROC9
CS 11	General measures applicable to all activities, General measures (ski irritants)	in PROC10
CS 12	General measures applicable to all activities, General measures (ski irritants)	in PROC13
CS 13	General measures applicable to all activities, General measures (ski irritants)	in PROC14
CS 14	General measures applicable to all activities, General measures (ski irritants)	in PROC15

4.2. Conditions of use affecting exposure

4.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

SDS Number:100000068089

Version 2.15

Product (article) characteristics			
Covers percentage substance in th	e product up to 100 %.		
Amount used (or contained in ar	ticles), frequency and duration of use/exposure		
Maximum allowable site tonnage (MSafe)	: 19.491 kg/day		
Release type	: Continuous release		
Emission days	: 300		
Technical and organisational co	nditions and measures		
Risk from environmental exposure Air - minimum efficiency of 90 % Water - minimum efficiency of 97,4			
Conditions and measures related	to sewage treatment plant		
STP type	: Municipal sewage treatment plant		
STP sludge treatment	<ul> <li>Prevent discharge of undissolved substance to or recover from wastewater.</li> <li>Do not apply industrial sludge to natural soils.</li> <li>Sewage sludge should be incinerated, contained or reclaimed.</li> </ul>		
STP effluent	: 2.000 m3/d		
Conditions and measures related to treatment of waste (including article waste)			
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.		
Other conditions affecting enviro	onmental exposure		
Receiving surface water flow	: 18.000 m3/d		
Local freshwater dilution factor	: 10		
Local marine water dilution factor	: 100		
	: Chemical production or refinery in closed process without ses with equivalent containment conditions (PROC1)		
Product (article) characteristics			
Covers percentage substance in th	e product up to 100 %.		
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure		
Amount used (or contained in articles), frequency and duration of use/exposure			
Duration	: Covers daily exposures up to 8 hours		
Technical and organisational co	nditions and measures		
SDS Number:100000068089	44/88		

# AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

Assumes use at not more than 20°C above ambient temperature.

4.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

:

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

 Temperature
 : Assumes use at not more than 20°C above ambient temperature.

# 4.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics		
Covers percentage substance in the product up to 100 %.		
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure	
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	: Covers daily exposures up to 8 hours	
SDS Number:100000068089	45/88	

SAFETY DATA SHEET

#### Version 2.15

Revision Date 2023-10-30

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 4.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 4.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

 Product (article) characteristics

 Covers percentage substance in the product up to 100 %.

 Physical form of product
 : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure</td>

 Amount used (or contained in articles), frequency and duration of use/exposure

 Duration
 : Covers daily exposures up to 8 hours

 SDS Number:10000068089
 46/88

SAFETY DATA SHEET

#### Version 2.15

Revision Date 2023-10-30

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 4.2.7. Control of worker exposure: Industrial spraying (PROC7)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 4.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

# Physical form of product : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

SDS Number:100000068089

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 4.2.9. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 4.2.10. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

#### **Product (article) characteristics**

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

SDS Number:100000068089

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 4.2.11. Control of worker exposure: Roller application or brushing (PROC10)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 4.2.12. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics			
Covers percentage substance in the proc	duct up to 100 %.		
Physical form of product : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure			
Amount used (or contained in articles), frequency and duration of use/exposure			
Duration :	Covers daily exposures up to 8 hours		
SDS Number:100000068089	49/88		

Version 2.15

Revision Date 2023-10-30

SAFETY DATA SHEET

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 4.2.13. Control of worker exposure: Tabletting, compression, extrusion, pelettisation, granulation (PROC14)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 4.2.14. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics		
Covers percentage substance in the product up to 100 %.		
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure	
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	: Covers daily exposures up to 8 hours	
SDS Number:100000068089	50/88	

Version 2.15

Revision Date 2023-10-30

SAFETY DATA SHEET

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 4.3. Exposure estimation and reference to its source

4.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Protection Target	Exposure estimate	RCR
Freshwater	0,334 µg/l (EUSES)	0,278
Sea water	0,0326 μg/l (EUSES)	0,027
Freshwater sediment	0,129 mg/kg wet weight (EUSES)	0,276
Sea sediment	0,0126 mg/kg wet weight (EUSES)	0,027
Soil	0,216 mg/kg wet weight (EUSES)	0,570
Air	0,303 mg/m <sup>3</sup>	

#### Additional information on exposure estimation

Common practices vary across sites thus conservative process release estimates used.

4.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

4.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

SDS Number:10000068089

## AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

4.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 4.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 4.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 4.3.7. Worker exposure: Industrial spraying (PROC7)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

4.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

4.3.9. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

4.3.10. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 4.3.11. Worker exposure: Roller application or brushing (PROC10)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

SDS Number:10000068089

Version 2.15

Revision Date 2023-10-30

#### 4.3.12. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 4.3.13. Worker exposure: Tabletting, compression, extrusion, pelettisation, granulation (PROC14)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 4.3.14. Worker exposure: Use as laboratory reagent (PROC15)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).

SDS Number:100000068089

Alpha		ETY DATA SHEET
Version 2	Plus® 1-Decene 2.15 Revisio	n Date 2023-10-30
	se in coatings – professional; Professional uses (SU22).	
5.1. HITE	e section	
-	re Scenario name : Use in coatings – professional	
	ed Short Title : Use in coatings – professional; Professional	uses (SU22).
Substan	ce : dec-1-ene <u>EC-No.: 212-819-2</u>	
Environ	ment	
CS 1	Use in coatings – professional	ERC8a, ERC8d
Worker		
CS 2	General measures applicable to all activities, General measures (skin irritants)	PROC1
CS 3	General measures applicable to all activities, General measures (skin irritants)	PROC2
CS 4	General measures applicable to all activities, General measures (skin irritants)	PROC3
CS 5	General measures applicable to all activities, General measures (skin irritants)	PROC4
CS 6	General measures applicable to all activities, General measures (skin irritants)	PROC5
CS 7	General measures applicable to all activities, General measures (skin irritants)	PROC8a
CS 8	General measures applicable to all activities, General measures (skin irritants)	PROC8b
CS 9	General measures applicable to all activities, General measures (skin irritants)	PROC10
CS 10	General measures applicable to all activities, General measures (skin irritants)	PROC11
CS 11	General measures applicable to all activities, General measures (skin irritants)	PROC13
CS 12	General measures applicable to all activities, General measures (skin irritants)	PROC15
CS 13	General measures applicable to all activities, General measures (skin irritants)	PROC19

## 5.2. Conditions of use affecting exposure

5.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a) / Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

SDS Number:100000068089

Version 2.15

Product (article) characteristics		
Covers percentage substance in th	e product up to 100 %.	
Amount used (or contained in ar	ticles), frequency and duration of use/exposure	
Maximum allowable site tonnage (MSafe)	: 52 kg/day	
Release type	: Wide dispersive use	
Emission days	: 300	
Technical and organisational co	nditions and measures	
Risk from environmental exposure Air - minimum efficiency of 0 % Water - minimum efficiency of 97,4		
Conditions and measures related	d to sewage treatment plant	
STP type	: Municipal sewage treatment plant	
STP sludge treatment	<ul> <li>Prevent discharge of undissolved substance to or recover from wastewater.</li> <li>Do not apply industrial sludge to natural soils.</li> <li>Sewage sludge should be incinerated, contained or reclaimed.</li> </ul>	
STP effluent	: 2.000 m3/d	
Conditions and measures related	d to treatment of waste (including article waste)	
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.	
Other conditions affecting enviro	onmental exposure	
Receiving surface water flow	: 18.000 m3/d	
Local freshwater dilution factor	: 10	
Local marine water dilution factor	: 100	
	e: Chemical production or refinery in closed process without ses with equivalent containment conditions (PROC1)	
Covers percentage substance in th	e product up to 100 %.	
Physical form of product	<ul> <li>Liquid, vapour pressure &lt; 0.5 kPa at Standard Temperature and Pressure</li> </ul>	
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures		
SDS Number:100000068089	55/88	

# AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

Assumes use at not more than 20°C above ambient temperature.

5.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

:

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature : Assumes use at not more than 20°C above ambient temperature.

# 5.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics		
Covers percentage substance in t	the product up to 100 %.	
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure	
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	: Covers daily exposures up to 8 hours	
SDS Number:100000068089	56/88	

Version 2.15

Revision Date 2023-10-30

SAFETY DATA SHEET

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

Assumes use at not more than 20°C above ambient : temperature.

#### 5.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

Amount used (or contained in articles), frequency and duration of use/exposure

Duration

Covers daily exposures up to 8 hours 2

Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 5.2.6. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics Covers percentage substance in the product up to 100 %. : Liquid, vapour pressure < 0.5 kPa at Standard Temperature Physical form of product and Pressure Amount used (or contained in articles), frequency and duration of use/exposure Duration : Covers daily exposures up to 8 hours SDS Number:100000068089 57/88

SAFETY DATA SHEET

#### Version 2.15

Revision Date 2023-10-30

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 5.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 5.2.8. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

: Covers daily exposures up to 8 hours

SDS Number:100000068089

Version 2.15

Revision Date 2023-10-30

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 5.2.9. Control of worker exposure: Roller application or brushing (PROC10)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 5.2.10. Control of worker exposure: Non-industrial spraying (PROC11)

Product (article) characteristics			
Covers percentage substance in the proc	duct up to 100 %.		
Physical form of product :	Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure		
Amount used (or contained in articles), frequency and duration of use/exposure			
Duration :	Covers daily exposures up to 8 hours		
SDS Number:100000068089	59/88		

SAFETY DATA SHEET

#### Version 2.15

Revision Date 2023-10-30

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 5.2.11. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 5.2.12. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics			
roduct up to 100 %.			
: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure			
Amount used (or contained in articles), frequency and duration of use/exposure			
: Covers daily exposures up to 8 hours			
60/88			

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 5.2.13. Control of worker exposure: Manual activities involving hand contact (PROC19)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 5.3. Exposure estimation and reference to its source

5.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a) / Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

Protection Target	Exposure estimate	RCR	
Freshwater	0,334 μg/l (EUSES)	0,278	
Sea water	0,0326 μg/l (EUSES)	0,027	
Freshwater sediment	0,129 mg/kg wet weight (EUSES) 0,276		
SDS Number:100000068089	61/88	1	

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

Sea sediment	0,0126 mg/kg wet weight (EUSES)	0,027
Soil	0,163 mg/kg wet weight (EUSES)	0,431
Air	0,0061 mg/m³	

#### Additional information on exposure estimation

Common practices vary across sites thus conservative process release estimates used.

5.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

5.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

5.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

5.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

5.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

5.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

SDS Number:100000068089

## AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

5.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 5.3.9. Worker exposure: Roller application or brushing (PROC10)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 5.3.10. Worker exposure: Non-industrial spraying (PROC11)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 5.3.11. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 5.3.12. Worker exposure: Use as laboratory reagent (PROC15)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 5.3.13. Worker exposure: Manual activities involving hand contact (PROC19)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).

۵Inha	SAFE Plus® 1-Decene	TY DATA SHEET		
Version 2		Date 2023-10-30		
ES 6: Us	e in Coatings - Consumer; Consumer uses (SU21).			
	esection			
b.r. ritie	section			
Exposur	e Scenario name : Use in Coatings - Consumer			
	ed Short Title : Use in Coatings - Consumer; Consumer uses	(SU21).		
Substan	ce : dec-1-ene <u>EC-No.:</u> 212-819-2			
Environr	nent			
CS 1	Use in Coatings - Consumer	ERC8a, ERC8d		
Consum	er			
CS 2	General measures applicable to all activities, General measures (skin irritants)	PC1		
CS 3	General measures applicable to all activities, General measures (skin irritants)	PC4		
CS 4	General measures applicable to all activities, General measures (skin PC8 irritants)			
CS 5	General measures applicable to all activities, General measures (skin PC9a irritants)			
CS 6	General measures applicable to all activities, General measures (skin PC9b irritants)			
CS 7	General measures applicable to all activities, General measures (skin irritants)	PC9c		
CS 8	General measures applicable to all activities, General measures (skin irritants)	PC15		
CS 9	General measures applicable to all activities, General measures (skin irritants)	PC18		
CS 10	General measures applicable to all activities, General measures (skin irritants)	PC23		
CS 11	General measures applicable to all activities, General measures (skin irritants)	PC24		
CS 12	General measures applicable to all activities, General measures (skin irritants)	PC31		
CS 13	General measures applicable to all activities, General measures (skin irritants)	PC34		

## 6.2. Conditions of use affecting exposure

6.2.1. Control of environmental exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a) / Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

SDS Number:100000068089

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

#### Product (article) characteristics

Covers percentage substance in the product up to 100 %.

#### Amount used (or contained in articles), frequency and duration of use/exposure

Maximum allowable site tonnage : 52 kg/day (MSafe)

Release type Emission days

: 365

#### Conditions and measures related to treatment of waste (including article waste)

:

Waste treatment

External treatment and disposal of waste should comply with : applicable local and/or national regulations.

Wide dispersive use

#### Other conditions affecting environmental exposure

Receiving surface water flow	:	18.000 m3/d
Local freshwater dilution factor	:	10
Local marine water dilution factor	:	100

#### 6.2.2. Control of consumer exposure: Adhesives, sealants (PC1)

Product (article) characteristic	cs		
Covers percentage substance ir	n the product up to 100 %.		
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure		
Amount used (or contained in articles), frequency and duration of use/exposure			
Duration	: Covers daily exposures up to 8 hours		
Conditions and measures related to personal protection, hygiene and health evaluation			
Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.			
Other conditions affecting consumers exposure			

Temperature

Assumes use at not more than 20°C above ambient : temperature.

6.2.3. Control of consumer exposure: Anti-Freeze and de-icing products (PC4)		
Product (article) characteristics		
SDS Number:10000068089	65/88	

AlphaPlus®	1-Decene
------------	----------

Version 2.15

Revision Date 2023-10-30

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

:

Duration

Covers daily exposures up to 8 hours

#### Conditions and measures related to personal protection, hygiene and health evaluation

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting consumers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 6.2.4. Control of consumer exposure: Biocidal products (PC8)

Product (article) characteristics Covers percentage substance in the product up to 100 %. Physical form of product : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure Amount used (or contained in articles), frequency and duration of use/exposure Duration : Covers daily exposures up to 8 hours Conditions and measures related to personal protection, hygiene and health evaluation Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified. Other conditions affecting consumers exposure Temperature : Assumes use at not more than 20°C above ambient temperature.

#### 6.2.5. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

# Product (article) characteristics Covers percentage substance in the product up to 100 %. SDS Number:100000068089

AlphaPlus® 1-Decene		SAFETY DATA SHEET
Version 2.15		Revision Date 2023-10-30
Physical form of product	:	Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amount used (or contained in artic	les	s), frequency and duration of use/exposure
Duration	:	Covers daily exposures up to 8 hours
Conditions and measures related t	o p	ersonal protection, hygiene and health evaluation
(tested to EN374) if hand contact with	t. Id n su on i y sk	entify potential areas for indirect skin contact. Wear gloves ubstance likely. Clean up contamination/spills as soon as they immediately. Provide basic employee training to prevent /
Other conditions affecting consum	ners	s exposure
Temperature	:	Assumes use at not more than 20°C above ambient temperature.
6.2.6. Control of consumer exposur	re:	Fillers, putties, plasters, modelling clay (PC9b)
Product (article) characteristics		
Covers percentage substance in the	pro	duct up to 100 %.
Physical form of product	:	Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amount used (or contained in artic	les	s), frequency and duration of use/exposure
Duration	:	Covers daily exposures up to 8 hours
Conditions and measures related t	o p	ersonal protection, hygiene and health evaluation
Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.		
Other conditions affecting consumers exposure		
Temperature	:	Assumes use at not more than 20°C above ambient temperature.
6.2.7. Control of consumer exposure: Finger paints (PC9c)		
Product (article) characteristics		
Covers percentage substance in the	pro	duct up to 100 %.
Physical form of product	:	Liquid, vapour pressure < 0.5 kPa at Standard Temperature
SDS Number:100000068089		67/88

Version 2.15

SAFETY DATA SHEET

Revision Date 2023-10-30

#### and Pressure

Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Conditions and measures related to personal protection, hygiene and health evaluation

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting consumers exposure

Temperature

Assumes use at not more than 20°C above ambient temperature.

#### 6.2.8. Control of consumer exposure: Non-metal surface treatment products (PC15)

:

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Conditions and measures related to personal protection, hygiene and health evaluation

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.

No other specific measures identified.

Other conditions affecting consumers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 6.2.9. Control of consumer exposure: Ink and toners (PC18)

Product (article) characteristics					
Covers percentage substance in the product up to 100 %.					
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure				
SDS Number:100000068089	68/88				

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Conditions and measures related to personal protection, hygiene and health evaluation

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting consumers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 6.2.10. Control of consumer exposure: Leather treatment products (PC23)

#### **Product (article) characteristics**

Covers percentage substance in the product up to 100 %.

 Physical form of product
 : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure</td>

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Conditions and measures related to personal protection, hygiene and health evaluation

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting consumers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 6.2.11. Control of consumer exposure: Lubricants, greases, release products (PC24)

Product (article) characteristics						
Covers percentage substance in the product up to 100 %.						
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure					
SDS Number:100000068089	69/88					

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Conditions and measures related to personal protection, hygiene and health evaluation

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting consumers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 6.2.12. Control of consumer exposure: Polishes and wax blends (PC31)

#### **Product (article) characteristics**

Covers percentage substance in the product up to 100 %.

 Physical form of product
 : Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure</td>

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Conditions and measures related to personal protection, hygiene and health evaluation

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting consumers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 6.2.13. Control of consumer exposure: Textile dyes and impregnating products (PC34)

Product (article) characteristics						
Covers percentage substance in the product up to 100 %.						
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure					
SDS Number:100000068089	70/88					

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Conditions and measures related to personal protection, hygiene and health evaluation

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting consumers exposure

Temperature	:	Assumes use at not more than 20°C above ambient
		temperature.

#### 6.3. Exposure estimation and reference to its source

6.3.1. Environmental release and exposure: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a) / Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

Protection Target	Exposure estimate	RCR
Freshwater	0,283 µg/l (EUSES)	0,236
Sea water	0,0276 μg/l (EUSES)	0,023
Freshwater sediment	0,109 mg/kg wet weight (EUSES)	0,235
Sea sediment	0,0106 mg/kg wet weight (EUSES)	0,023
Soil	0,135 mg/kg wet weight (EUSES)	0,355
Air	0,005 mg/m <sup>3</sup>	

#### Additional information on exposure estimation

Common practices vary across sites thus conservative process release estimates used.

#### 6.3.2. Consumer exposure: Adhesives, sealants (PC1)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 6.3.3. Consumer exposure: Anti-Freeze and de-icing products (PC4)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

SDS Number:100000068089

# AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

#### 6.3.4. Consumer exposure: Biocidal products (PC8)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 6.3.5. Consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

6.3.6. Consumer exposure: Fillers, putties, plasters, modelling clay (PC9b)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

6.3.7. Consumer exposure: Finger paints (PC9c)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

6.3.8. Consumer exposure: Non-metal surface treatment products (PC15)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

6.3.9. Consumer exposure: Ink and toners (PC18)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

6.3.10. Consumer exposure: Leather treatment products (PC23)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

6.3.11. Consumer exposure: Lubricants, greases, release products (PC24)

SDS Number:100000068089

Version 2.15

Revision Date 2023-10-30

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 6.3.12. Consumer exposure: Polishes and wax blends (PC31)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 6.3.13. Consumer exposure: Textile dyes and impregnating products (PC34)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).

Version 2.15

Revision Date 2023-10-30

SAFETY DATA SHEET

# ES 7: Use in Oil and Gas field drilling and production operations - Industrial; Industrial uses (SU3).

#### 7.1. Title section

Exposure Scenario name	: Use in Oil and Gas field drilling and production operations - Industrial
Structured Short Title	: Use in Oil and Gas field drilling and production operations - Industrial; Industrial uses (SU3).
Substance	: dec-1-ene <u>EC-No.:</u> 212-819-2

### Environment

Environ	ment	
CS 1	Use in Oil and Gas field drilling and production operations - Industrial	ERC4
Worker		
CS 2	General measures applicable to all activities, General measures (skin irritants)	PROC1
CS 3	General measures applicable to all activities, General measures (skin irritants)	PROC2
CS 4	General measures applicable to all activities, General measures (skin irritants)	PROC3
CS 5	General measures applicable to all activities, General measures (skin irritants)	PROC4
CS 6	General measures applicable to all activities, General measures (skin irritants)	PROC8a
CS 7	General measures applicable to all activities, General measures (skin irritants)	PROC8b

#### 7.2. Conditions of use affecting exposure

7.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Amount used (or contained in articles), frequency and duration of use/exposure

Release type

Remarks

: Continuous release : Not applicable

Technical and organisational conditions and measures

Discharge to aquatic environment is restricted (see section 4.2).

SDS Number:100000068089

SAFETY DATA SHEET AlphaPlus® 1-Decene Revision Date 2023-10-30 Version 2.15 Conditions and measures related to sewage treatment plant STP type : Municipal sewage treatment plant STP sludge treatment : Prevent environmental discharge consistent with regulatory requirements. Conditions and measures related to treatment of waste (including article waste) Waste treatment External treatment and disposal of waste should comply with : applicable local and/or national regulations. 7.2.2. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1) Product (article) characteristics Covers percentage substance in the product up to 100 %. Physical form of product Liquid, vapour pressure < 0.5 kPa at Standard Temperature : and Pressure Amount used (or contained in articles), frequency and duration of use/exposure Duration Covers daily exposures up to 8 hours : Technical and organisational conditions and measures Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified. Other conditions affecting workers exposure : Assumes use at not more than 20°C above ambient Temperature temperature. 7.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2) Product (article) characteristics Covers percentage substance in the product up to 100 %. Physical form of product Liquid, vapour pressure < 0.5 kPa at Standard Temperature : and Pressure Amount used (or contained in articles), frequency and duration of use/exposure Duration Covers daily exposures up to 8 hours • SDS Number:10000068089 75/88

SAFETY DATA SHEET

#### Version 2.15

Revision Date 2023-10-30

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance.

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 7.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

Assumes use at not more than 20°C above ambient temperature.

# 7.2.5. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

:

SDS Number:100000068089

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 7.2.6. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 7.2.7. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

#### Amount used (or contained in articles), frequency and duration of use/exposure

SDS Number:100000068089

SAFETY DATA SHEET

Version 2.15

Revision Date 2023-10-30

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

#### 7.3. Exposure estimation and reference to its source

7.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

#### Additional information on exposure estimation

There are no expected releases to the environment from this use, so no exposure assessment is made.

7.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

7.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

7.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

7.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

SDS Number:10000068089

## AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

7.3.6. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

# 7.3.7. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 7.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Discharge to aquatic environment is restricted by law and industry prohibits release.

SDS Number:100000068089

SAFETY	ΠΑΤΑ	SHEET
SAFEII	DATA	SHEET

Version 2.15

Revision Date 2023-10-30

ES 8: Us	e in polymer production – industrial; Industrial uses (SU3).	
8.1. Title	section	
Exposur	e Scenario name : Use in polymer production – industrial	
Structur	ed Short Title : Use in polymer production – industrial; Industr	ial uses (SU3).
Substan	<b>ce</b> : dec-1-ene <u>EC-No.:</u> 212-819-2	
Environ	nent	
CS 1	Use in polymer production – industrial	ERC4, ERC6c
Worker		
CS 2	General measures applicable to all activities, General measures (skin irritants)	PROC1
CS 3	General measures applicable to all activities, General measures (skin irritants)	PROC2
CS 4	General measures applicable to all activities, General measures (skin irritants)	PROC3
CS 5	General measures applicable to all activities, General measures (skin irritants)	PROC4
CS 6	General measures applicable to all activities, General measures (skin irritants)	PROC5
CS 7	General measures applicable to all activities, General measures (skin irritants)	PROC6
CS 8	General measures applicable to all activities, General measures (skin irritants)	PROC8a
CS 9	General measures applicable to all activities, General measures (skin irritants)	PROC8b
CS 10	General measures applicable to all activities, General measures (skin irritants)	PROC14
CS 11	General measures applicable to all activities, General measures (skin irritants)	PROC21

#### 8.2. Conditions of use affecting exposure

8.2.1. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4) / Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article) (ERC6c)

Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Amount used (or contained in articles), frequency and duration of use/exposure

SDS Number:10000068089

	SAFETY DATA SHEET
AlphaPlus® 1-Decene	
Version 2.15	Revision Date 2023-10-30
Maximum allowable site tonnage (MSafe)	: 51.203 kg/day
Release type	: Continuous release
Emission days	: 300
Technical and organisational con	ditions and measures
Risk from environmental exposure in Air - minimum efficiency of 80 % Water - minimum efficiency of 97,4	
Conditions and measures related	to sewage treatment plant
STP type	: Municipal sewage treatment plant
STP sludge treatment	<ul> <li>Prevent discharge of undissolved substance to or recover from wastewater.</li> <li>Do not apply industrial sludge to natural soils.</li> <li>Sewage sludge should be incinerated, contained or reclaimed.</li> </ul>
STP effluent	: 2.000 m3/d
Conditions and measures related	to treatment of waste (including article waste)
Waste treatment	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Other conditions affecting enviro	nmental exposure
Receiving surface water flow	: 18.000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
	Chemical production or refinery in closed process without es with equivalent containment conditions (PROC1)
Product (article) characteristics	
Covers percentage substance in the	e product up to 100 %.
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amount used (or contained in art	icles), frequency and duration of use/exposure
Duration	: Covers daily exposures up to 8 hours
Technical and organisational con	ditions and measures
(tested to EN374) if hand contact wi	ct. Identify potential areas for indirect skin contact. Wear gloves th substance likely. Clean up contamination/spills as soon as they tion immediately. Provide basic employee training to prevent / ny skin problems that may develop.
SDS Number:100000068089	81/88

### AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

Other co	onditions	affecting	workers	exposure
----------	-----------	-----------	---------	----------

Temperature

Assumes use at not more than 20°C above ambient temperature.

:

8.2.3. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

#### Product (article) characteristics

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.

#### Other conditions affecting workers exposure

Temperature

: Assumes use at not more than 20°C above ambient temperature.

# 8.2.4. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

**Product (article) characteristics** 

Covers percentage substance in the product up to 100 %.

Physical form of product

: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure

### Amount used (or contained in articles), frequency and duration of use/exposure

Duration

: Covers daily exposures up to 8 hours

#### Technical and organisational conditions and measures

Do not ingest. If swallowed then seek immediate medical assistance. Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent /

SDS Number:100000068089

Alpha Diug 1 Dagana	SAFETY DATA SHEET
AlphaPlus® 1-Decene Version 2.15	Revision Date 2023-10-30
Γ	
minimise exposures and to report an No other specific measures identified	
Other conditions affecting workers	s exposure
Temperature	: Assumes use at not more than 20°C above ambient temperature.
8.2.5. Control of worker exposure: (PROC4)	Chemical production where opportunity for exposure arises
Product (article) characteristics	
Covers percentage substance in the	product up to 100 %.
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amount used (or contained in artic	cles), frequency and duration of use/exposure
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conc	litions and measures
(tested to EN374) if hand contact wit	t. Identify potential areas for indirect skin contact. Wear gloves h substance likely. Clean up contamination/spills as soon as they ion immediately. Provide basic employee training to prevent / by skin problems that may develop.
Other conditions affecting workers	s exposure
Temperature	: Assumes use at not more than 20°C above ambient temperature.
8.2.6. Control of worker exposure:	Mixing or blending in batch processes (PROC5)
Product (article) characteristics	
Covers percentage substance in the	product up to 100 %.
Physical form of product	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amount used (or contained in artic	cles), frequency and duration of use/exposure
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conc	ditions and measures
(tested to EN374) if hand contact wit	k immediate medical assistance. tt. Identify potential areas for indirect skin contact. Wear gloves h substance likely. Clean up contamination/spills as soon as they ion immediately. Provide basic employee training to prevent /
SDS Number:100000068089	83/88

			SAFETY DATA SHEET
AlphaPlus® 1-Decene			
Version 2.15			Revision Date 2023-10-30
minimise exposures and to report a No other specific measures identifie		kin problems that may develop.	
Other conditions affecting worke	ers e	xposure	
Temperature	:	Assumes use at not more than 20°0 temperature.	C above ambient
8.2.7. Control of worker exposure	: Ca	lendering operations (PROC6)	
Product (article) characteristics			
Covers percentage substance in th	e pro	oduct up to 100 %.	
Physical form of product	:	Liquid, vapour pressure < 0.5 kPa a and Pressure	at Standard Temperature
Amount used (or contained in art	ticle	s), frequency and duration of use/e	xposure
Duration	:	Covers daily exposures up to 8 hou	irs
Technical and organisational cor	nditio	ons and measures	
(tested to EN374) if hand contact w	uct. Io vith s ation any sl	dentify potential areas for indirect skir ubstance likely. Clean up contaminati immediately. Provide basic employee	ion/spills as soon as they
Other conditions affecting worke	ers e	xposure	
Temperature	:	Assumes use at not more than 20°0 temperature.	C above ambient
8.2.8. Control of worker exposure dedicated-facilities (PROC8a)	: Tra	ansfer of substance or mixture (cha	arging/discharging) at non
Product (article) characteristics			
Covers percentage substance in the	e pro	oduct up to 100 %.	
Physical form of product	:	Liquid, vapour pressure < 0.5 kPa a and Pressure	at Standard Temperature
Amount used (or contained in art	ticle	s), frequency and duration of use/e	exposure
Duration	:	Covers daily exposures up to 8 hou	irs
Technical and organisational cor	nditio	ons and measures	
(tested to EN374) if hand contact w	uct. Io /ith s	nmediate medical assistance. dentify potential areas for indirect skir ubstance likely. Clean up contaminati immediately. Provide basic employee	ion/spills as soon as they
SDS Number:100000068089		84/88	

	SAFETY DATA SHEET
AlphaPlus® 1-Decene	
Version 2.15	Revision Date 2023-10-30
minimise exposures and to report any s No other specific measures identified.	kin problems that may develop.
Other conditions affecting workers e	xposure
Temperature :	Assumes use at not more than 20°C above ambient temperature.
8.2.9. Control of worker exposure: Tra dedicated facilities (PROC8b)	ansfer of substance or mixture (charging/discharging) at
Product (article) characteristics	
Covers percentage substance in the pro	oduct up to 100 %.
Physical form of product :	Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amount used (or contained in article	s), frequency and duration of use/exposure
Duration :	Covers daily exposures up to 8 hours
Technical and organisational condition	ons and measures
(tested to EN374) if hand contact with s	dentify potential areas for indirect skin contact. Wear gloves ubstance likely. Clean up contamination/spills as soon as they immediately. Provide basic employee training to prevent /
Other conditions affecting workers e	xposure
Temperature :	Assumes use at not more than 20°C above ambient temperature.
8.2.10. Control of worker exposure: Ta (PROC14)	abletting, compression, extrusion, pelettisation, granulation
Product (article) characteristics	
Covers percentage substance in the pro	oduct up to 100 %.
Physical form of product :	Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amount used (or contained in article	s), frequency and duration of use/exposure
Duration :	Covers daily exposures up to 8 hours
Technical and organisational condition	ons and measures
	nmediate medical assistance. dentify potential areas for indirect skin contact. Wear gloves ubstance likely. Clean up contamination/spills as soon as they
SDS Number:100000068089	85/88

# AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

No other specific measures in	tamination immediately. Provide basic er eport any skin problems that may develop dentified.	
Other conditions affecting	workers exposure	
Temperature	: Assumes use at not more th temperature.	an 20°C above ambient
3.2.11. Control of worker ex n/on materials and/or articl	posure: Low energy manipulation and es (PROC21)	handling of substances bound
Product (article) characteri	stics	
Covers percentage substanc	e in the product up to 100 %.	
Physical form of product	: Liquid, vapour pressure < 0 and Pressure	5 kPa at Standard Temperature
Amount used (or contained	I in articles), frequency and duration o	f use/exposure
Duration	: Covers daily exposures up t	o 8 hours
Technical and organisation	al conditions and measures	
minimise exposures and to re No other specific measures in		).
Other conditions affecting		
Other conditions affecting	: Assumes use at not more th temperature.	an 20°C above ambient
Temperature 3.3. Exposure estimation 3.3.1. Environmental release no inclusion into or onto ar		rocessing aid at industrial site
Temperature 3.3. Exposure estimation 3.3.1. Environmental release no inclusion into or onto ar ndustrial site (inclusion or	temperature. and reference to its source e and exposure: Use of non-reactive p rticle) (ERC4) / Use of monomer in pol	rocessing aid at industrial site
Temperature 3.3. Exposure estimation 3.3.1. Environmental release no inclusion into or onto ar ndustrial site (inclusion or Protection Target	temperature. and reference to its source e and exposure: Use of non-reactive p rticle) (ERC4) / Use of monomer in pol not into/onto article) (ERC6c)	rocessing aid at industrial site ymerisation processes at
Temperature 3.3. Exposure estimation 3.3.1. Environmental release no inclusion into or onto ar ndustrial site (inclusion or Protection Target Freshwater	and reference to its source e and exposure: Use of non-reactive p rticle) (ERC4) / Use of monomer in pol not into/onto article) (ERC6c) Exposure estimate	rocessing aid at industrial site ymerisation processes at RCR
Temperature 3.3. Exposure estimation 3.3.1. Environmental release no inclusion into or onto ar ndustrial site (inclusion or Protection Target Freshwater Sea water	temperature. and reference to its source e and exposure: Use of non-reactive p rticle) (ERC4) / Use of monomer in pol not into/onto article) (ERC6c) Exposure estimate 0,476 µg/l (EUSES)	rocessing aid at industrial site ymerisation processes at RCR 0,396
Temperature 3.3. Exposure estimation 3.3.1. Environmental release no inclusion into or onto ar ndustrial site (inclusion or Protection Target Freshwater Sea water Freshwater sediment	temperature. and reference to its source e and exposure: Use of non-reactive p rticle) (ERC4) / Use of monomer in pol not into/onto article) (ERC6c) Exposure estimate 0,476 μg/l (EUSES) 0,0468 μg/l (EUSES)	rocessing aid at industrial site ymerisation processes at RCR 0,396 0,039
Temperature 3.3. Exposure estimation 3.3.1. Environmental release no inclusion into or onto ar ndustrial site (inclusion or Protection Target Freshwater Sea water Freshwater sediment Sea sediment	temperature. and reference to its source e and exposure: Use of non-reactive p rticle) (ERC4) / Use of monomer in pol not into/onto article) (ERC6c) Exposure estimate 0,476 μg/l (EUSES) 0,0468 μg/l (EUSES) 0,183 mg/kg wet weight (EUSES)	rocessing aid at industrial site ymerisation processes at RCR 0,396 0,039 0,394
Temperature 3.3. Exposure estimation 3.3.1. Environmental release (no inclusion into or onto ar	temperature.         and reference to its source         e and exposure: Use of non-reactive p         tricle) (ERC4) / Use of monomer in pol         not into/onto article) (ERC6c)         Exposure estimate         0,476 µg/l (EUSES)         0,0468 µg/l (EUSES)         0,183 mg/kg wet weight (EUSES)         0,018 mg/kg wet weight (EUSES)	rocessing aid at industrial site ymerisation processes at 0,396 0,039 0,394 0,039

Version 2.15

SAFETY DATA SHEET

Revision Date 2023-10-30

#### Additional information on exposure estimation

Common practices vary across sites thus conservative process release estimates used.

8.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

8.3.3. Worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

8.3.4. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 8.3.5. Worker exposure: Chemical production where opportunity for exposure arises (PROC4)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 8.3.6. Worker exposure: Mixing or blending in batch processes (PROC5)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 8.3.7. Worker exposure: Calendering operations (PROC6)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

# 8.3.8. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

SDS Number:100000068089

### AlphaPlus® 1-Decene

Version 2.15

Revision Date 2023-10-30

8.3.9. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 8.3.10. Worker exposure: Tabletting, compression, extrusion, pelettisation, granulation (PROC14)

#### Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

8.3.11. Worker exposure: Low energy manipulation and handling of substances bound in/on materials and/or articles (PROC21)

Additional information on exposure estimation

A quantitative risk assessment is not required for human health.

#### 8.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).