

Version 5.0 Revision Date 2025-09-02

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1

Product information

Product Name : Scentinel® A Gas Odorant

Material : 1017907, 1017909, 1119674, 1119564, 1106807, 1098462, 1102596, 1086453, 1098407, 1086452, 1102264, 1072060,

102596, 1086453, 1096407, 1066452, 1102264, 1072060, 1098463, 1103512, 1070006, 1024777, 1024776, 1024775, 1024774, 1029441, 1029442, 1029443, 1029444, 1029445

EC-No.Registration number

	u	
Chemical name	CAS-No.	Legal Entity
	EC-No.	Registration number
	Index No.	
Ethyl Mercaptan	75-08-1	
	200-837-3	Chevron Phillips Chemicals International NV
	016-022-00-9	01-2119491286-30-0000

1.2

Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses : Manufacture of Ethanethiol used under Strictly Controlled

Supported Conditions

Use at Industrial Site - Intermediate

Injection as odorant in Liquified Petroleum Gas under

Strictly Controlled Conditions - Industrial

Injection as odorant in Liquified Petroleum Gas under

Strictly Controlled Conditions - Consumer

Uses advised against : This material should not be used for purposes other than the

identified uses in section 1 without expert advice.

1.3

Details of the supplier of the safety data sheet

Company : Chevron Phillips Chemical Company LP

9500 Lakeside Blvd. The Woodlands, TX 77381

Local : Chevron Phillips Chemicals International N.V.

Airport Plaza (Stockholm Building)

Leonardo Da Vincilaan 19

1831 Diegem Belgium

SDS Requests: (800) 852-5530

Responsible Party: Product Safety Group

Email:sds@cpchem.com

SDS Number:100000068741 1/21

Version 5.0 Revision Date 2025-09-02

1.4

Emergency telephone:

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week) Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: POISON CENTER MILÂN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico "Agostino Gemelli", Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico "Umberto I" Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera "Antonio Cardarelli" Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera "Papa Giovanni XXIII" Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24

hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Version 5.0 Revision Date 2025-09-02

Organization that prepared

the SDS

: Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

ODOR-FADE WARNING

A GAS LEAK CAN CAUSE A FIRE OR EXPLOSION RESULTING IN SERIOUS INJURY OR DEATH.

Be aware that the stenching chemical added to gas to make it detectable may not warn of a gas leak or the presence of propane or natural gas to all persons in every instance.

Instances where the odorant in an odorized gas may be undetectable include:

- Odor intensity may fade or be eliminated for a variety of chemical and physical causes, including the oxidation of rusting pipes, adsorption into or sticking onto the interior of pipes or appliances, or absorption into liquids.
- Contact with soil in underground leaks may de-odorize or remove odorant from the gas.
- Some people have a diminished ability, or inability to smell the stench. Factors that negatively affect a person's sense of smell include age, gender, medical conditions, and alcohol/tobacco usage.
- The stench of odorized gas may not awaken sleeping persons.
- Other odors may mask or hide the stench.
- Exposure to the odor for even a short period of time, may cause nasal fatigue, where a person can no longer smell the stench.

Gas detectors listed by the Underwriters Laboratories (UL) can be used as an extra measure of safety for detecting gas leaks, especially under conditions where the odorant alone may not provide an adequate warning. Gas detectors emit a loud, shrill sound when gas is present and do not depend on sense of smell. Because the odor intensity can fade or people may have problems with their sense of smell, we recommend installing, per manufacturer's instructions, one or more combustible gas detectors, in suitable locations to ensure adequate coverage to detect gas leaks.

Educate yourself, your employees, and your customers with the content of this warning and other important facts associated with the so-called "odor-fade phenomenon."

SECTION 2: Hazards identification

2.1

Classification of the substance or mixture REGULATION (EC) No 1272/2008 REGULATION (EC) No 1272/2008 REGULATION (EC) No 1272/2008

Flammable liquids, Category 1 H224:

Extremely flammable liquid and vapor.

Acute toxicity, Category 4 H302:

Harmful if swallowed.

Acute toxicity, Category 3 H331:

Toxic if inhaled.

Serious eye damage, Category 1 H318:

Causes serious eye damage.

Skin sensitization, Sub-category 1B H317:

May cause an allergic skin reaction.

Short-term (acute) aquatic hazard, H400:

Category 1 Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, H410:

Category 1 Very toxic to aquatic life with long lasting effects.

SDS Number:100000068741 3/21

Version 5.0 Revision Date 2025-09-02

2.2

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms









Signal Word : Danger

Hazard Statements : H224 Extremely flammable liquid and vapor.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H331 Toxic if inhaled.

H410 Very toxic to aquatic life with long lasting

effects.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.
P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eve protection/ face protection/ hearing

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep

container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

Hazardous ingredients which must be listed on the label:

• 75-08-1 Ethyl Mercaptan

2.3

Other hazards

Results of PBT and vPvB

assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1%

or higher.

Endocrine disrupting

properties

: The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

SDS Number:100000068741

Version 5.0 Revision Date 2025-09-02

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Synonyms **ETSH**

> Ethanethiol Ethyl Mercaptan

Molecular formula C2H6S

Hazardous ingredients

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]	Specific Conc. Limits, M-factors and ATEs
Ethyl Mercaptan	75-08-1 200-837-3 016-022-00-9	Flam. Liq. 1; H224 Acute Tox. 4; H302 Acute Tox. 3; H331 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	99 - 100	ATE 682 mg/kg ATE vapor 7,14 mg/l M [Acute]=10 M [Chronic]=10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1

Description of first-aid measures

General advice : Move out of dangerous area. Consult a physician. Show this

material safety data sheet to the doctor in attendance. Material

may produce a serious, potentially fatal pneumonia if

swallowed or vomited.

If inhaled : Call a physician or poison control center immediately. If

unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact Small amounts splashed into eyes can cause irreversible

> tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye

wide open while rinsing. If eye irritation persists, consult a

specialist.

If swallowed Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

SDS Number:100000068741 5/21

Version 5.0 Revision Date 2025-09-02

4.2 Most important symptoms and effects, both acute and delayed Notes to physician

Symptoms : No data available.

Risks : No data available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No data available.

SECTION 5: Firefighting measures

Flash point : -48°C (-54°F)

Method: ASTM D 93

Autoignition temperature : 295°C (563°F)

5.1

Extinguishing media

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

5.2

Special hazards arising from the substance or mixture

fighting

Specific hazards during fire : Do not allow run-off from fire fighting to enter drains or water

courses.

5.3

Advice for firefighters

Special protective

equipment for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case

of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed

containers.

Fire and explosion

protection

: Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Hazardous decomposition

products

: Carbon oxides. Sulfur oxides.

SECTION 6: Accidental release measures

6.1

Personal precautions, protective equipment and emergency procedures

SDS Number:100000068741 6/21

Version 5.0 Revision Date 2025-09-02

Personal precautions : Use personal protective equipment. Ensure adequate

ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low

areas.

6.2

Environmental precautions

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

6.3

Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

6.4

Reference to other sections

Reference to other sections : For personal protection see section 8. For disposal

considerations see section 13.

SECTION 7: Handling and storage

7.1

Precautions for safe handling Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any

process in which this mixture is being used.

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

7.2

Conditions for safe storage, including any incompatibilities

Storage

Requirements for storage areas and containers

: Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical

SDS Number:100000068741 7/21

Version 5.0 Revision Date 2025-09-02

installations / working materials must comply with the

technological safety standards.

Uses advised against : This material should not be used for purposes other than the

identified uses in section 1 without expert advice.

SECTION 8: Exposure controls/personal protection

R	1

SDS Number:100000068741

Control parameters Ingredients with workplace control parameters

Zložky Ethyl Mercaptan	Podstata	Hodnota	Kontrolné parametre	Poznámka
Etnyi wercaptan		NDEL sedement	0.5 4.0	
	SK OEL SK OEL	NPEL priemerný NPEL krátkodobý	0,5 ppm, 1,3 mg/m3 1 ppm, 2,6 mg/m3	
	SK OEL	INFEL KIAIKOOODY	i ppiii, 2,6 ilig/ilis	
61				
Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
Ethyl Mercaptan	SI OEL	MV	0,5 ppm, 1,3 mg/m3	
	SI OEL	KTV	1 ppm, 2,6 mg/m3	
RO				
Componente	Sursă	Valoare	Parametri de control	Notă
Ethyl Mercaptan	RO OEL	STEL	1 mg/m3	
•			1 3 -	1
PT				
Componentes	Base	Valor	Parâmetros de controle	Nota
Ethyl Mercaptan	PT OEL	VLE-MP	0,5 ppm,	
PL Składniki	Podstawa	Wartość	Parametry dotyczące	Uwaga
ONIAUTIINI	Fousiawa	v v ai tusu	kontroli	Owaya
Ethyl Mercaptan	PL NDS	NDS	1 mg/m3	
y	PL NDS	NDSch	2 mg/m3	
	•	•	1 0	
10		1	1.4	T
Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
Ethyl Mercaptan	FOR-2011-12-06- 1358	GV	0,5 ppm, 1 mg/m3	
	1000	1		I
1K		•		
Съставки	Основа	Стойност	Параметри на	Бележка
Ed. 184	144.051	100	контрол	
Ethyl Mercaptan	MK OEL	MV	0,5 ppm, 1,3 mg/m3	
.V				
Sastāvdalas	Bāze	Vērtība	Kontroles parametri	Piezīme
Ethyl Mercaptan	LV OEL	AER 8 st	1 mg/m3	
T	Ŏ-w	11	17 to - 11	D1.1
Komponentai Ethyl Marganton	Šaltinis LT OEL	Vertė	Kontrolės parametrai	Pastaba
Ethyl Mercaptan O patekimas per nepat	_	IPRD	1 mg/m3	Ο,
O patekililas per liepa.	zoisią uuą			
S		_	_	
Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
Ethyl Mercaptan	IS OEL	TWA	0,5 ppm, 1 mg/m3	
E				
Components	Basis	Value	Control parameters	Note
Ethyl Mercaptan	IE OEL	OELV - 8 hrs (TWA)	0,5 ppm,	NOLE
Lary, Moroaptari	I IL OLL	JEEV OIII3 (TVVA)	υ,υ ρριτι,	I.
1 U				
Komponensek	Bázis	Érték	Ellenőrzési	Megjegyzés
		AK-érték	paraméterek	
Ethyl Mercaptan	HU OEL		0,5 ppm, 1 mg/m3	N, i,

8/21

			SAFE	TY DATA SHEET
Scentinel® A Ga	s Odorant			
Version 5.0			Revision	Date 2025-09-02
N Irritáló anyagok,	egyszerű fojtógázok, csekély eg	gészségkárosító hatással t	oíró anyagok. Korrekció NEM sz	ükséges.
HR				
Sastojci	Temelj	Vrijednost	Nadzorni parametri	Bilješka
Ethyl Mercaptan	HR OEL	GVI	0,5 ppm, 1,3 mg/m3	
	HR OEL	KGVI	2 ppm, 5,2 mg/m3	
GR				
Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
Ethyl Mercaptan	GR OEL	TWA	10 ppm, 25 mg/m3	
	GR OEL	STEL	10 ppm, 25 mg/m3	
GB				
Components	Basis	Value	Control parameters	Note
Ethyl Mercaptan	GB EH40	TWA	0,5 ppm, 1,3 mg/m3	
	GB EH40	STEL	2 ppm, 5,2 mg/m3	
FR				
Composants	Base	Valeur	Paramètres de	Note
			contrôle	
Ethyl Mercaptan	FR VLE	VME	0,5 ppm, 1 mg/m3	Valeurs limites admises (circulaires),
Valeurs limites Valeurs limites a admises (circulaires)	dmises (circulaires)			(onodianeo),
FI				
Aineosat	Peruste	Arvo	Valvontaa koskevat	Huomautus
			muuttujat	
Ethyl Mercaptan	FIOEL	HTP-arvot 15 min	0,5 ppm, 1,3 mg/m3	
ES				
Componentes	Base	Valor	Parámetros de control	Nota
Ethyl Mercaptan	ES VLA	VLA-ED	0,5 ppm, 1,3 mg/m3	
	<u>.</u>		·	
Komponendid cood	Alunad	Väärtus	Kantrallinaramaatrid	Märkusad
Komponendid, osad Ethyl Mercaptan	Alused EE OEL	Väärtus Piirnorm	Kontrolliparameetrid 0,5 ppm, 1 mg/m3	Märkused C,
C Kantserogeense	_	FIIIIIOIIII	0,5 ppm, 1 mg/m5	O,
DK				
Komponenter	Basis	Værdi	Kontrolparametre	Note
Ethyl Mercaptan	DK OEL	GV	0,5 ppm, 1 mg/m3	
·	DK OEL	S	1 ppm, 2 mg/m3	
DE				
Inhaltsstoffe	Grundlage	Wert	Zu überwachende	Bemerkung
Illianssione	Grundlage	VVEIL	Parameter	Demerkung
Ethyl Mercaptan	DE TRGS 900	AGW	0,5 ppm, 1,3 mg/m3	Н,
	DE DFG MAK	MAK	0,5 ppm, 1,3 mg/m3	H, D,
D Für die Beurteilur Daten vor oder d H Hautresorptiv	ng der fruchtschädigenden Wirk lie vorliegenden Daten reichen f	kung ggf. inklusive der entv ür eine Einstufung in eine	wicklungsneurotoxischen Wirkur der Gruppen A, B oder C nicht a	ng liegen entweder keine aus
СН	ı			1
Inhaltsstoffe	Grundlage	Wert	Zu überwachende	Bemerkung
Ed. 184	011.0111/4	******	Parameter	
Ethyl Mercaptan	CH SUVA CH SUVA	MAK-Wert KZGW	0,5 ppm, 1,3 mg/m3 1 ppm, 2,6 mg/m3	
	CH SUVA	NZGVV	1 ppm, 2,6 mg/m3	
BG				
Съставки	Основа	Стойност	Параметри на контрол	Бележка
	BG OEL	TWA	1 mg/m3	
Ethyl Mercaptan				
·				
BE	Rasis	Waarde	Controlenarameters	Opmerking
BE Bestanddelen	Basis BE OEL	Waarde TGG 8 hr	Controleparameters 0,5 ppm, 1,3 mg/m3	Opmerking
BE Bestanddelen Ethyl Mercaptan		Waarde TGG 8 hr	Controleparameters 0,5 ppm, 1,3 mg/m3	Opmerking
BE Bestanddelen Ethyl Mercaptan	BE OEL	TGG 8 hr	0,5 ppm, 1,3 mg/m3	
BE Bestanddelen Ethyl Mercaptan			0,5 ppm, 1,3 mg/m3 Zu überwachende	Opmerking Bemerkung
BE Bestanddelen Ethyl Mercaptan AT Inhaltsstoffe	BE OEL Grundlage	TGG 8 hr Wert	0,5 ppm, 1,3 mg/m3 Zu überwachende Parameter	
BE Bestanddelen Ethyl Mercaptan	BE OEL	TGG 8 hr	0,5 ppm, 1,3 mg/m3 Zu überwachende	

DNEL : End Use: Workers

SDS Number:100000068741 9/21

Version 5.0 Revision Date 2025-09-02

Routes of exposure: Inhalation

Potential health effects: Chronic effects, Systemic effects

Value: 14,5 mg/m3

DNEL : End Use: Workers

Routes of exposure: Skin contact

Potential health effects: Chronic effects, Systemic effects

Value: 2,06 mg/kg

DNEL : End Use: Workers

Routes of exposure: Inhalation

Potential health effects: Chronic effects, Local effects

Value: 18,6 mg/m3

PNEC : Fresh water

Value: 0,0001 mg/l

PNEC : Marine water

Value: 0,00001 mg/l

PNEC : Fresh water sediment

Value: 0,00049 mg/kg

PNEC : Marine sediment

Value: 0,000049 mg/kg

PNEC : Soil

Value: 0,000039 mg/kg

8.2

Exposure controls Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to

maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Full-Face Supplied-Air Respirator. A positive pressure, air-supplying respirator may be appropriate if there is potential for

uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators

may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe

SDS Number:100000068741 10/21

Version 5.0 Revision Date 2025-09-02

the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Remove and wash contaminated clothing before re-use. Skin should be washed after contact. Complete head face and neck protection. Rubber apron. Footwear protecting against chemicals.

Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not

eat or drink. When using do not smoke. Wash hands before

breaks and immediately after handling the product.

For additional details, see the Exposure Scenario in the Annex portion

SECTION 9: Physical and chemical properties

9.1

Information on basic physical and chemical properties

Appearance

Form : liquid
Physical state : liquid
Color : Colorless
Odor : Repulsive

Safety data

Flash point : -48° C (-54° F)

Method: ASTM D 93

Lower explosion limit : 2,8 %(V)

Upper explosion limit : 18 %(V)

Oxidizing properties : No

Autoignition temperature : 295°C (563°F)

Molecular formula : C2H6S

Molecular weight : 62,14 g/mol

pH : Not applicable

Pour point : No data available

Initial boiling point and boiling : 35°C (95°F)

range

Vapor pressure : 16,20 PSI

SDS Number:100000068741 11/21

Scentinel® A Gas Odorant

Version 5.0 Revision Date 2025-09-02

at 37,8°C (100,0°F)

Relative density : 0,84

at 15,6 °C (60,1 °F)

Water solubility : negligible

Partition coefficient: n-

: No data available

octanol/water

Viscosity, kinematic : No data available

Relative vapor density : 2,1

(Air = 1.0)

Evaporation rate : 1

Percent volatile : > 99 %

9.2

Other information

Conductivity : No data available

SECTION 10: Stability and reactivity

10.1

Reactivity : Stable under recommended storage conditions.

10.2

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

10.3

Possibility of hazardous reactions

Hazardous reactions : Hazardous reactions: Hazardous polymerization does not

occur.

Hazardous reactions: Vapors may form explosive mixture with

air.

10.4

Conditions to avoid : Heat, flames and sparks.

10.5

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

10.6

Hazardous decomposition

products

: Carbon oxides Sulfur oxides

SDS Number:100000068741 12/21

Scentinel® A Gas Odorant

Version 5.0 Revision Date 2025-09-02

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1

Information on toxicological effects

Acute oral toxicity

Ethyl Mercaptan : LD50: 682 mg/kg

Species: Rat Sex: male

Method: Fixed Dose Method

Acute toxicity estimate: 682 mg/kg

Method: ATE value derived from LD50/LC50 value

Acute inhalation toxicity

Ethyl Mercaptan : LC50: 11,23 mg/l

Exposure time: 4 h Species: Rat Sex: male

Test atmosphere: vapor

LC50: 7,14 mg/l Exposure time: 4 h Species: Mouse

Sex: male

Test atmosphere: vapor

Acute toxicity estimate: 7,14 mg/l

Test atmosphere: vapor

Method: ATE value derived from LD50/LC50 value

Skin irritation

Ethyl Mercaptan : slight irritation.

Scentinel® A Gas Odorant

Eye irritation : May cause irreversible eye damage.

Scentinel® A Gas Odorant

Sensitization : Causes sensitization.

Repeated dose toxicity

Ethyl Mercaptan : Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 25, 100, 400 ppm Exposure time: 13 wks

Number of exposures: 6 hr/d, 5 d/wk

NOEL: 100 ppm

Lowest observable effect level: 400 ppm

Method: OECD Guideline 413

Information given is based on data obtained from similar

substances.

SDS Number:100000068741 13/21

Version 5.0 Revision Date 2025-09-02

Species: Rat, Male and female

Sex: Male and female Application Route: Oral Dose: 0, 10, 50, 200 mg/kg Exposure time: 42-53 days

NOEL: 50 mg/kg

Method: OECD Guideline 422

Information given is based on data obtained from similar

substances.

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 9, 97, 196 ppm Exposure time: 13 wks

Number of exposures: 6 hr/d, 5 d/wk

NOEL: >=196 ppm

Method: OECD Guideline 413

Information given is based on data obtained from similar

substances.

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0.03, 0.26, 0.55 mg/L

Exposure time: 13 wks

Number of exposures: 6 hr/d, 5 d/wk

NOEL: 0,03 mg/l

Method: OECD Test Guideline 413

Information given is based on data obtained from similar

substances.

Genotoxicity in vitro

Ethyl Mercaptan : Test Type: Ames test

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Escherichia coli - reverse mutation

assay)

Result: negative

Test Type: Mouse lymphoma assay Method: OECD Guideline 476

Result: Ambiguous

Test Type: Sister Chromatid Exchange Assay

Metabolic activation: with and without metabolic activation

Result: positive

Test Type: Micronucleus test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

Genotoxicity in vivo

Ethyl Mercaptan : Test Type: Micronucleus test

Species: Mouse

Method: Mutagenicity (micronucleus test)

SDS Number:100000068741 14/21

Version 5.0 Revision Date 2025-09-02

Result: negative

Reproductive toxicity

Ethyl Mercaptan : Species: Rat

Sex: male and female Application Route: Oral diet Dose: 0, 10, 50, 200 mg/kg Exposure time: 42-53 days Number of exposures: once daily Method: OECD Guideline 422 NOAEL Parent: 200 mg/kg NOAEL F1: 50 mg/kg

Information given is based on data obtained from similar

substances.

Developmental Toxicity

Ethyl Mercaptan : Species: Rat

Application Route: Inhalation Dose: 0, 0.037, 0.28, or 0.56 mg/L Number of exposures: 6 hrs/d

Test period: GD 6-19

Method: OECD Guideline 414 NOAEL Teratogenicity: > 0,56 mg/l

Information given is based on data obtained from similar

substances.

Species: Rat

Application Route: Inhalation Dose: 0, 10, 100, 200 ppm Number of exposures: 6 hrs/d

Test period: GD 6-19

Method: OECD Guideline 414 NOAEL Teratogenicity: > 200 ppm NOAEL Maternal: > 200 ppm

Information given is based on data obtained from similar

substances.

Aspiration toxicity

Ethyl Mercaptan : May be harmful if swallowed and enters airways.

CMR effects

Ethyl Mercaptan : Carcinogenicity: Not available

Mutagenicity: Not mutagenic in Ames Test.

Teratogenicity: Animal testing did not show any effects on

fetal development.

Reproductive toxicity: Animal testing did not show any effects

on fertility.

11.2

Information on other hazards

Scentinel® A Gas Odorant

Further information : Solvents may degrease the skin. Inhalation of high vapor

concentrations may cause symptoms like headache,

dizziness, tiredness, nausea and vomiting.

SDS Number:100000068741 15/21

Version 5.0 Revision Date 2025-09-02

Endocrine disrupting

properties

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1

Toxicity

Toxicity to fish

Ethyl Mercaptan : 2,4 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

Ethyl Mercaptan : EC50: < 0,1 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

Toxicity to algae

Ethyl Mercaptan : EC50: 3 mg/l

Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (green algae)

Method: OECD Test Guideline 201

M-Factor

ethanethiol : M-Factor (Acute Aquat. Tox.) 10

M-Factor (Chron. Aquat. Tox.) 10

12.2

Persistence and degradability

Biodegradability

Ethyl Mercaptan : aerobic

Result: Not readily biodegradable.

0 %

Testing period: 29 d

Method: OECD Test Guideline 301F

12.3

Bioaccumulative potential

Elimination information (persistence and degradability)

Bioaccumulation : This material is not expected to bioaccumulate.

SDS Number:100000068741 16/21

Version 5.0 Revision Date 2025-09-02

12.4

Mobility in soil

Mobility

Ethyl Mercaptan : The product will be dispersed amongst the various

environmental compartments (soil/ water/ air).

12.5

Results of PBT and vPvB assessment

Results of PBT assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6

Endocrine disrupting properties

Endocrine disrupting

properties

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7

Other adverse effects

Additional ecological

information

: Very toxic to aquatic life with long lasting effects.

12.8

Additional Information

Ecotoxicology Assessment

Short-term (acute) aquatic hazard

Ethyl Mercaptan : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard

Ethyl Mercaptan : Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1

Waste treatment methods

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

SDS Number:100000068741 17/21

Scentinel® A Gas Odorant

Version 5.0 Revision Date 2025-09-02

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

For additional details, see the Exposure Scenario in the Annex portion

SECTION 14: Transport information

14.1 - 14.7

Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN2363, ETHYL MERCAPTAN, 3, I, MARINE POLLUTANT, (ETHYL MERCAPTAN)

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN2363, ETHYL MERCAPTAN, 3, I, (-48 °C c.c.), MARINE POLLUTANT, (ETHYL MERCAPTAN)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2363, ETHYL MERCAPTAN, 3, I

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2363, ETHYL MERCAPTAN, 3, I, (D/E), ENVIRONMENTALLY HAZARDOUS, (ETHYL MERCAPTAN)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

33,UN2363,ETHYL MERCAPTAN, 3, I, ENVIRONMENTALLY HAZARDOUS, (ETHYL MERCAPTAN)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2363, ETHYL MERCAPTAN, 3, I, ENVIRONMENTALLY HAZARDOUS, (ETHYL MERCAPTAN)

Maritime transport in bulk according to IMO instruments

SDS Number:100000068741 18/21

Version 5.0 Revision Date 2025-09-02

SECTION 15: Regulatory information

15.1

Safety, health and environmental regulations/legislation specific for the substance or mixture **National legislation**

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Water hazard class

(Germany)

: WGK 3 highly hazardous to water

15.2

Chemical Safety Assessment

A Chemical Safety Assessment 200-837-3 Components : ethanethiol

has been carried out for this

substance.

Major Accident Hazard

Legislation

Update: 2003 : 96/82/EC

Highly flammable

Quantity 1: 5.000 t Quantity 2: 50.000 t

96/82/EC Update: 2003 Dangerous for the environment

Quantity 1: 100 t Quantity 2: 200 t

: ZEU_SEVES3 Update: FLAMMABLE LIQUIDS

P5a

Quantity 1: 10 t Quantity 2: 50 t

: ZEU SEVES3 Update: **ENVIRONMENTAL HAZARDS**

E1

Quantity 1: 100 t Quantity 2: 200 t

Notification status

Europe REACH This product is in full compliance according to REACH

regulation 1907/2006/EC.

Switzerland CH INV On the inventory, or in compliance with the inventory On or in compliance with the active portion of the United States of America (USA)

TSCA TSCA inventory

Canada DSL All components of this product are on the Canadian

Australia AIIC On the inventory, or in compliance with the inventory New Zealand NZIoC On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory Japan ENCS On the inventory, or in compliance with the inventory Japan ISHL Korea KECI All substances in this product were registered, notified

to be registered, or exempted from registration by

19/21 SDS Number:100000068741

Scentinel® A Gas Odorant

Version 5.0 Revision Date 2025-09-02

CPChem through an Only Representative according to K-REACH regulations. Importation of this product is permitted if the Korean Importer of Record was included on CPChem's notifications or if the Importer of

Record themselves notified the substances.

Philippines PICCS : On the inventory, or in compliance with the inventory China IECSC : On the inventory, or in compliance with the inventory Taiwan TCSI : On the inventory, or in compliance with the inventory Other TECI : On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 3

Fire Hazard: 4 Reactivity Hazard: 0



Further information

Legacy SDS Number : 25580

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Ke	y or legend to abbreviations and a	cronyms used in	the safety data sheet
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances

SDS Number:100000068741 20/21

Scentinel® A Gas Odorant

Version 5.0 Revision Date 2025-09-02

MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

Full text of H-Statements referred to under sections 2 and 3.

H224	Extremely flammable liquid and vapor.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SDS Number:100000068741 21/21