

**TrusTec™ Diesel Reference Fuel T-36**

Version 2.2

Revision Date 2025-10-23

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : TrusTec™ Diesel Reference Fuel T-36
Material : 1024272, 1108916, 1024276, 1024273, 1024274, 1024275,
1032194

Use : Reference Fuel
Uses advised against : This material should not be used for purposes other than the
identified uses in section 1 without expert advice.

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
9500 Lakeside Blvd.
The Woodlands, TX 77381

Local : See Company Address

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Iceland: 543 2222 (24 hours/day, 7 days/week)
 Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;
 Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)
 Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Lithuania: +370 (85) 2362052
 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)
 Malta: +356 2395 2000
 The Netherlands: NVIC: +31 (0)88 755 8000
 Norway: 22 59 13 00 (24 hours/day, 7 days/week)
 Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Portugal: CIAV phone number: +351 800 250 250
 Romania: +40213183606
 Slovakia: +421 2 5477 4166
 Slovenia: Phone number: 112
 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)
 Sweden: 112 – ask for Poisons Information

Organization that prepared the SDS : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification

Classification of the substance or mixture
GHS Classification and labelling according to JIS Z 7252-2019 and JIS Z 7253-2019 (GHS 2015)

Classification

: Acute toxicity, Category 4, Inhalation
 Skin corrosion/irritation, Category 2
 Carcinogenicity, Category 2
 Specific target organ toxicity - repeated exposure, Category 2, Liver, Blood, thymus
 Aspiration hazard, Category 1
 Short-term (acute) aquatic hazard, Category 2
 Long-term (chronic) aquatic hazard, Category 2

Labeling

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Symbol(s)	:	  
Signal Word	:	Danger
Hazard Statements	:	H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H332: Harmful if inhaled. H351: Suspected of causing cancer. H373: May cause damage to organs (Liver, Blood, thymus) through prolonged or repeated exposure. H411: Toxic to aquatic life with long lasting effects.
Precautionary Statements	:	Prevention: P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P260: Do not breathe mist or vapors. P264: Wash skin thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P273: Avoid release to the environment. P280: Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302 + P352: IF ON SKIN: Wash with plenty of water. P304 + P340 + P312: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P308 + P313: IF exposed or concerned: Get medical advice/ attention. P331: Do NOT induce vomiting. P332 + P313: If skin irritation occurs: Get medical advice/ attention. P391: Collect spillage. Storage: P405: Store locked up. Disposal: P501: Dispose of contents/ container to an approved waste disposal plant.

SECTION 3: Composition/information on ingredients

Synonyms : Diesel Reference Fuel T

Molecular formula : Mixture

Chemical name	CAS-No.	Concentration	ENCS/ISHL number
Diesel fuel, no. 2	68476-34-6	100%	(9)-1702
Naphthalene	91-20-3	0 % - 1%	4-311

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

SECTION 4: First aid measures

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Notes to physician

- Symptoms : No information available.
- Risks : No information available.
- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

- Flash point : 99.9°C (211.8°F)
Method: closed cup
- Autoignition temperature : No data available
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Fire and explosion protection : Normal measures for preventive fire protection.
- Hazardous decomposition products : Hydrocarbons. Carbon oxides.

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Storage

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Uses advised against : This material should not be used for purposes other than the identified uses in section 1 without expert advice.
- Use : Reference Fuel

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters**

JP

Components	Basis	Value	Control parameters	Note
Naphthalene	JP OEL ISHL	ACL	10 ppm,	
n-hexane	JP OEL ISHL	ACL	40 ppm,	
	JP OEL JSOH	OEL-M	40 ppm, 140 mg/m3	S,
Cumene	JP OEL JSOH	OEL-M	10 ppm, 50 mg/m3	S, 2B,
	JP ISHL OEL 577-2(2)	8h-OEL-M	10 ppm,	
Toluene	JP OEL ISHL	ACL	20 ppm,	
	JP OEL JSOH	OEL-M	50 ppm, 188 mg/m3	1, S,
Ethylbenzene	JP OEL JSOH	OEL-M	20 ppm, 87 mg/m3	2, S, 2B,
	JP OEL ISHL	ACL	20 ppm,	

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Benzene	JP OEL ISHL	ACL	1 ppm,	
	JP OEL JSOH	REF-Carc	1 ppm,	S, 1,
	JP OEL JSOH	REF-Carc	0.1 ppm,	S, 1,

- 1 Group 1: carcinogenic to humans
 2 Group 2: Substances presumed to cause reproductive toxicity in humans
 2B Group 2B: possibly carcinogenic to humans
 S Skin absorption

Biological exposure indices**JP**

Substance name	CAS-No.	Control parameters	Sampling time	Update
Toluene	108-88-3	Toluene: 0.6 mg/l In setting OEL-B, consideration is given to the relationship between biological monitoring values and OEL-Ms. (Blood)	Within 2 h prior to end of shift at end of work week	2023-09-25
		Toluene: 0.06 mg/l In setting OEL-B, consideration is given to the relationship between biological monitoring values and OEL-Ms. (Urine)	Within 2 h prior to end of shift at end of work week	2023-09-25
Ethylbenzene	100-41-4	Mandelic acid + Phenylglyoxylic acid: 200 mg/g creatinine In setting OEL-B, consideration is given to the relationship between biological monitoring values and OEL-Ms. (Urine)	End of shift at end of workweek	2023-09-25
		Mandelic acid: 150 mg/g creatinine In setting OEL-B, consideration is given to the relationship between biological monitoring values and OEL-Ms. (Urine)	End of shift	2023-09-25
		Ethylbenzene: 15 µg/l In setting OEL-B, consideration is given to the relationship between biological monitoring values and OEL-Ms. (Urine)	End of shift	2023-09-25
n-hexane	110-54-3	2,5-Hexanedione - after acid hydrolysis: 3 mg/g creatinine (Urine)	End of shift at weekend	2011-05-18
		2,5-Hexanedione - after acid hydrolysis: 0.3 mg/g creatinine (Urine)	End of shift at weekend	2011-05-18
		2,5-Hexanedione - after acid hydrolysis: 3 mg/g creatinine After acid hydrolysis (Urine) In setting OEL-B, consideration is given to the relationship between biological monitoring values and OEL-Ms. ()	End of shift at weekend	2023-09-25
		2,5-Hexanedione - without acid hydrolysis: 0.3 mg/g creatinine Without acid hydrolysis (Urine) In setting OEL-B, consideration is given to the relationship between biological monitoring values and OEL-Ms. ()	End of shift at weekend	2023-09-25

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Personal protective equipment

- Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Protective suit. Safety shoes.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Form : liquid
- Physical state : liquid at 20°C (68°F)
(101.30 kPa)
- Color : Pale yellow, Brown
- Odor : Mild

Safety data

- Flash point : 99.9°C (211.8°F)
Method: closed cup
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Oxidizing properties : No

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Autoignition temperature	: No data available
Thermal decomposition	: No data available
Molecular formula	: Mixture
Molecular weight	: Not applicable
pH	: Not applicable
Pour point	: -6.7°C (19.9°F) Method: ASTM D97
Boiling point/boiling range	: 222-366°C (432-691°F) Method: ASTM D 86
Vapor pressure	: 0.10 kPa at 40°C (104°F)
Relative density	: 0.8101
Density	: 6.76 g/cm3
Bulk density	: 6.75 L/G
Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: 3.088 cSt at 40°C (104°F)
Relative vapor density	: No data available
Evaporation rate	: No data available
Percent volatile	: > 99 %
Conductivity	: No data available

SECTION 10: Stability and reactivity

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur.
Conditions to avoid	: No data available.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Thermal decomposition	: No data available
Hazardous decomposition products	: Hydrocarbons Carbon oxides
Other data	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

Diesel fuel, no. 2 : LD50: > 5,000 mg/kg
Species: Rat
Sex: male and female
Method: OECD Test Guideline 401

Naphthalene : LD50: 500 mg/kg
Method: Converted acute toxicity point estimate

Acute inhalation toxicity

Diesel fuel, no. 2 : LC50: 4.1 mg/l
Exposure time: 4 h
Species: Rat
Sex: male and female
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Test substance: yes

Acute dermal toxicity

Diesel fuel, no. 2 : LD50 Dermal: > 4,300 mg/kg
Species: Rabbit
Sex: male and female
Test substance: yes

TrusTec™ Diesel Reference Fuel T-36

Skin irritation : Skin irritation

May cause skin irritation in susceptible persons.

TrusTec™ Diesel Reference Fuel T-36

Eye irritation : Vapors may cause irritation to the eyes, respiratory system and the skin.

TrusTec™ Diesel Reference Fuel T-36

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Sensitization : Did not cause sensitization on laboratory animals.

Repeated dose toxicity

Diesel fuel, no. 2 : Species: Rat, Male and female
Sex: Male and female
Application Route: Dermal
Dose: 0, 30, 125, 500 mg/kg
Exposure time: 13 wks
Number of exposures: daily, 5 days/week
NOEL: 30 mg/kg
Method: OECD Guideline 411
Target Organs: Thymus, Liver, Bone marrow
Information given is based on data obtained from similar substances.

Species: Rat, Male and female
Sex: Male and female
Application Route: inhalation (dust/mist/fume)
Dose: 0, 0.35, 0.88, 1.71 mg/l
Exposure time: 13 wks
Number of exposures: Twice/wk
NOEL: > 1.71 mg/l
Method: OECD Guideline 413

Genotoxicity in vitro

Diesel fuel, no. 2 : Test Type: Ames test
Result: positive

Test Type: Mouse lymphoma assay
Result: negative

Naphthalene : Test Type: Ames test
Result: negative

Test Type: Sister Chromatid Exchange Assay
Result: negative

Test Type: Unscheduled DNA synthesis assay
Result: negative

Genotoxicity in vivo

Diesel fuel, no. 2 : Test Type: Dominant lethal assay
Species: Mouse
Dose: 100 or 400 ppm
Result: negative

Naphthalene : Test Type: Mouse micronucleus assay
Result: negative

Carcinogenicity

Diesel fuel, no. 2 : Species: Mouse
Sex: male
Dose: 0, 25 ul
Exposure time: lifetime

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Naphthalene

Number of exposures: 3 times/wk
Remarks: Moderate dermal carcinogen

Species: Mouse
Sex: male
Dose: 10, 30 ppm
Exposure time: 105 weeks
Number of exposures: 6 hours/day, 5 days/week
Test substance: yes
Print Date: No information available.
Remarks: No evidence of carcinogenicity

Species: Mouse
Sex: female
Dose: 10, 30 ppm
Exposure time: 105 weeks
Number of exposures: 6 hours/day, 5 days/week
Test substance: yes
Print Date: No information available.
Remarks: increased incidence of alveolar/bronchiolar adenomas

Species: Rat
Sex: male and female
Dose: 10, 30, 60 ppm
Exposure time: 105 weeks
Number of exposures: 6 hours/day, 5 days/week
Test substance: yes
Print Date: No information available.
Remarks: nose respiratory epithelial adenoma, increased incidence of olfactory neuroblastomas

Developmental Toxicity

Diesel fuel, no. 2

: Species: Rat
Application Route: Inhalation
Dose: 0, 86.9, 408.8 ppm
Number of exposures: 6 h/d
Test period: GD 6-15
Method: OECD Guideline 414
NOAEL Teratogenicity: 408.8 ppm
NOAEL Maternal: 408.8 ppm
Information given is based on data obtained from similar substances.

Species: Rat
Application Route: Dermal
Dose: 30, 125, 500, 1000 mg/kg
Exposure time: daily
Test period: GD 0-20
Method: OECD Guideline 414
NOAEL Teratogenicity: 125 mg/kg
Information given is based on data obtained from similar substances.

Naphthalene

Species: Rabbit
Application Route: oral gavage
Dose: 40, 200, 400 mg/kg
Test period: 29 d, GD 6-18

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

NOAEL Teratogenicity: 400 mg/kg

TrusTec™ Diesel Reference Fuel T-36**Aspiration toxicity** : May be fatal if swallowed and enters airways.**CMR effects**

Diesel fuel, no. 2 : Carcinogenicity: Limited evidence of carcinogenicity in animal studies
Teratogenicity: Animal testing did not show any effects on fetal development.

Naphthalene Carcinogenicity: Limited evidence of carcinogenicity in animal studies

TrusTec™ Diesel Reference Fuel T-36**Further information** : Solvents may degrease the skin.**SECTION 12: Ecological information****Toxicity to fish**

Diesel fuel, no. 2 : LL50: 21 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
semi-static test Method: OECD Test Guideline 203

Naphthalene LC50: 3.2 mg/l
Exposure time: 96 h
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates

Diesel fuel, no. 2 : EC50: 2 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

Naphthalene LC50: 2.16 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

Toxicity to algae

Diesel fuel, no. 2 : ErL50: 22 mg/l
Exposure time: 72 h
Species: Raphidocellus subcapitata (algae)
static test Analytical monitoring: no
Method: OECD Test Guideline 201

Naphthalene EC50: 2.96 mg/l
Exposure time: 48 h
Species: Selenastrum capricornutum (algae)

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Biodegradability

Diesel fuel, no. 2 : aerobic
Result: Not readily biodegradable.
57.5 %
Testing period: 28 d
Method: OECD Test Guideline 301F

Bioaccumulation

Diesel fuel, no. 2 : Accumulation in aquatic organisms is expected.

Mobility

Diesel fuel, no. 2 : No data available

Results of PBT assessment

Diesel fuel, no. 2 : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : Toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Toxic to aquatic life.

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIESEL FUEL), 9, III, (99.9 °C c.c.), MARINE POLLUTANT, (DIESEL FUEL)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIESEL FUEL), 9, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1202, DIESEL FUEL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

30, UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information**National legislation****Poisonous and Deleterious Substances Control Law**

: Not applicable

Industrial Safety and Health Law

Substances Subject to be : naphthalene(408)
Notified Names Law Article
57-2 (Ministerial Order Article
34-2 Appended Table 2)
Enforcement Order of the :
Industrial Safety and Health
Law - Attached table 1
(Dangerous Substances)

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Harmful Substances Required : Not applicable
 Permission for Manufacture
 Hazardous Substances : Not applicable
 Subject to Labeling
 Requirements
 Ordinance on Prevention of : Not applicable
 Organic Solvent Poisoning
 Ordinance on Prevention of : Not applicable
 Lead Poisoning
 Harmful Substances : Not applicable
 Prohibited from Manufacture
 Ordinance on Prevention of : Not applicable
 Hazards Due to Specified
 Chemical Substances
 Ordinance on Prevention of : Not applicable
 Tetraalkyl Lead Poisoning
 : Not applicable
 : Not applicable

Substances Prevented From : Not applicable
 Impairment of Health Listed

Chemical Substance Control Law

Priority Assessment Chemical : naphthalene(76)
 Substance n-hexane(3)
 cumene(126)
 toluene(46)
 ethylbenzene(50)
 Benzene(45)

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

: Not applicable

Other regulations

Fire Service Law : Flammable liquids
 Type 3 petroleums
 Hazardous rank III

High Pressure Gas Safety Act : Not applicable

Explosive Control Law : Not applicable

Vessel Safety Law : Miscellaneous dangerous substances and articles (Article 2
 and 3 of rules on shipping and storage of dangerous goods and
 its Attached Table 1)

Aviation Law : Miscellaneous dangerous substances and articles (Article 194
 of The Enforcement Rules of Aviation Law and its Attached
 Table 1)

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Notification status

Europe REACH	:	This product is in full compliance according to REACH regulation 1907/2006/EC.
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On or in compliance with the active portion of the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AIIC	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Japan ISHL	:	On the inventory, or in compliance with the inventory
Korea KECI	:	All substances in this product were registered, notified to be registered, or exempted from registration by CPChem through an Only Representative according to K-REACH regulations. Importation of this product is permitted if the Korean Importer of Record was included on CPChem's notifications or if the Importer of Record themselves notified the substances.
Philippines PICCS	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory
Other TECI	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information**Further information**

Legacy SDS Number : CPC00523

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate